

MATERIAL SAFETY DATA SHEET

050YE652-HMF GOLD

Version Number 1.0 Revision Date 04/23/2002 Page 1 of 8 Print Date 11/4/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902	
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).	
Product name	:	050YE652-HMF GOLD	
Product code	:	CC10014483	
Chemical Name	:	Mixture	
CAS-No.	:	Mixture	
Product Use	:	Industrial Applications	

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Carbon black	1333-86-4	0.1 - 1
2-Naphthalenecarboxylic acid,	7585-41-3	1 - 5
4-[(5-chloro-4-methyl-2-sulfophenyl)azo]-3-		
hydroxy-, barium salt (1:1)		
Calcium carbonate	1317-65-3	1 - 5
Titanium dioxide	13463-67-7	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating or crosslinking and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed.
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.



MATERIAL SAFETY DATA SHEET

050YE652-HMF GOLD

ion Number 1.0 sion Date 04/23/2002	Page Print Date 11/2
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists so medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	 Not applicable Not applicable Not relevant Carbon dioxide blanket, Water spray, dry powder, foam.
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positiv pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	: None
	5. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should red be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE



MATERIAL SAFETY DATA SHEET

050YE652-HMF GOLD

/ersion Number 1.0 Revision Date 04/23/2002		Page 3 of 8 Print Date 11/4/2011			
Handling	:	Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.			
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.			
8. EXI	POSUF	RE CONTROLS / PERSONAL PROTECTION			
Respiratory protection	:	No personal respiratory protective equipment normally required.			
Eye/Face Protection	:	Safety glasses with side-shields.			
Hand protection	:	Protective gloves.			
Skin and body protection	:	Long sleeved clothing.			
Additional Protective Measures	:	Safety shoes.			
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.			
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.			
Exposure limit(s)					



MATERIAL SAFETY DATA SHEET

050YE652-HMF GOLD

Version Number 1.0 Revision Date 04/23/2002

Page 4 of 8 Print Date 11/4/2011

: Not applicable.

: Not determined

: Not established

: Not applicable

: Not applicable

: Not applicable

Components	Value	Exposure time	Exposure type	List:
2-Naphthalenecarboxy lic acid, 4-[(5-chloro-4-methyl- 2-sulfophenyl)azo]-3-h ydroxy-, barium salt (1:1)	0.5 mg/m3	Time Weighted Average (TWA):	as Ba	ACGIH
2-Naphthalenecarboxy lic acid, 4-[(5-chloro-4-methyl- 2-sulfophenyl)azo]-3-h ydroxy-, barium salt (1:1)	0.5 mg/m3	PEL:	as Ba	OSHA Z1
Calcium carbonate	10 mg/m3	Time Weighted Average (TWA):	Total dust.	ACGIH
Calcium carbonate	5 mg/m3	PEL:	Respirable dust.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
Carbon black	3.5 mg/m3	Time Weighted Average (TWA):	Total dust. as carbon black	ACGIH
Carbon black	3.5 mg/m3	PEL:	Total dust. as carbon black	OSHA Z1
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):	Total dust.	ACGIH
Titanium dioxide	15 mg/m3	PEL:	Total dust.	OSHA Z1

9. PHYSICAL AND CHEMICAL PROPERTIES

Form Appearance Color Odor Melting point/range Boiling Point: Water solubility

Incompatible Materials

Hazardous decomposition

10. STABILITY AND REACTIVITY

Stability

products

: Stable.

: Solid

: Pellets

: YELLOW

: Very faint

: Insoluble

: Not determined

: Not applicable

Hazardous Polymerization : Conditions to avoid

Will not occur.

- Keep away from oxidizing agents and open flame. To avoid thermal : decomposition, do not overheat.
- : Incompatible with strong acids and oxidizing agents.
- Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen :
 - (NOx), other hazardous materials, and smoke are all possible.

Evaporation rate

Specific Gravity

Bulk density

Vapor pressure

Vapor density

pН

11. TOXICOLOGICAL INFORMATION

4/8



MATERIAL SAFETY DATA SHEET

050YE652-HMF GOLD

Version Number 1.0 Revision Date 04/23/2002 Page 5 of 8 Print Date 11/4/2011

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1333-86-4	Carbon black	Systemic effects	Eyes, Respiratory system.
7585-41-3	2-Naphthalenecarboxylic acid, 4-[(5-chloro-4-methyl-2-s ulfophenyl)azo]-3-hydrox y-, barium salt (1:1)	Irritant	Eyes, Skin.
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

LC50 / LD50

This product contains the following components which in their pure form have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
1333-86-4	Carbon black	Oral LD50	>15,400 mg/kg	rat
		Dermal LD50	> 3 gm/kg	rabbit

Carcinogenicity:

This product contains the following components which in their pure form have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
1333-86-4	Carbon black	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

Additional Health Hazard Information:



MATERIAL SAFETY DATA SHEET

050YE652-HMF GOLD

Version Number 1.0 Revision Date 04/23/2002 Page 6 of 8 Print Date 11/4/2011

Carbon black 1333-86-4 Carcinogenicity: Many inhalation toxicologists believe that the tumor response observed in the referenced rat studies is species specific and does not correlate to human exposure. However, the IARC evaluation in Monograph Volume 65, issued in April 1996 concluded that, "There is sufficient evidence in experimental animals for the carcinogenicity of carbon black". Based on this evaluation, along with their evaluation of inadequate evidence of carcinogenicity in humans, IARC's overall evaluation is that "Carbon Black is possibly carcinogenic to humans (Group 2B). Carbon Black has not been listed as a carcinogen by the National Toxicology Program (NTP) or the Occupational Safety and Health Administration (OSHA). The National Institute of Occupational Safety and Health (NIOSH) criteria document on carbon black recommends that only carbon black with PAH (polynuclear aromatic hydrocarbon) levels greater than 0.1% be considered suspect carcinogens.

	12. ECOLOGICAL INFORMATION		
Persistence and degradability	: Not readily biodegradable.		
Environmental Toxicity	: Chemicals are not readily available as they are bound within the matrix of the polymer.		
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the matrix of the polymer.		
Additional advice	: No data available.		
	13. DISPOSAL CONSIDERATIONS		
Product	: Like most thermoplastics the product can be recycled. Where possible, recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.		
Contaminated packaging : Recycling is preferred when possible. The generator of was has the responsibility for proper waste classification, trans and disposal in accordance with applicable federal, state/p and local regulations.			
	14. TRANSPORT INFORMATION		
U.S. D.O.T. / CA T.D.G. Classification (Non-bulk ground)	: Not regulated for transportation.		
ICAO/IATA	: Not regulated for transportation.		
IMO / IMDG	: Not regulated for transportation.		
	15. REGULATORY INFORMATION		
US Regulations:			



MATERIAL SAFETY DATA SHEET

050YE652-HMF GOLD

Version Number 1.0 Revision Date 04/23/2002			Page 7 of 8 Print Date <u>11/4/2011</u>
OSHA Status : Cl	lassified as hazard	dous based on compo	onents.
	: All components of this product are listed on the TSCA inventory or are exempt.		
US. EPA CERCLA Hazardous Substan	aces (40 CFR 302)	
Chemical Name 2-Naphthalenecar boxylic acid, 4-[(5-chloro-4-me thyl-2-sulfophenyl)azo]-3-hydroxy-, barium salt (1:1)	3	RQ for Mixture 34,483 LB	e/Product
California Proposition : Th 65	nis product does r	ot contain a substand	e listed by California Prop 65.
SARA Title III Section 313 Toxic Cher	micals:		
Chemical Name		CAS-No.	Weight %
BARIUM COMPOUND	DS	7585-41-3	2.90
Canadian Regulations:	2.4		
WHMIS Classification : D2	2A		
WHMIS Ingredient Disclosure I	List		
CAS-No. 7585-41-3 1333-86-4			
	sted.		
National Inventories:			
Australia AICS : Li	sted.		
China IECS : Li	sted.		
Europe EINECS : No	ot determined.		
Japan ENCS : No	ot determined.		
Korea KECI : Li	sted.		
Philippines PICCS : Li	sted.		
1	6. OTHER INFO	ORMATION	
	7/8		



MATERIAL SAFETY DATA SHEET

050YE652-HMF GOLD

Version Number 1.0 Revision Date 04/23/2002 Page 8 of 8 Print Date 11/4/2011

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.