

#### MATERIAL SAFETY DATA SHEET

### **RED 3002-HI PERFORMANCE UV #3**

Version Number 1.0 Revision Date 04/22/2002 Page 1 of 6 Print Date 11/4/2011

#### 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	RED 3002-HI PERFORMANCE UV #3
Product code	:	CC10014569
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

#### 2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
1,6-Hexanediamine,	70624-18-9	1 - 5
N,N'-bis(2,2,6,6-tetramethyl-4-piperidinyl)-,		
polymer with 2,4,6-trichloro-1,3,5-triazine,		
reaction products		
D&C red No. 9	5160-02-1	1 - 5
Titanium dioxide	13463-67-7	1 - 5
Benzoic acid,	15782-06-6	5 - 10
2-[(2-hydroxy-3,6-disulfo-1-naphthalenyl)az		
o]-, barium salt (2:3)		

#### **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some fumes may be released upon heating or crosslinking and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See Sections 3 and 11 for special precautions.

#### POTENTIAL HEALTH EFFECTS

Routes of Exposure:	:	: Inhalation, Ingestion, Skin contact	
Acute exposure			
Inhalation Ingestion Eyes	:	Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to eyes.	



#### MATERIAL SAFETY DATA SHEET

## RED 3002-HI PERFORMANCE UV #3

ision Date 04/22/2002	Print Date 11/4/2
Skin	: Experience shows no unusual dermatitis hazard from routine handling
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases o doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	<ul> <li>Not applicable</li> <li>Not applicable</li> <li>Not relevant</li> <li>Carbon dioxide blanket, Water spray, dry powder, foam.</li> <li>Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.</li> <li>None</li> </ul>
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 1 of this MSDS for proper disposal methods.



#### MATERIAL SAFETY DATA SHEET

## **RED 3002-HI PERFORMANCE UV #3**

Version Number 1.0 Revision Date 04/22/2002 Page 3 of 6 Print Date 11/4/2011

		7. HANDLING AND STORAGE
Handling	:	Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.
8. EXP	OSUF	RE CONTROLS / PERSONAL PROTECTION
Respiratory protection	:	No personal respiratory protective equipment normally required.
Eye/Face Protection	:	Safety glasses with side-shields.
Hand protection	:	Protective gloves.
Skin and body protection	:	Long sleeved clothing.
Additional Protective Measures	:	Safety shoes.
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Benzoic acid,	0.5 mg/m3	Time Weighted Average	as Ba	ACGIH
2-[(2-hydroxy-3,6-disu		(TWA):		
lfo-1-naphthalenyl)azo				
]-, barium salt (2:3)				
Benzoic acid,	0.5 mg/m3	PEL:	as Ba	OSHA Z1
2-[(2-hydroxy-3,6-disu				
lfo-1-naphthalenyl)azo				
]-, barium salt (2:3)				
D&C red No. 9	0.5 mg/m3	Time Weighted Average	as Ba	ACGIH
		(TWA):		
D&C red No. 9	0.5 mg/m3	PEL:	as Ba	OSHA Z1
Titanium dioxide	10 mg/m3	Time Weighted Average	Total dust.	ACGIH
	_	(TWA):		
Titanium dioxide	15 mg/m3	PEL:	Total dust.	OSHA Z1

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

Form

: Solid

Evaporation rate

: Not applicable.

# PolyOne.

#### MATERIAL SAFETY DATA SHEET

## RED 3002-HI PERFORMANCE UV #3

Version Number 1.0 Revision Date 04/22/2002		Page 4 of 6 Print Date 11/4/2011
Appearance Color Odor Melting point/range Boiling Point: Water solubility	<ul> <li>Pellets Specific Gravity</li> <li>RED Bulk density</li> <li>Very faint Vapor pressure</li> <li>Not determined Vapor density</li> <li>Not applicable pH</li> <li>Insoluble</li> </ul>	<ul> <li>Not determined</li> <li>Not established</li> <li>Not applicable</li> <li>Not applicable</li> <li>Not applicable</li> </ul>
	10. STABILITY AND REACTIVITY	
Stability	: Stable.	
Hazardous Polymerization	: Will not occur.	
Conditions to avoid	: Keep away from oxidizing agents and open decomposition, do not overheat.	flame. To avoid thermal
Incompatible Materials	: Incompatible with strong acids and oxidizin	ng agents.
Hazardous decomposition products	: Carbon dioxide (CO2), carbon monoxide (CO2), carbon monoxide (CO2), carbon monoxide (CO2), other hazardous materials, and smol	

#### 11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

#### **Toxicity Overview**

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
70624-18-9	1,6-Hexanediamine,	Highly Toxic	Refer to MSDS for Toxicity
	N,N'-bis(2,2,6,6-tetrameth		Data
	yl-4-piperidinyl)-,polymer		
	with		
	2,4,6-trichloro-1,3,5-triazi		
	ne, reaction products		
5160-02-1	D&C red No. 9	Irritant	Eyes, Skin.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.
15782-06-6	Benzoic acid,	Irritant	Eyes, Skin.
	2-[(2-hydroxy-3,6-disulfo-		
	1-naphthalenyl)azo]-,		
	barium salt (2:3)		

#### LC50 / LD50

This product contains the following components which in their pure form have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
			•	



#### MATERIAL SAFETY DATA SHEET

## RED 3002-HI PERFORMANCE UV #3

Version Number 1.0	
Revision Date 04/22/2002	

Page 5 of 6 Print Date 11/4/2011

	N,N'-bi yl-4-pip with 2,4,6-tr	xanediamine, s(2,2,6,6-tetrameth beridinyl)-,polymer ichloro-1,3,5-triazi tion products	LC50 Oral LD50	112 mg/m3 9,910 mg/kg	rat rat
		12. ECOLOGIC	AL INFORMAT	ION	
Persistence and degrad	lability	: Not readily bio	odegradable.		
Environmental Toxicit	ty	: Chemicals are of the polymer	•	ble as they are boun	d within the matrix
Bioaccumulation Pote	ntial	: Chemicals are of the polymer	•	ble as they are boun	d within the matrix
Additional advice		: No data availa	ble.		
		13. DISPOSAL	CONSIDERATI	ONS	
Product		possible, recyc generator of w classification,	ling is preferred t aste material has t transportation and	oduct can be recycl o disposal or incine the responsibility fo l disposal in accord ial and local regular	ration. The or proper waste ance with
Contaminated packagi	ng	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.			
		14. TRANSPOR	<b>AT INFORMATI</b>	ON	
U.S. D.O.T. / CA T.D. Classification (Non-bu ground)		: Not regulated	for transportation.		
ICAO/IATA		: Not regulated	for transportation.		
IMO / IMDG		: Not regulated for transportation.			
		15. REGULATO	RY INFORMAT	ION	
US Regulations:					
OSHA Status : Classified as hazardous based on components.					
OSHA Status			mponents of this product are listed on the TSCA inventory or are ot.		



#### MATERIAL SAFETY DATA SHEET

## **RED 3002-HI PERFORMANCE UV #3**

Version Number 1.0 Revision Date 04/22/2002 Page 6 of 6 Print Date 11/4/2011

California Proposition 65

: WARNING! This product contains a chemical known in the State of California to cause cancer.

SARA Title III Section 313 Toxic Chemicals:

Chemical Name	CAS-No.	Weight %
BARIUM COMPOUNDS	15782-06-6	8.81
BARIUM COMPOUNDS	5160-02-1	2.93

Canadian Regulations:

WHMIS Classification : D1A

WHMIS Ingredient Disclosure List

CAS-No.
15782-06-6
5160-02-1

DSL

: Listed.

National Inventories:

Australia AICS	:	Not determined.
China IECS	:	Not determined.
Europe EINECS	:	Not determined.
Japan ENCS	:	Not determined.
Korea KECI	:	Not determined.
Philippines PICCS	:	Not determined.

#### **16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.