

MATERIAL SAFETY DATA SHEET

# DEWALT YELLOW #283 (HM)

Version Number 1.0 Revision Date 05/13/2002 Page 1 of 7 Print Date 11/4/2011

# 1. PRODUCT AND COMPANY IDENTIFICATION

### POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	DEWALT YELLOW #283 (HM)
Product code	:	CC10014614
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

### 2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
C.I. Pigment Red 108	58339-34-7	1 - 5
Barium sulfate	7727-43-7	10 - 30
Cadmium	7440-43-9	10 - 30

# **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating or crosslinking and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

### POTENTIAL HEALTH EFFECTS

<b>Routes of Exposure:</b>	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes	<ul> <li>Resin particles, like other inert materials, can be mechanically irritating.</li> <li>May be harmful if swallowed.</li> <li>Resin particles, like other inert materials, are mechanically irritating to</li> </ul>
Skin	<ul><li>eyes.</li><li>Experience shows no unusual dermatitis hazard from routine handling.</li></ul>
Chronic exposure	: Refer to Section 11 for Toxicological Information.



MATERIAL SAFETY DATA SHEET

# DEWALT YELLOW #283 (HM)

Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases o doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	<ul> <li>Not applicable</li> <li>Not applicable</li> <li>Not relevant</li> <li>Carbon dioxide blanket, Water spray, dry powder, foam.</li> </ul>
Special Fire Fighting Procedures Unusual Fire/Explosion	<ul> <li>Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.</li> <li>None</li> </ul>
Hazards	
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 1 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.



# MATERIAL SAFETY DATA SHEET

# DEWALT YELLOW #283 (HM)

Version Number 1.0 Revision Date 05/13/2002 Page 3 of 7 Print Date 11/4/2011

Storage

: Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.

# 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Respiratory protection	:	No personal respiratory protective equipment normally required.
Eye/Face Protection	:	Safety glasses with side-shields.
Hand protection	:	Protective gloves.
Skin and body protection	:	Long sleeved clothing.
Additional Protective Measures	:	Safety shoes.
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Barium sulfate	10 mg/m3	Time Weighted Average	Total dust.	ACGIH
		(TWA):		
Barium sulfate	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
C.I. Pigment Red 108	0.005	Time Weighted Average	as Cd	OSHA
-	mg/m3	(TWA):		
	0.0025	OSHA Action level:	as Cd	OSHA
	mg/m3			
	0.2 mg/m3	PEL:	as Se	OSHA Z1
C.I. Pigment Red 108	0.2 mg/m3	Time Weighted Average	as Se	MX OEL
-	_	(TWA):		
	0.01	Time Weighted Average		ACGIH
	mg/m3	(TWA):		
C.I. Pigment Red 108	0.2 mg/m3	Time Weighted Average		ACGIH
	_	(TWA):		
Cadmium	0.01	Time Weighted Average	Inhalable fraction. as	ACGIH
	mg/m3	(TWA):	Cd	
	0.002	Time Weighted Average	Respirable fraction. as	ACGIH
	mg/m3	(TWA):	Cd	
Cadmium	0.005	Time Weighted Average	Total as Cd	OSHA
	mg/m3	(TWA):		

### 9. PHYSICAL AND CHEMICAL PROPERTIES



# MATERIAL SAFETY DATA SHEET

# DEWALT YELLOW #283 (HM)

Version Number 1.0 Revision Date 05/13/2002

Page 4 of 7 Print Date 11/4/2011

Form Appearance Color Odor Melting point/range Boiling Point: Water solubility	:	Solid Pellets YELLOW Very faint Not determi Not applical Insoluble		Evaporation rate Specific Gravity Bulk density Vapor pressure Vapor density pH	:	Not applicable. Not determined Not established Not applicable Not applicable Not applicable
		10. STABI	LITY AND RE	CACTIVITY		
Stability		: Stable.				
Hazardous Polymerization		: Will not	occur.			
Conditions to avoid		-	ay from oxidizi osition, do not o	ing agents and open fla	ame.	To avoid thermal
Incompatible Materials		: Incompa	tible with stron	g acids and oxidizing a	agent	ts.
Hazardous decomposition		: Carbon o	lioxide (CO2),	carbon monoxide (CO	), oxi	ides of nitrogen

#### 11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

(NOx), other hazardous materials, and smoke are all possible.

Toxicity Overview

products

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
58339-34-7	C.I. Pigment Red 108	Irritant	Eyes, Skin.
7727-43-7	Barium sulfate	Irritant	Respiratory system.
		Systemic effects	Eyes, Respiratory system.
7440-43-9	Cadmium	Systemic effects	Respiratory system, blood and blood forming system, Kidney, urinary system, reproductive system.
		Highly Toxic	Refer to MSDS for Toxicity Data

#### LC50 / LD50

This product contains the following components which in their pure form have the following toxicity data:

[	CAS-No.	Chemical Name	Route	Value	Species
	7440-43-9	Cadmium	LC50	25 mg/m3	rat
			Oral LD50	2,330 mg/kg	rat

Carcinogenicity:



MATERIAL SAFETY DATA SHEET

# DEWALT YELLOW #283 (HM)

Version Number 1.0 Revision Date 05/13/2002 Page 5 of 7 Print Date 11/4/2011

This product contains the following components which in their pure form have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
58339-34-7	C.I. Pigment Red 108	yes	1	no
7440-43-9	Cadmium	yes	1	1

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

#### Additional Health Hazard Information:

C.I. Pigment Red 108 58339-34-7 Can produce rapid and sometimes fatal pulmonary edema, chronic absorption leads to liver and kidney damage.

# Additional Health Hazard Information:

Cadmium 7440-43-9 Can produce rapid and sometimes fatal pulmonary edema, chronic absorption leads to liver and kidney damage.

Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the matrix of the polymer.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the matrix of the polymer.
Additional advice	: No data available.
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastics the product can be recycled. Where possible, recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION



# MATERIAL SAFETY DATA SHEET

# DEWALT YELLOW #283 (HM)

sion Number 1.0 rision Date 05/13/2002			Prin	Page 6 t Date 11/4/2
U.S. D.O.T. / CA T.D.G. Classification (Non-bulk ground)	: Not regulate	d for transportation.		
ICAO/IATA	: Not regulate	d for transportation.		
IMO / IMDG	: Not regulate	d for transportation.		
	15. REGULAT	ORY INFORMATIO	N	
US Regulations:				
OSHA Status	: Classified as	hazardous based on co	omponents.	
TSCA Status	: All compone exempt.	ents of this product are l	isted on the TSCA	inventory or are
US. EPA CERCLA Hazardous	-	FR 302)		
	California to	52 LB This product contains cause cancer., WARN own in the State of Cali	ING! This product	contains a
SARA Title III Section 313 To	xic Chemicals:			
Chemical Name	;	CAS-No.	Weight %	
CADMIUM CO SELENIUM CO		58339-34-7	3.30	
CADMIUM		7440-43-9	19.29	
ZINC COMPO	UNDS	557-05-1	0.00	
ZINC COMPO	UNDS	1314-98-3	14.05	
Canadian Regulations:				
WHMIS Classification	: D1A			
WHMIS Ingredient Dis	closure List			
CAS-No.				
58339-34-7				
7440-43-9 1333-86-4				

DSL

557-05-1

: Listed.



## MATERIAL SAFETY DATA SHEET

# DEWALT YELLOW #283 (HM)

Version Number 1.0 Revision Date 05/13/2002 Page 7 of 7 Print Date 11/4/2011

National Inventories:

Australia AICS	:	Listed.
China IECS	:	Listed.
Europe EINECS	:	Not determined.
Japan ENCS	:	Not determined.
Korea KECI	:	Listed.
Philippines PICCS	:	Listed.

#### **16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.