

MATERIAL SAFETY DATA SHEET

AMAZON GREEN M5612A

Version Number 1.0 Revision Date 04/22/2002 Page 1 of 7 Print Date 11/4/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	AMAZON GREEN M5612A
Product code	:	CC10014650
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Rutile, antimony chromium buff	68186-90-3	0.1 - 1
Tin oxide (SnO2)	18282-10-5	0.1 - 1
Carbon black	1333-86-4	1 - 5
Titanium dioxide	13463-67-7	1 - 5
Mica	12001-26-2	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some fumes may be released upon heating or crosslinking and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See Sections 3 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes Skin	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to eyes. Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	 : Experience shows no unusual dermatics nazard from routile nationing. : Refer to Section 11 for Toxicological Information.



MATERIAL SAFETY DATA SHEET

AMAZON GREEN M5612A

Version Number 1.0 Revision Date 04/22/2002 Page 2 of 7 Print Date 11/4/2011

Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases o doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion	 Not applicable Not applicable Not relevant Carbon dioxide blanket, Water spray, dry powder, foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. None
Hazards	
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 1 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat



MATERIAL SAFETY DATA SHEET

AMAZON GREEN M5612A

sion Date 04/22/2002			Print I	Page 3 2/4/2	
	01	nly in areas with appropriate e	xhaust ventilation.		
Storage		eep containers dry and tightly nd contamination. Keep in a c		absorption	
8. I	EXPOSURE	CONTROLS / PERSONAL	PROTECTION		
Respiratory protection	: N	o personal respiratory protecti	ive equipment normally r	equired.	
Eye/Face Protection	: S	afety glasses with side-shields			
Hand protection	: P	: Protective gloves.			
Skin and body protection	: L	ong sleeved clothing.			
Additional Protective Measures	: S	: Safety shoes.			
General Hygiene Considerations	: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.				
Engineering measures	: H	eat only in areas with appropr	into avhaust vantilation	D '1	
		ppropriate exhaust ventilation		Provide	
Exposure limit(s)				Provide	
				List:	
Exposure limit(s)	aj	ppropriate exhaust ventilation	at machinery.		
Exposure limit(s) Components	aj Value	Exposure time Time Weighted Average	at machinery. Exposure type Total dust. as carbon	List: ACGIH	
Exposure limit(s) Components Carbon black Carbon black Mica	aj Value 3.5 mg/m3 3.5 mg/m3 3 mg/m3	Exposure time Time Weighted Average (TWA):	at machinery. Exposure type Total dust. as carbon black Total dust. as carbon black Total dust.	List: ACGIH OSHA Z1 ACGIH	
Exposure limit(s) Components Carbon black Carbon black	aj Value 3.5 mg/m3 3.5 mg/m3	Exposure time Time Weighted Average (TWA): PEL: Time Weighted Average	at machinery. Exposure type Total dust. as carbon black Total dust. as carbon black	List: ACGIH OSHA Z1	
Exposure limit(s) Components Carbon black Carbon black Mica	aj Value 3.5 mg/m3 3.5 mg/m3 3 mg/m3	Exposure time Time Weighted Average (TWA): PEL: Time Weighted Average (TWA):	at machinery. Exposure type Total dust. as carbon black Total dust. as carbon black Total dust.	List: ACGIH OSHA Z1 ACGIH	
Exposure limit(s) Components Carbon black Carbon black Mica Mica	aj Value 3.5 mg/m3 3.5 mg/m3 3 mg/m3 20 mppcf	Exposure time Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): PEL: Time Weighted Average	at machinery. Exposure type Total dust. as carbon black Total dust. as carbon black Total dust. Total dust.	List: ACGIH OSHA Z1 ACGIH OSHA ACGIH	
Exposure limit(s) Components Carbon black Carbon black Mica Mica Titanium dioxide	aj Value 3.5 mg/m3 3.5 mg/m3 3 mg/m3 20 mppcf 10 mg/m3 15 mg/m3	Exposure time Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): PEL: Time Weighted Average (TWA):	at machinery. Exposure type Total dust. as carbon black Total dust. as carbon black Total dust. Total dust. Total dust. Total dust. Total dust.	List: ACGIH OSHA Z1 ACGIH OSHA ACGIH	
Exposure limit(s) Components Carbon black Carbon black Mica Mica Titanium dioxide Titanium dioxide	aj Value 3.5 mg/m3 3.5 mg/m3 3 mg/m3 20 mppcf 10 mg/m3 15 mg/m3 9. PHYSIC	Exposure time Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO	at machinery. Exposure type Total dust. as carbon black Total dust. as carbon black Total dust. Total dust. Total dust. Total dust. DPERTIES	List: ACGIH OSHA Z1 ACGIH OSHA ACGIH OSHA Z1	
Exposure limit(s) Components Carbon black Carbon black Mica Mica Titanium dioxide Titanium dioxide	aj Value 3.5 mg/m3 3.5 mg/m3 3 mg/m3 20 mppcf 10 mg/m3 15 mg/m3 9. PHYSIC : Solid	Exposure time Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PR(Evapo	at machinery. Exposure type Total dust. as carbon black Total dust. as carbon black Total dust. as carbon black Total dust. Notal dust.	List: ACGIH OSHA Z1 ACGIH OSHA ACGIH OSHA Z1 applicable.	
Exposure limit(s) Components Carbon black Carbon black Mica Mica Titanium dioxide Titanium dioxide Form Appearance	aj Value 3.5 mg/m3 3.5 mg/m3 3 mg/m3 20 mppcf 10 mg/m3 15 mg/m3 9. PHYSIC : Solid : Pelle	Exposure time Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO L Evapo ts Specifi	Exposure type Total dust. as carbon black Total dust. as carbon black Total dust. as carbon black Total dust. DPERTIES ration rate : Not ïc Gravity : Not	List: ACGIH OSHA Z1 ACGIH OSHA ACGIH OSHA Z1 applicable. determined	
Exposure limit(s) Components Carbon black Carbon black Mica Mica Titanium dioxide Titanium dioxide Form Appearance Color	ap Value 3.5 mg/m3 3.5 mg/m3 3.5 mg/m3 3 mg/m3 20 mppcf 10 mg/m3 15 mg/m3 9. PHYSIC : Solid : Pelle : GRE	Exposure time Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO L Evapo ts Specif EN Bulk d	at machinery. Exposure type Total dust. as carbon black Total dust. Vertice and the second seco	List: ACGIH OSHA Z1 ACGIH OSHA ACGIH OSHA Z1 OSHA Z1 applicable. determined established	
Exposure limit(s) Components Carbon black Carbon black Mica Mica Titanium dioxide Titanium dioxide Form Appearance Color Odor	ap Value 3.5 mg/m3 3.5 mg/m3 3.5 mg/m3 3 mg/m3 20 mppcf 10 mg/m3 15 mg/m3 9. PHYSIC : Solid : Pelle : GRE : Very	Exposure time Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRC L Evapo ts Specif EN Bulk d faint Vapor	at machinery. Exposure type Total dust. as carbon black Total dust. as carbon black Total dust. as carbon black Total dust. Notal dust. DPERTIES ration rate : Not ic Gravity : Not pressure : Not	List: ACGIH OSHA Z1 ACGIH OSHA ACGIH OSHA Z1 applicable. determined established applicable	
Exposure limit(s) Components Carbon black Carbon black Mica Mica Titanium dioxide Titanium dioxide Form Appearance Color	aj Value 3.5 mg/m3 3.5 mg/m3 3.5 mg/m3 3 mg/m3 20 mppcf 10 mg/m3 15 mg/m3 15 mg/m3 9. PHYSIC : Solid : Pelle : GRE : Very : Not c	Exposure time Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRC L Evapo ts Specif EN Bulk d faint Vapor	at machinery. Exposure type Total dust. as carbon black Total dust. OPERTIES ration rate : Not ic Gravity : Not pressure : Not density : Not	List: ACGIH OSHA Z1 ACGIH OSHA ACGIH OSHA Z1 applicable. determined established	

- : Not applicable : Not applicable

10. STABILITY AND REACTIVITY



MATERIAL SAFETY DATA SHEET

AMAZON GREEN M5612A

Version Number 1.0 Revision Date 04/22/2002 Page 4 of 7 Print Date 11/4/2011

Stability	:	Stable.
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
68186-90-3	Rutile, antimony	Irritant	Eyes, Skin.
	chromium buff		
18282-10-5	Tin oxide (SnO2)	Systemic effects	Respiratory system.
1333-86-4	Carbon black	Systemic effects	Eyes, Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.
12001-26-2	Mica	Systemic effects	Respiratory system.

LC50 / LD50

This product contains the following components which in their pure form have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
18282-10-5	Tin oxide (SnO2)	Oral LD50	> 20 gm/kg	rat
1333-86-4	Carbon black	Oral LD50	>15,400 mg/kg	rat
		Dermal LD50	> 3 gm/kg	rabbit

Carcinogenicity:

This product contains the following components which in their pure form have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
1333-86-4	Carbon black	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

- 2A The component is probably carcinogenic to humans.
- 2B The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:



MATERIAL SAFETY DATA SHEET

AMAZON GREEN M5612A

Version Number 1.0 Revision Date 04/22/2002 Page 5 of 7 Print Date 11/4/2011

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

Additional Health Hazard Information:

Rutile, antimony chromium buff 68186-90-3 Can cause eye irritation. Can cause skin irritation. Symptoms may include redness and burning of skin, and other skin damage. Additional symptoms of skin contact may include: antimony measles (a red, pimply rash).

Additional Health Hazard Information:

Carbon black 1333-86-4 Carcinogenicity: Many inhalation toxicologists believe that the tumor response observed in the referenced rat studies is species specific and does not correlate to human exposure. However, the IARC evaluation in Monograph Volume 65, issued in April 1996 concluded that, "There is sufficient evidence in experimental animals for the carcinogenicity of carbon black". Based on this evaluation, along with their evaluation of inadequate evidence of carcinogenicity in humans, IARC's overall evaluation is that "Carbon Black is possibly carcinogenic to humans (Group 2B). Carbon Black has not been listed as a carcinogen by the National Toxicology Program (NTP) or the Occupational Safety and Health Administration (OSHA). The National Institute of Occupational Safety and Health (NIOSH) criteria document on carbon black recommends that only carbon black with PAH (polynuclear aromatic hydrocarbon) levels greater than 0.1% be considered suspect carcinogens.

	12. ECOLOGICAL INFORMATION
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the matrix of the polymer.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the matrix of the polymer.
Additional advice	: No data available.
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastics the product can be recycled. Where possible, recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. D.O.T. / CA T.D.G. Classification (Non-bulk	: Not regulated for transportation.

5/7



MATERIAL SAFETY DATA SHEET

AMAZON GREEN M5612A

ion Number 1.0 sion Date 04/22/2002		Page 6 Print Date 11/4/2
ICAO/IATA	:	Not regulated for transportation.
IMO / IMDG	:	Not regulated for transportation.
	15.	REGULATORY INFORMATION
US Regulations:		
OSHA Status	:	Classified as hazardous based on components.
TSCA Status	:	All components of this product are listed on the TSCA inventory or an exempt.
California Proposition 65	:	This product does not contain a substance listed by California Prop 65
Canadian Regulations:		
WHMIS Classification	:	D2B
WHMIS Ingredient Disc	closu	re List
CAS-No. 1333-86-4 12001-26-2 68186-90-3 18282-10-5		
DSL	:	Listed.
National Inventories:		
Australia AICS	:	Listed.
China IECS	:	Listed.
Europe EINECS	:	Not determined.
Japan ENCS	:	Not determined.
Korea KECI	:	Listed.
Philippines PICCS	:	Listed.
		16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.



MATERIAL SAFETY DATA SHEET

AMAZON GREEN M5612A

Version Number 1.0 Revision Date 04/22/2002 Page 7 of 7 Print Date 11/4/2011