

MATERIAL SAFETY DATA SHEET

BLUE GRAY M5616

Version Number 1.0 Revision Date 04/25/2002 Page 1 of 5 Print Date 11/4/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	BLUE GRAY M5616
Product code	:	CC10015005
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Silica, amorphous	7631-86-9	1 - 5
Titanium dioxide	13463-67-7	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating or crosslinking and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin Chronic exposure	 Experience shows no unusual dermatitis hazard from routine handling. Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.



MATERIAL SAFETY DATA SHEET

BLUE GRAY M5616

Version Number 1.0 Page 2 of 5 Revision Date 04/25/2002 Print Date 11/4/2011 **4. FIRST AID MEASURES** Inhalation Move to fresh air in case of accidental inhalation of fumes from ÷ overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice. Ingestion Do not induce vomiting without medical advice. When symptoms : persist or in all cases of doubt seek medical advice. Eyes Rinse immediately with plenty of water, also under the eyelids, for at : least 15 minutes. If eye irritation persists, seek medical attention. Skin Wash off with soap and plenty of water. If skin irritation persists seek : medical attention. **5. FIRE-FIGHTING MEASURES** Flash point Not applicable : Flammable Limits Upper explosion limit Not applicable : Lower explosion limit Not applicable : Autoignition temperature Not relevant : Carbon dioxide blanket, Water spray, dry powder, foam. Suitable extinguishing media : Special Fire Fighting Fullface self-contained breathing apparatus (SCBA) used in positive : Procedures pressure mode should be worn to prevent inhalation of airborne contaminants. Unusual Fire/Explosion None · Hazards 6. ACCIDENTAL RELEASE MEASURES Personal precautions : Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls. Environmental precautions Should not be released into the environment. The product should not : be allowed to enter drains, water courses or the soil. Clean up promptly by sweeping or vacuum. Package all material in Methods for cleaning up : plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods. 7. HANDLING AND STORAGE Handling Take measures to prevent the build up of electrostatic charge. Heat : only in areas with appropriate exhaust ventilation. Storage Keep containers dry and tightly closed to avoid moisture absorption ·



MATERIAL SAFETY DATA SHEET

BLUE GRAY M5616

Version Number 1.0 Revision Date 04/25/2002			Print	Page 3 of 5 Date 11/4/2011	
	a	nd contamination. Keep in a	dry, cool place.		
8. H	XPOSURE	CONTROLS / PERSONAI	PROTECTION		
Respiratory protection	: N	o personal respiratory protec	tive equipment normally	required.	
Eye/Face Protection	: S	: Safety glasses with side-shields.			
Hand protection	: P	rotective gloves.			
Skin and body protection	: L	ong sleeved clothing.			
Additional Protective Measures	: S	afety shoes.			
General Hygiene Considerations		andle in accordance with goo Vash hands before breaks and		afety practice.	
Engineering measures		leat only in areas with approp ppropriate exhaust ventilatior		Provide	
Exposure limit(s)					
Components	Value	Exposure time	Exposure type	List:	
Silica, amorphous	20 mppcf	PEL:	Total dust.	OSHA	
Silica, amorphous	20 mppcf	PEL:	Total dust.	Z3	
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):	Total dust.	ACGIH	
Titanium dioxide	15 mg/m3	PEL:	Total dust.	OSHA Z1	
	9. PHYSIC	CAL AND CHEMICAL PR	OPERTIES		
T.	0.1		· · · · · · · · · · · · · · · · · · ·	1. 1.1	
Form	: Solic : Pelle	1		applicable.	
Appearance Color	: BLU			determined established	
Odor	: Very		-	applicable	
Melting point/range				applicable	
Boiling Point:		applicable pH	2	applicable	
Water solubility	: Insol			approvere	
	10. S	STABILITY AND REACTI	VITY		
Stability	: S	table.			
Hazardous Polymerization	n : W	Vill not occur.			
Conditions to avoid		eep away from oxidizing age ecomposition, do not overhea		woid thermal	



MATERIAL SAFETY DATA SHEET

BLUE GRAY M5616

T		·			
Incompatible Materia	ls :	Incompatible	with strong acids an	d oxidizing agents.	
Hazardous decomposi products	ition :			onoxide (CO), oxides of nitrogen, and smoke are all possible.	
	11. 7	TOXICOLOG	ICAL INFORMAT	ΓΙΟΝ	
health data for the ind Toxicity Overview	ividual compo	onents which co	omprise the mixture.	osure effects listed are based on ex rm have the following characteristi	
CAS-No.		ical Name	Effect	Target Organ	
7631-86-9	Silica, amo		Irritant	Eyes, Respiratory system.	
13463-67-7	Titanium d	ioxide	Systemic effects	Respiratory system.	
	12	2. ECOLOGIO	CAL INFORMATI	ON	
Persistence and degra	dability :	Not readily bi	odegradable.		
Environmental Toxici	-	-	e not readily availabl	e as they are bound within the matr	
Bioaccumulation Pote	ential :	Chemicals are of the polyme		e as they are bound within the matri	
Additional advice	:	No data avail	able.		
	13	3. DISPOSAL	CONSIDERATIO	NS	
Product		: Like most thermoplastics the product can be recycled. Where possible, recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.			
Contaminated packag	ing :	has the respon	nsibility for proper w n accordance with a	ble. The generator of waste materia vaste classification, transportation pplicable federal, state/provincial	
	1	4. TRANSPO	RT INFORMATIC	DN	
U.S. D.O.T. / CA T.D Classification (Non-b ground)		Not regulated	for transportation.		
ICAO/IATA	:	Not regulated	for transportation.		



MATERIAL SAFETY DATA SHEET

BLUE GRAY M5616

ision Date 04/25/2002		Print Date 11/4/
IMO / IMDG	:	Not regulated for transportation.
	15.	REGULATORY INFORMATION
US Regulations:		
OSHA Status	:	Classified as hazardous based on components.
TSCA Status		All components of this product are listed on the TSCA inventory or a exempt.
California Proposition 65	:	This product does not contain a substance listed by California Prop 6
Canadian Regulations:		
WHMIS Classification	:	D2B
WHMIS Ingredient Disc	losur	e List
CAS-No. 1333-86-4 7631-86-9		
DSL	:	Listed.
National Inventories:		
Australia AICS	:	Listed.
China IECS	:	Listed.
Europe EINECS	:	Not determined.
Japan ENCS	:	Not determined.
Korea KECI	:	Listed.
Philippines PICCS	:	Listed.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.