

MATERIAL SAFETY DATA SHEET

BLUE 2X

Version Number 1.0 Revision Date 05/16/2002 Page 1 of 5 Print Date 11/4/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	\mathbf{r}	
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	BLUE 2X
Product code	:	CC10015487
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Titanium dioxide	13463-67-7	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating or crosslinking and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact				
Acute exposure					
Inhalation Ingestion Eyes Skin	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Particulates, like other inert materials can be mechanically irritating. Experience shows no unusual dermatitis hazard from routine handling. 				
Chronic exposure	: Refer to Section 11 for Toxicological Information.				
Medical Conditions Aggravated by Exposure:	: None known.				
	4. FIRST AID MEASURES				

1/5

MATERIAL SAFETY DATA SHEET



sion Number 1.0 ision Date 05/16/2002	Page 2 Print Date 11/4/2
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases o doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature	 Not applicable Not applicable Not relevant
Suitable extinguishing media	: Carbon dioxide blanket, Water spray, dry powder, foam.
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	: none
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by scoop or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 1 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	: Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.



MATERIAL SAFETY DATA SHEET

BLUE 2X

Version Number 1.0 Revision Date 05/16/2002 Page 3 of 5 Print Date 11/4/2011

	APUSUKE	CONTROLS / PERSO	JNAL P	KOIECHON	
Respiratory protection		No personal respiratory p lusty conditions occur we			
Eye/Face Protection	: s	safety glasses			
Hand protection	: F	Protective gloves.			
Skin and body protection	: I	long sleeved clothing.			
Additional Protective Measures	: S	: Safety shoes.			
General Hygiene Considerations	р	: Wash hands and face before breaks and immediately after handling the product. Handle in accordance with good industrial hygiene and safety practice for diagnostics.			
Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.					
Exposure limit(s)					
Components	Value	Exposure time		Exposure type	List:
Titanium dioxide	10 mg/m3	Time Weighted Aver	rage	Total dust.	ACGIH
	6	(TWA):	C		
Titanium dioxide	15 mg/m3	PEL:		Total dust.	OSHA Z1
	9. PHYSI	CAL AND CHEMICAI	L PRO	PERTIES	
Form	: Solie	d	Evapora	ation rate : N	ot applicable.
Appearance	: flake				ot determined
Color	: BLU		Bulk de	2	ot determined
Odor					ot determined
Melting point/range			Vapor d		ot determined
Boiling Point:			pН	•	ot applicable
Water solubility	: Inso		r		·····
10. STABILITY AND REACTIVITY					
Stability	: S	Stable.			
Hazardous Polymerization	a : V	Will not occur.			
	Conditions to avoid : To avoid thermal decomposition, do not overheat.				
Conditions to avoid	: 1				



MATERIAL SAFETY DATA SHEET

BLUE 2X

Version Number 1.0 Revision Date 05/16/2002

Page 4 of 5 Print Date 11/4/2011

Hazardous decomposition products

: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), dense black smoke.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ			
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.			
	12. ECOLOGIC	AL INFORMATION	I			
Persistence and degrada	bility : Not readily bi	odegradable.				
Environmental Toxicity		: Chemicals are not readily available as they are bound within the matrix of the polymer.				
Bioaccumulation Potent	ial : Not inherently	Not inherently biodegradable.				
Additional advice		: Chemicals are not readily available as they are bound within the matrix of the polymer.				
	13. DISPOSAL	CONSIDERATIONS				
Product	generator of w classification,	: Where possible, recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.				
Contaminated packagin	has the respon and disposal i	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.				
	14. TRANSPOI	RT INFORMATION				
U.S. D.O.T. / CA T.D.C Classification (Non-bull ground)		for transportation.				
ICAO/IATA	: Not regulated	for transportation.				
IMO / IMDG	: Not regulated	for transportation.				
	15. REGULATO	ORY INFORMATION	1			

MATERIAL SAFETY DATA SHEET



BLUE 2X		
Version Number 1.0 Revision Date 05/16/2002		Page 5 of 5 Print Date 11/4/2011
US Regulations:		
OSHA Status	:	Classified as hazardous based on components.
TSCA Status	:	All components of this product are listed on the TSCA inventory or are exempt.
California Proposition 65	:	This product does not contain a substance listed by California Prop 65.
Canadian Regulations:		
WHMIS Classification	:	D2B
DSL	:	Listed.
National Inventories:		
Australia AICS	:	Not determined.
China IECS	:	Not determined.
Europe EINECS	:	Not determined.
Japan ENCS	:	Not determined.
Korea KECI	:	Not determined.
Philippines PICCS	:	Not determined.

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.