



MATERIAL SAFETY DATA SHEET

Medium Tone

Version Number 1.1 Revision Date 01/21/2004 Page 1 of 8 Print Date *11/13/2011*

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	Medium Tone
Product code	:	CC10015651
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight %
8-Oxa-3,5-dithia-4-stannatetradecanoic acid, 10-ethyl-4,4-dimethyl-7-oxo-, 2-ethylhexyl ester	57583-35-4	1 - 5
Stannane, methyltris(2-ethylhexyloxycarbonylmethylth io)-	57583-34-3	1 - 5
Titanium dioxide	13463-67-7	1 - 5
Nickel iron chromite black spinel (C.I. Pigment Black 30)	71631-15-7	5 - 10

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

 Routes of Exposure:
 : Inhalation, Ingestion, Skin contact

 Acute exposure
 Inhalation

 Inhalation
 : Particulates, like other inert materials can be mechanically irritating. Excessive inhalation of product vapors, especially during heating or processing, may be irritating to respiratory system.



MATERIAL SAFETY DATA SHEET

Medium Tone

sion Number 1.1 ision Date 01/21/2004	Page 2 Print Date 11/13/2
Ingestion Eyes Skin	 May be harmful if swallowed. Particulates, like other inert materials can be mechanically irritating. Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	 Not applicable Not applicable Not applicable Carbon dioxide blanket, water spray, dry powder, foamnone.
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	 Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.



MATERIAL SAFETY DATA SHEET

Medium Tone

weaium ione	
Version Number 1.1 Revision Date 01/21/2004	Page 3 of 8 Print Date 11/13/2011
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge Heat only in areas with appropriate exhaust ventilation.
Storage	: Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.
8. EXP	OSURE CONTROLS / PERSONAL PROTECTION
Respiratory protection	: No personal respiratory protective equipment normally required.
Eye/Face Protection	: Safety glasses with side-shields.
Hand protection	: Protective gloves.
Skin and body protection	: Long sleeved clothing.
Additional Protective Measures	: Safety shoes.
General Hygiene Considerations	: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	: Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.
Exposure limit(s)	



MATERIAL SAFETY DATA SHEET

Medium Tone

Version Number 1.1 Revision Date 01/21/2004

Page 4 of 8 Print Date 11/13/2011

Components	Value	Exposure time	Exposure type	List:
8-Oxa-3,5-dithia-4-sta nnatetradecanoic acid, 10-ethyl-4,4-dimethyl- 7-oxo-, 2-ethylhexyl ester	0.1 mg/m3	PEL:	as Sn	OSHA Z1
	0.1 mg/m3	Time Weighted Average (TWA):	as Sn	ACGIH
	0.2 mg/m3	Short Term Exposure Limit (STEL):	as Sn	ACGIH
Nickel iron chromite black spinel (C.I. Pigment Black 30)	0.5 mg/m3	PEL:	as Cr	OSHA Z1
	1 mg/m3	PEL:	as Ni	OSHA Z1
	0.5 mg/m3	Time Weighted Average (TWA):	as Cr	ACGIH
	0.2 mg/m3	Time Weighted Average (TWA):	Inhalable fraction. as Ni	ACGIH
Stannane, methyltris(2-ethylhexy loxycarbonylmethylthi o)-	0.1 mg/m3	PEL:	as Sn	OSHA Z1
	0.1 mg/m3	Time Weighted Average (TWA):	as Sn	ACGIH
	0.2 mg/m3	Short Term Exposure Limit (STEL):	as Sn	ACGIH
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):		ACGIH
	15 mg/m3	PEL:	Total dust.	OSHA Z1

9. PHYSICAL AND CHEMICAL PROPERTIES

Form Appearance Color Odor Melting point/range Boiling Point: Water solubility

: Solid : Pellets : BROWN Very faint : Not determined : Not applicable : Insoluble

:

Evaporation rate Specific Gravity: Bulk density Vapor pressure Vapour density рН

Not applicable : Not determined : : Not established : Not applicable : Not applicable Not applicable :

10. STABILITY AND REACTIVITY

Stability	:	Stable.
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Avoid contact with strong oxidizers. Also, avoid contact with acetal or



MATERIAL SAFETY DATA SHEET

Medium Tone

Version Number 1.1 Revision Date 01/21/2004	Page 5 of 8 Print Date 11/13/2011
	acetal copolymers and with amine containing materials during processing. At processing conditions, these materials are mutually destructive and involve rapid degradation. Thoroughly purge and mechanically clean processing equipment to avoid even trace quantities of these materials from coming in contact with each other. Prevent cross contamination of feedstocks.
Hazardous decomposition products	 Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating (approximately 30 minutes or more) above 392 °F (200 °C) or short term heating at 482 °F (250 °C) may result in product decomposition and evolution of carbon monoxide and hydrogen chloride.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
57583-35-4	8-Oxa-3,5-dithia-4-stannat	Irritant	Eyes, Skin.
	etradecanoic acid,		
	10-ethyl-4,4-dimethyl-7-o		
	xo-, 2-ethylhexyl ester		
57583-34-3	Stannane,	Irritant	Eyes, Skin.
	methyltris(2-ethylhexylox		
	ycarbonylmethylthio)-		
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.
71631-15-7	Nickel iron chromite black	Irritant	Eyes, Skin.
	spinel (C.I. Pigment Black		
	30)		
		sensitizer	Skin.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
57583-34-3	Stannane, methyltris(2-ethylhexylox ycarbonylmethylthio)-	Oral LD50	920 mg/kg	rat

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No. Chemical Name OSHA IA	RC NTP
-------------------------------	--------



MATERIAL SAFETY DATA SHEET

Medium Tone

Version Number 1.1 Revision Date 01/21/2004 Page 6 of 8 Print Date 11/13/2011

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.2A - The component is probably carcinogenic to humans.

2B - The component is probably carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

Additional Health Hazard Information:

Nickel iron chromite black spinel (C.I. Pigment Black 30) 71631-15-7 Skin sensitizer "nickel itch", with pulmonary, brain, liver, kidney andmuscle effects.

Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the matrix of the polymer.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the matrix of the polymer.
Additional advice	: No data available
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA (air)	: Refer to specific regulation.
IMO / IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	



MATERIAL SAFETY DATA SHEET

Medium Tone

Version Number 1.1 Revision Date 01/21/2004 Page 7 of 8 Print Date 11/13/2011

OSHA Status	: Classified as hazard	-		
TSCA Status	: All components of Inventory.	this product are liste	ed on or exemp	pt from the T
. EPA CERCLA Hazardous S	Substances (40 CFR 302			
Not applicable				
California Proposition 65	: WARNING! This California to cause		hemical know	vn to the Stat
RA Title III Section 302 Extr	emely Hazardous Subst	ance		
Not applicable				
RA Title III Section 313 Toxi	ic Chemicals:			
RA Title III Section 313 Toxi	ic Chemicals:	CAS-No.	Weight	%
		CAS-No. 71631-15-7	Weight 7.88	%
Chemical Name CHROMIUM III COMP	OUNDSNICKEL			%
Chemical Name CHROMIUM III COMP COMPOUNDS CHROMIUM III COMP	OUNDSNICKEL	71631-15-7	7.88	%
Chemical Name CHROMIUM III COMP COMPOUNDS CHROMIUM III COMP COMPOUNDS	OUNDSNICKEL	71631-15-7	7.88	%
Chemical Name CHROMIUM III COMP COMPOUNDS CHROMIUM III COMP COMPOUNDS nadian Regulations: National Pollutant Releas	POUNDSNICKEL	71631-15-7 68186-90-3	0.60	
Chemical Name CHROMIUM III COMP COMPOUNDS CHROMIUM III COMP COMPOUNDS nadian Regulations: National Pollutant Releas Chemical Name	OUNDSNICKEL OUNDSANTIMONY e Inventory (NPRI)	71631-15-7 68186-90-3 CAS-No.	7.88 0.60 Weight %	NPRI ID#
Chemical Name CHROMIUM III COMP COMPOUNDS CHROMIUM III COMP COMPOUNDS nadian Regulations: National Pollutant Releas Chemical Name Nickel iron chromite black	OUNDSNICKEL OUNDSANTIMONY e Inventory (NPRI)	71631-15-7 68186-90-3	0.60	
Chemical Name CHROMIUM III COMP COMPOUNDS CHROMIUM III COMP COMPOUNDS nadian Regulations: National Pollutant Releas Chemical Name Nickel iron chromite black Black 30) Nickel iron chromite black	OUNDSNICKEL OUNDSANTIMONY e Inventory (NPRI) spinel (C.I. Pigment	71631-15-7 68186-90-3 CAS-No.	7.88 0.60 Weight %	NPRI ID#
Chemical Name CHROMIUM III COMP COMPOUNDS CHROMIUM III COMP COMPOUNDS nadian Regulations: National Pollutant Releas Chemical Name Nickel iron chromite black Black 30)	POUNDSNICKEL POUNDSANTIMONY e Inventory (NPRI) spinel (C.I. Pigment spinel (C.I. Pigment	71631-15-7 68186-90-3 CAS-No. 71631-15-7	7.88 0.60 Weight % 7.88	NPRI ID# 68
Chemical Name CHROMIUM III COMP COMPOUNDS CHROMIUM III COMP COMPOUNDS nadian Regulations: National Pollutant Releas Chemical Name Nickel iron chromite black i Black 30) Nickel iron chromite black i Black 30)	POUNDSNICKEL POUNDSANTIMONY e Inventory (NPRI) spinel (C.I. Pigment spinel (C.I. Pigment buff	71631-15-7 68186-90-3 CAS-No. 71631-15-7 71631-15-7	7.88 0.60 Weight % 7.88 7.88	NPRI ID# 68 168

WHMIS Ingredient Disclosure List

CAS-No.
57583-35-4
71631-15-7
57583-34-3



MATERIAL SAFETY DATA SHEET

Medium Tone

Version Number 1.1
Revision Date 01/21/2004

Page 8 of 8 Print Date *11/13/2011*

	DSL	:	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.	
Natio	nal Inventories:			
	Australia AICS	:	Not determined	
	China IECS	:	Not determined	
	Europe EINECS	:	Not determined	
	Japan ENCS	:	Not determined	
	Korea KECI	:	Not determined	
	Philippines PICCS	:	Not determined	
			14 OTHED INCODMATION	

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.