

MATERIAL SAFETY DATA SHEET

BLUE

Version Number 1.0 Revision Date 05/16/2002 Page 1 of 5 Print Date 11/4/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name		BLUE
Product code	:	CC10015973
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Titanium dioxide	13463-67-7	5 - 10

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating or crosslinking and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.



MATERIAL SAFETY DATA SHEET

BLUE

	4. FIRST AID MEASURES
Inhalation	 Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits	
Upper explosion limit	: Not applicable
Lower explosion limit	: Not applicable
Autoignition temperature	: Not relevant
Suitable extinguishing media	: Carbon dioxide blanket, Water spray, dry powder, foam.
Special Fire Fighting	: Fullface self-contained breathing apparatus (SCBA) used in positive
Procedures	pressure mode should be worn to prevent inhalation of airborne
	contaminants.
Unusual Fire/Explosion Hazards	: None
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	: Keep containers dry and tightly closed to avoid moisture absorption



MATERIAL SAFETY DATA SHEET

BLUE

				Р	rint Date 11/4/2	
	a	nd contamination. Keep i	n a dry,	cool place.		
8. 1	EXPOSURE	CONTROLS / PERSON	NAL PR	OTECTION		
Respiratory protection	: N	o personal respiratory pro	otective e	equipment norma	ally required.	
Eye/Face Protection	: S	afety glasses with side-sh	side-shields.			
Hand protection	: Protective gloves.					
Skin and body protection	: L	ong sleeved clothing.				
Additional Protective Measures	: S	afety shoes.				
General Hygiene Considerations	: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.					
Engineering measures	: Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.					
Exposure limit(s)						
Componento	Value	Error a survey diverse		Environmente forme	List:	
Components Titanium dioxide	10 mg/m3	Exposure time Time Weighted Avera (TWA):	ge	Exposure type Total dust.	ACGIH	
Titanium dioxide	15 mg/m3	PEL:		Total dust.	OSHA Z1	
	9. PHYSIC	CAL AND CHEMICAL	PROPE	RTIES		
					N7 / 11 11	
Form	: Solic	l E	vaporatio	on rate :	Not applicable.	
Appearance	: Solic : Pelle	l E sts Sj	vaporatio pecific C	on rate : bravity :	Not determined	
Appearance Color	: Solic : Pelle : BLU	I E ots Sj E B	vaporatio pecific C ulk dens	on rate : bravity : ity :	Not determined Not established	
Appearance Color Odor	: Solic : Pelle : BLU : Very	I E ots Sj E B y faint V	vaporatio pecific C ulk dens apor pre	on rate : Fravity : ity : ssure :	Not determined Not established Not applicable	
Appearance Color Odor Melting point/range	: Solic : Pelle : BLU : Very : Note	I E ts S ₁ E B faint V determined V	vaporatio pecific C ulk dens apor pre apor der	on rate : Fravity : ity : ssure : sity :	Not determined Not established Not applicable Not applicable	
Appearance Color Odor	: Solic : Pelle : BLU : Very : Note	l E ts Sp E B faint V determined V applicable pl	vaporatio pecific C ulk dens apor pre apor der	on rate : Fravity : ity : ssure : sity :	Not determined Not established Not applicable	
Appearance Color Odor Melting point/range Boiling Point:	: Solic : Pelle : BLU : Very : Not : Not : Insol	l E ts Sp E B faint V determined V applicable pl	vaporatio pecific C ulk dens apor pre apor der H	on rate : Fravity : ity : ssure : sity :	Not determined Not established Not applicable Not applicable	
Appearance Color Odor Melting point/range Boiling Point:	: Solic : Pelle : BLU : Very : Not : Not : Insol 10. S	l E ets Sj E B faint V determined V applicable pl uble	vaporatio pecific C ulk dens apor pre apor der H	on rate : Fravity : ity : ssure : sity :	Not determined Not established Not applicable Not applicable	
Appearance Color Odor Melting point/range Boiling Point: Water solubility	: Solic : Pelle : BLU : Very : Not (: Not (: Insol 10. S : S	I E ts S ₁ E B faint V determined V applicable pl uble STABILITY AND REAC	vaporatio pecific C ulk dens apor pre apor der H	on rate : Fravity : ity : ssure : sity :	Not determined Not established Not applicable Not applicable	
Appearance Color Odor Melting point/range Boiling Point: Water solubility Stability	: Solic : Pelle : BLU : Very : Not a : Insol 10. § n : V : K	I E ts Sj E B faint V determined V applicable pl uble STABILITY AND REAC table.	vaporatio pecific C ulk dens apor pre apor der H C TIVIT	on rate : fravity : ity : ssure : isity : Y	Not determined Not established Not applicable Not applicable Not applicable	



MATERIAL SAFETY DATA SHEET

BLUE

Version Number 1.0 Revision Date 05/16/2002 Page 4 of 5 Print Date 11/4/2011

Hazardous decomposition products

: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ			
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.			
	12. ECOLOGIO	CAL INFORMATION	I			
Persistence and degrada						
Environmental Toxicity		 Chemicals are not readily available as they are bound within the matrix of the polymer. Chemicals are not readily available as they are bound within the matrix of the polymer. 				
Bioaccumulation Poten						
Additional advice	: No data avail	able.				
	13. DISPOSAL	CONSIDERATIONS	5			
Product Contaminated packagir	possible, recy generator of v classification applicable fea ng : Recycling is p has the respon and disposal	 Like most thermoplastics the product can be recycled. Where possible, recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal. 				
	14. TRANSPO	RT INFORMATION				
U.S. D.O.T. / CA T.D.G. : Not re Classification (Non-bulk ground)		l for transportation.				
ICAO/IATA	: Not regulated	l for transportation.				
IMO / IMDG	: Not regulated	l for transportation.				
	15 DECLUAT	ORY INFORMATION	T			

MATERIAL SAFETY DATA SHEET



BLUE Version Number 1.0 Page 5 of 5 Print Date 11/4/2011 Revision Date 05/16/2002 US Regulations: **OSHA Status** : Classified as hazardous based on components. **TSCA Status** : All components of this product are listed on the TSCA inventory or are exempt. California Proposition : This product does not contain a substance listed by California Prop 65. 65 Canadian Regulations: WHMIS Classification : D2B DSL : Listed. National Inventories: Australia AICS : Listed. China IECS : Listed. **Europe EINECS** Not determined. : Japan ENCS : Listed. Korea KECI : Listed. **Philippines PICCS** : Listed.

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.