

MATERIAL SAFETY DATA SHEET

YELLOW ABS

Version Number 1.0 Revision Date 05/17/2002 Page 1 of 6 Print Date 11/4/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	YELLOW ABS
Product code	:	CC10016090
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
2,4,8,10-Tetraoxa-3,9-diphosphaspiro[5.5]un	26741-53-7	1 - 5
decane,		
3,9-bis[2,4-bis(1,1-dimethylethyl)phenoxy]-		
Titanium dioxide	13463-67-7	5 - 10

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating or crosslinking and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation	: Resin particles, like other inert materials, can be mechanically irritating.
Ingestion	: May be harmful if swallowed.
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.





ion Number 1.0 sion Date 05/17/2002	Page 2 Print Date 11/4/2
Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases o doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 Not applicable Not applicable Not relevant Carbon dioxide blanket, Water spray, dry powder, foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. None
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	 Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 1 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.

MATERIAL SAFETY DATA SHEET





YELLOW ABS					
Version Number 1.0 Revision Date 05/17/2002				Print	Page 3 of 6 Date 11/4/2011
Storage		eep containers dry and contamination. I		osed to avoid moistur, , cool place.	e absorption
8.1	EXPOSURE	CONTROLS / PE	RSONAL PI	ROTECTION	
Respiratory protection	: N	o personal respirato	ory protective	equipment normally	required.
Eye/Face Protection	: S	afety glasses with si	ide-shields.		
Hand protection	: P	rotective gloves.			
Skin and body protection	: L	ong sleeved clothin	g.		
Additional Protective Measures	: S	afety shoes.			
General Hygiene Considerations				ndustrial hygiene and s the end of workday.	safety practice.
Engineering measures		eat only in areas wi		e exhaust ventilation. machinery.	Provide
Exposure limit(s)					
Components	Value	Exposure ti	me	Exposure type	List:
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):		Total dust.	ACGIH
Titanium dioxide	15 mg/m3	PEL:		Total dust.	OSHA Z1
	9. PHYSIC	CAL AND CHEMI	CAL PROP	ERTIES	
Form Appearance Color Odor Melting point/range Boiling Point: Water solubility	: Very : Not o	ts LOW faint determined applicable	Evaporat Specific Bulk den Vapor pr Vapor de pH	Gravity : Not isity : Not ressure : Not ensity : Not	t applicable. t determined t established t applicable t applicable t applicable
	10. 8	STABILITY AND	REACTIVIT	ГҮ	
Stability	: S	table.			
Hazardous Polymerizatio	n : W	/ill not occur.			



MATERIAL SAFETY DATA SHEET

YELLOW ABS

Version Number 1.0 Revision Date 05/17/2002		Page 4 of 6 Print Date <i>11/4/2011</i>
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
26741-53-7	2,4,8,10-Tetraoxa-3,9-diph osphaspiro[5.5]undecane, 3,9-bis[2,4-bis(1,1-dimeth ylethyl)phenoxy]-	toxic	Refer to MSDS for Toxicity Data
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

LC50 / LD50

This product contains the following components which in their pure form have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
26741-53-7	2,4,8,10-Tetraoxa-3,9-diph	LC50	> 2 gm/m3	rat
	osphaspiro[5.5]undecane,	Oral LD50	5,580 mg/kg	rat
	3,9-bis[2,4-bis(1,1-dimeth	Dermal LD50	> 200 mg/kg	rabbit
	ylethyl)phenoxy]-			

12. ECOLOGICAL INFORMATION Persistence and degradability : Not readily biodegradable. Environmental Toxicity Chemicals are not readily available as they are bound within the matrix : of the polymer. **Bioaccumulation Potential** Chemicals are not readily available as they are bound within the matrix : of the polymer. Additional advice No data available. · 13. DISPOSAL CONSIDERATIONS Product : Like most thermoplastics the product can be recycled. Where possible, recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. Contaminated packaging : Recycling is preferred when possible. The generator of waste material



MATERIAL SAFETY DATA SHEET

YELLOW ABS

		has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	1	4. TRANSPORT INFORMATION
U.S. D.O.T. / CA T.D.G. Classification (Non-bulk ground)	:	Not regulated for transportation.
ICAO/IATA	:	Not regulated for transportation.
IMO / IMDG	:	Not regulated for transportation.
	15	. REGULATORY INFORMATION
US Regulations:		
OSHA Status	:	Classified as hazardous based on components.
TSCA Status	:	All components of this product are listed on the TSCA inventory or ar exempt.
California Proposition 65	:	This product does not contain a substance listed by California Prop 65
Canadian Regulations:		
WHMIS Classification	:	D1B
DSL	:	Listed.
National Inventories:		
Australia AICS	:	Listed.
China IECS	:	Listed.
Europe EINECS	:	Not determined.
Japan ENCS	:	Not determined.
Korea KECI	:	Not determined.
Philippines PICCS	:	Listed.
		16. OTHER INFORMATION

MATERIAL SAFETY DATA SHEET



YELLOW ABS

Version Number 1.0 Revision Date 05/17/2002 Page 6 of 6 Print Date 11/4/2011

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.