

MATERIAL SAFETY DATA SHEET

GREY

Version Number 1.0 Revision Date 05/20/2002 Page 1 of 7 Print Date 11/4/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902	
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).	
Product name	:	GREY	
Product code	:	CC10016327	
Chemical Name	:	Mixture	
CAS-No.	:	Mixture	
Product Use	:	Industrial Applications	

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Carbon black	1333-86-4	1 - 5
Chromium (III) oxide	1308-38-9	1 - 5
Titanium dioxide	13463-67-7	30 - 60

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating or crosslinking and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure::Inhalation, Ingestion, Skin contact				
Acute exposure				
Inhalation Ingestion Eyes Skin	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Particulates, like other inert materials can be mechanically irritating. Experience shows no unusual dermatitis hazard from routine handling. 			
Chronic exposure	: Refer to Section 11 for Toxicological Information.			
Medical Conditions Aggravated by Exposure:	: None known.			



MATERIAL SAFETY DATA SHEET

GREY

sion Date 05/20/2002	Print Date 11/4/2
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seel medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit	: Not applicable
Lower explosion limit	: Not applicable
Autoignition temperature	: Not relevant
Suitable extinguishing media	: Carbon dioxide blanket, Water spray, dry powder, foam.
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	: none
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by scoop or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 12 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	: Keep containers dry and tightly closed to avoid moisture absorption



MATERIAL SAFETY DATA SHEET

GREY

			Print I	Page 3 Date 11/4/2		
and contamination. Keep in a dry, cool place.						
8. I	EXPOSURE	CONTROLS / PERSONAL	PROTECTION			
Respiratory protection		o personal respiratory protect usty conditions occur wear ap				
Eye/Face Protection	: sa	afety glasses				
Hand protection	: P1	rotective gloves.				
Skin and body protection	: L	ong sleeved clothing.				
Additional Protective Measures	: Sa	afety shoes.				
General Hygiene Considerations						
Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.						
	aŗ	ppropriate exhaust ventilation	at machinery.			
Exposure limit(s)	aŗ	opropriate exhaust ventilation	at machinery.			
Exposure limit(s) Components	ar Value	ppropriate exhaust ventilation	at machinery. Exposure type	List:		
		Exposure time Time Weighted Average		List: ACGIH		
Components	Value	Exposure time	Exposure type Total dust. as carbon			
Components Carbon black	Value 3.5 mg/m3	Exposure time Time Weighted Average (TWA): PEL: Time Weighted Average	Exposure type Total dust. as carbon black Total dust. as carbon	ACGIH		
Components Carbon black Carbon black	Value 3.5 mg/m3 3.5 mg/m3	Exposure time Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): Time Weighted Average	Exposure type Total dust. as carbon black Total dust. as carbon	ACGIH OSHA Z1		
Components Carbon black Carbon black Chromium (III) oxide	Value 3.5 mg/m3 3.5 mg/m3 0.5 mg/m3	Exposure time Time Weighted Average (TWA): PEL: Time Weighted Average (TWA):	Exposure type Total dust. as carbon black Total dust. as carbon black	ACGIH OSHA Z1 ACGIH		
Components Carbon black Carbon black Chromium (III) oxide Titanium dioxide	Value 3.5 mg/m3 3.5 mg/m3 0.5 mg/m3 10 mg/m3 15 mg/m3	Exposure time Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): Time Weighted Average (TWA):	Exposure type Total dust. as carbon black Total dust. as carbon black Total dust. Total dust.	ACGIH OSHA Z1 ACGIH ACGIH		
Components Carbon black Carbon black Chromium (III) oxide Titanium dioxide Titanium dioxide	Value 3.5 mg/m3 3.5 mg/m3 0.5 mg/m3 10 mg/m3 15 mg/m3 9. PHYSIC	Exposure time Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): Time Weighted Average (TWA): PEL: PEL: CAL AND CHEMICAL PR(Exposure type Total dust. as carbon black Total dust. as carbon black Total dust. Total dust. DPERTIES	ACGIH OSHA Z1 ACGIH ACGIH OSHA Z1		
Components Carbon black Carbon black Chromium (III) oxide Titanium dioxide Titanium dioxide	Value 3.5 mg/m3 3.5 mg/m3 0.5 mg/m3 10 mg/m3 15 mg/m3 9. PHYSIC : Solid	Exposure time Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO	Exposure type Total dust. as carbon black Total dust. as carbon black Total dust. Total dust. DPERTIES ration rate : Not	ACGIH OSHA Z1 ACGIH ACGIH OSHA Z1 applicable.		
Components Carbon black Carbon black Chromium (III) oxide Titanium dioxide Titanium dioxide	Value 3.5 mg/m3 3.5 mg/m3 0.5 mg/m3 10 mg/m3 15 mg/m3 9. PHYSIC : Solid : flakes	Exposure time Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO S Specifi	Exposure type Total dust. as carbon black Total dust. as carbon black Total dust. Total dust. DPERTIES ration rate : Not ic Gravity : Not	ACGIH OSHA Z1 ACGIH ACGIH OSHA Z1 applicable. determined		
Components Carbon black Carbon black Chromium (III) oxide Titanium dioxide Titanium dioxide Form Appearance Color	Value 3.5 mg/m3 3.5 mg/m3 0.5 mg/m3 10 mg/m3 15 mg/m3 9. PHYSIC : Solid : flake : GRE	Exposure time Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO S Specify Y Bulk of	Exposure type Total dust. as carbon black Total dust. as carbon black Total dust. Total dust. Total dust. DPERTIES ration rate : Not fic Gravity : Not lensity : Not	ACGIH OSHA Z1 ACGIH ACGIH OSHA Z1 applicable. determined determined		
Components Carbon black Carbon black Chromium (III) oxide Titanium dioxide Titanium dioxide Form Appearance Color Odor	Value 3.5 mg/m3 3.5 mg/m3 0.5 mg/m3 10 mg/m3 15 mg/m3 9. PHYSIC : Solid : flake: : GRE : Very	Exposure time Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO L Evapo s Specifi Y Bulk of faint Vapor	Exposure type Total dust. as carbon black Total dust. as carbon black Total dust. as carbon black Total dust. OPERTIES ration rate : Not lensity : Not pressure : Not	ACGIH OSHA Z1 ACGIH ACGIH OSHA Z1 applicable. determined determined		
Components Carbon black Carbon black Chromium (III) oxide Titanium dioxide Titanium dioxide Form Appearance Color	Value 3.5 mg/m3 3.5 mg/m3 0.5 mg/m3 10 mg/m3 15 mg/m3 9. PHYSIC : Solid : flake: : GRE : Very : Great	Exposure time Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO L Evapo s Specifi Y Bulk of faint Vapor	Exposure type Total dust. as carbon black Total dust. as carbon black Total dust. as carbon black Total dust. DPERTIES ration rate : Not ic Gravity : Not pressure : Not density : Not	ACGIH OSHA Z1 ACGIH ACGIH OSHA Z1 applicable. determined determined		

Stability

: Stable.



MATERIAL SAFETY DATA SHEET

GREY

Version Number 1.0 Revision Date 05/20/2002		Page 4 of 7 Print Date 11/4/2011
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), dense black smoke.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1333-86-4	Carbon black	Systemic effects	Eyes, Respiratory system.
1308-38-9	Chromium (III) oxide	Irritant	Eyes, Skin.
		sensitizer	Skin.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

LC50 / LD50

This product contains the following components which in their pure form have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
1333-86-4	Carbon black	Oral LD50	>15,400 mg/kg	rat
		Dermal LD50	> 3 gm/kg	rabbit

Carcinogenicity:

This product contains the following components which in their pure form have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
1333-86-4	Carbon black	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

Additional Health Hazard Information:



MATERIAL SAFETY DATA SHEET

GREY

Version Number 1.0	Page 5 of 7
Revision Date 05/20/2002	Print Date 11/4/2011

Carbon black 1333-86-4 Carcinogenicity: Many inhalation toxicologists believe that the tumor response observed in the referenced rat studies is species specific and does not correlate to human exposure. However, the IARC evaluation in Monograph Volume 65, issued in April 1996 concluded that, "There is sufficient evidence in experimental animals for the carcinogenicity of carbon black". Based on this evaluation, along with their evaluation of inadequate evidence of carcinogenicity in humans, IARC's overall evaluation is that "Carbon Black is possibly carcinogenic to humans (Group 2B). Carbon Black has not been listed as a carcinogen by the National Toxicology Program (NTP) or the Occupational Safety and Health Administration (OSHA). The National Institute of Occupational Safety and Health (NIOSH) criteria document on carbon black recommends that only carbon black with PAH (polynuclear aromatic hydrocarbon) levels greater than 0.1% be considered suspect carcinogens.

Additional Health Hazard Information:

Chromium (III) oxide 1308-38-9 The trivalent form has a low order of acute toxicity but may cause dermatitis, pulmonary sensitization and corrosive effect on eyes.

Persistence and degradability	: Not readily biodegradable.			
Environmental Toxicity	Chemicals are not readily available as they are bound within the matrix of the polymer.			
Bioaccumulation Potential	: Not inherently biodegradable.			
Additional advice	: Chemicals are not readily available as they are bound within the matri of the polymer.			
	13. DISPOSAL CONSIDERATIONS			
Product	: Where possible, recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.			
Contaminated packaging	: Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.			
	14. TRANSPORT INFORMATION			
U.S. D.O.T. / CA T.D.G. Classification (Non-bulk ground)	: Not regulated for transportation.			
ICAO/IATA	: Not regulated for transportation.			
IMO / IMDG	: Not regulated for transportation.			
	15. REGULATORY INFORMATION			



MATERIAL SAFETY DATA SHEET

GREY

Version Number 1.0 Revision Date 05/20/2002			Print Da	Page 6 of 7 ate 11/4/2011
US Regulations:				
OSHA Status :	Classified as hazar	dous based on cor	nponents.	
TSCA Status :	TSCA Status : All components of this product are listed on the TSCA inventory or a exempt.			entory or are
California Proposition : 65	This product does	not contain a subst	tance listed by Califor	nia Prop 65.
SARA Title III Section 313 Toxic C	Chemicals:			
Chemical Name		CAS-No.	Weight %]
CHROMIUM III CO	OMPOUNDS	1308-38-9	3.30	
WHMIS Classification : WHMIS Ingredient Disclosu CAS-No. 1333-86-4 1308-38-9 DSL :	D2B tre List Listed.			
National Inventories:				
Australia AICS :	Listed.			
China IECS :	Listed.			
Europe EINECS :	Not determined.			
Japan ENCS :	Listed.			
Korea KECI :	Listed.			
Philippines PICCS :	Listed.			
	16. OTHER INF	ORMATION		

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

MATERIAL SAFETY DATA SHEET

GREY

Version Number 1.0 Revision Date 05/20/2002



Page 7 of 7 Print Date 11/4/2011