

MATERIAL SAFETY DATA SHEET

BLUE GRANITE

Version Number 1.0 Revision Date 05/20/2002 Page 1 of 5 Print Date 11/4/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	BLUE GRANITE
Product code	:	CC10016367
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Titanium dioxide	13463-67-7	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating or crosslinking and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.



MATERIAL SAFETY DATA SHEET

BLUE GRANITE

ion Number 1.0 sion Date 05/20/2002	Page 2 Print Date 11/4/
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for a least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	 Not applicable Not applicable Not relevant Carbon dioxide blanket, Water spray, dry powder, foam.
Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. None
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 1 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	: Keep containers dry and tightly closed to avoid moisture absorption



MATERIAL SAFETY DATA SHEET

BLUE GRANITE

ision Date 05/20/2002			Prin	Page 3 at Date 11/4/2		
and contamination. Keep in a dry, cool place.						
8. H	EXPOSURE	CONTROLS / PERSONA	L PROTECTION			
Respiratory protection	: N	o personal respiratory prote	ective equipment normall	y required.		
Eye/Face Protection	: S	: Safety glasses with side-shields.				
Hand protection	: Protective gloves.					
Skin and body protection	: Long sleeved clothing.					
Additional Protective Measures	: S					
General Hygiene Considerations	: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.					
Engineering measures		eat only in areas with appropriate exhaust ventilation		n. Provide		
Exposure limit(s)						
1	X 7.1			.		
Components	Value	Exposure time	Exposure type	List:		
Components Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):		ACGIH		
		Time Weighted Average				
Titanium dioxide	10 mg/m3 15 mg/m3	Time Weighted Average (TWA):	Total dust. Total dust.	ACGIH		
Titanium dioxide Titanium dioxide	10 mg/m3 15 mg/m3 9. PHYSIC	Time Weighted Average (TWA): PEL: CAL AND CHEMICAL P	Total dust. Total dust. ROPERTIES	ACGIH OSHA Z1		
Titanium dioxide Titanium dioxide	10 mg/m3 15 mg/m3	Time Weighted Average (TWA): PEL: CAL AND CHEMICAL P	Total dust. Total dust. ROPERTIES poration rate : No	ACGIH		
Titanium dioxide Titanium dioxide	10 mg/m3 15 mg/m3 9. PHYSIC : Solic	Time Weighted Average (TWA): PEL: CAL AND CHEMICAL P I Eva ts Spe	Total dust. Total dust. ROPERTIES poration rate : No cific Gravity : No	ACGIH OSHA Z1 ot applicable.		
Titanium dioxide Titanium dioxide Form Appearance	10 mg/m3 15 mg/m3 9. PHYSIC : Solic : Pelle	Time Weighted Average (TWA): PEL: CAL AND CHEMICAL P I Eva ts Spe E Bul	Total dust. Total dust. ROPERTIES poration rate : No cific Gravity : No k density : No	ACGIH OSHA Z1 ot applicable. ot determined		
Titanium dioxide Titanium dioxide Titanium dioxide Form Appearance Color Odor Melting point/range	10 mg/m3 15 mg/m3 9. PHYSIC : Solid : Pelle : BLU : Very : Not of	Time Weighted Average (TWA): PEL: CAL AND CHEMICAL P I Eva ts Spe E Bul faint Vag determined Vag	Total dust. Total dust. ROPERTIES poration rate : No cific Gravity : No k density : No por pressure : No por density : No	ACGIH OSHA Z1 ot applicable. ot determined ot established ot applicable ot applicable		
Titanium dioxide Titanium dioxide Titanium dioxide Form Appearance Color Odor Melting point/range Boiling Point:	10 mg/m3 15 mg/m3 9. PHYSIC : Solid : Pelle : BLU : Very : Not a : Not a	Time Weighted Average (TWA): PEL: CAL AND CHEMICAL P I Eva ts Spe E Bul faint Vap determined Vap applicable pH	Total dust. Total dust. ROPERTIES poration rate : No cific Gravity : No k density : No por pressure : No por density : No	ACGIH OSHA Z1 ot applicable. ot determined ot established ot applicable		
Titanium dioxide Titanium dioxide Titanium dioxide Form Appearance Color Odor Melting point/range	10 mg/m3 15 mg/m3 9. PHYSIC : Solid : Pelle : BLU : Very : Not of	Time Weighted Average (TWA): PEL: CAL AND CHEMICAL P I Eva ts Spe E Bul faint Vap determined Vap applicable pH	Total dust. Total dust. ROPERTIES poration rate : No cific Gravity : No k density : No por pressure : No por density : No	ACGIH OSHA Z1 ot applicable. ot determined ot established ot applicable ot applicable		
Titanium dioxide Titanium dioxide Titanium dioxide Form Appearance Color Odor Melting point/range Boiling Point:	10 mg/m3 15 mg/m3 9. PHYSIC : Solic : Pelle : BLU : Very : Not a : Insol	Time Weighted Average (TWA): PEL: CAL AND CHEMICAL P I Eva ts Spe E Bul faint Vap determined Vap applicable pH	Total dust. Total dust. ROPERTIES poration rate : No cific Gravity : No k density : No por density : No : No : No : No : No	ACGIH OSHA Z1 ot applicable. ot determined ot established ot applicable ot applicable		
Titanium dioxide Titanium dioxide Titanium dioxide Form Appearance Color Odor Melting point/range Boiling Point:	10 mg/m3 15 mg/m3 9. PHYSIC : Solid : Pelle : BLU : Very : Not a : Insol 10. S	Time Weighted Average (TWA): PEL: CAL AND CHEMICAL P I Eva ts Spe E Bul faint Vap determined Vap applicable pH uble	Total dust. Total dust. ROPERTIES poration rate : No cific Gravity : No k density : No por density : No : No : No : No : No	ACGIH OSHA Z1 ot applicable. ot determined ot established ot applicable ot applicable		
Titanium dioxide Titanium dioxide Titanium dioxide Form Appearance Color Odor Melting point/range Boiling Point: Water solubility	10 mg/m3 15 mg/m3 9. PHYSIC : Solid : Pelle : BLU : Very : Not a : Insol 10. S : S	Time Weighted Average (TWA): PEL: CAL AND CHEMICAL P I Eva ts Spe E Bul faint Vap determined Vap applicable pH uble	Total dust. Total dust. ROPERTIES poration rate : No cific Gravity : No k density : No por density : No : No : No : No : No	ACGIH OSHA Z1 ot applicable. ot determined ot established ot applicable ot applicable		
Titanium dioxide Titanium dioxide Titanium dioxide Form Appearance Color Odor Melting point/range Boiling Point: Water solubility Stability	10 mg/m3 15 mg/m3 9. PHYSIC : Solid : Pelle : BLU : Very : Not a : Insol 10. S n : W : K	Time Weighted Average (TWA): PEL: CAL AND CHEMICAL P I Eva ts Spe E Bul faint Vap determined Vap applicable pH uble CTABILITY AND REACT table.	Total dust. Total dust. ROPERTIES poration rate : No cific Gravity : No cor pressure : No por density : No cific TVITY : No	ACGIH OSHA Z1 ot applicable. ot determined ot established ot applicable ot applicable		



MATERIAL SAFETY DATA SHEET

BLUE GRANITE

Version Number 1.0 Revision Date 05/20/2002 Page 4 of 5 Print Date 11/4/2011

Hazardous decomposition products

: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ			
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.			
	12. ECOLOGIO	CAL INFORMATION	I			
Persistence and degrad						
Environmental Toxicity		: Chemicals are not readily available as they are bound within the matrix of the polymer.				
Bioaccumulation Poten		: Chemicals are not readily available as they are bound within the matrix of the polymer.				
Additional advice	: No data avail	able.				
	13. DISPOSAL	CONSIDERATIONS				
Product Contaminated packagir	possible, recy generator of v classification applicable fee g : Recycling is p has the respon and disposal i	 Like most thermoplastics the product can be recycled. Where possible, recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. 				
	14. TRANSPO	RT INFORMATION				
U.S. D.O.T. / CA T.D. Classification (Non-bul ground)	e	for transportation.				
ICAO/IATA	: Not regulated	for transportation.				
IMO / IMDG	: Not regulated	for transportation.				
	15. REGULATO	DRY INFORMATION	N			

MATERIAL SAFETY DATA SHEET



BLUE GRANITE

Version Number 1.0 Revision Date 05/20/2002		Page 5 of 5 Print Date 11/4/2011
US Regulations:		
OSHA Status	:	Classified as hazardous based on components.
TSCA Status	:	All components of this product are listed on the TSCA inventory or are exempt.
California Proposition 65	:	This product does not contain a substance listed by California Prop 65.
Canadian Regulations:		
WHMIS Classification	:	D2B
DSL	:	Listed.
National Inventories:		
Australia AICS	:	Listed.
China IECS	:	Listed.
Europe EINECS	:	Not determined.
Japan ENCS	:	Listed.
Korea KECI	:	Listed.
Philippines PICCS	:	Listed.

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.