

MATERIAL SAFETY DATA SHEET

# 10095055 GRAY UV

Version Number 1.0 Revision Date 05/22/2002 Page 1 of 7 Print Date 11/4/2011

### 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	10095055 GRAY UV
Product code	:	CC10016560
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

#### 2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Carbon black	1333-86-4	0.1 - 1
Rutile, antimony chromium buff	68186-90-3	0.1 - 1
Titanium dioxide	13463-67-7	10 - 30

#### 3. HAZARDS IDENTIFICATION

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating or crosslinking and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

#### POTENTIAL HEALTH EFFECTS

<b>Routes of Exposure:</b>	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes	<ul> <li>Resin particles, like other inert materials, can be mechanically irritating.</li> <li>May be harmful if swallowed.</li> <li>Resin particles, like other inert materials, are mechanically irritating to eves.</li> </ul>
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.



MATERIAL SAFETY DATA SHEET

# 10095055 GRAY UV

sion Date 05/22/2002	Print Date 11/4/2
Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases o doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for a least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	<ul> <li>Not applicable</li> <li>Not applicable</li> <li>Not relevant</li> <li>Carbon dioxide blanket, Water spray, dry powder, foam.</li> </ul>
Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	<ul> <li>Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.</li> <li>None</li> </ul>
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should no be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 1 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.

### MATERIAL SAFETY DATA SHEET

# 10095055 GRAY UV



Version Number 1.0 Revision Date 05/22/2002		Page 3 of 7 Print Date 11/4/2011
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.
8. EXP	OSUR	RE CONTROLS / PERSONAL PROTECTION
Respiratory protection	:	No personal respiratory protective equipment normally required.
Eye/Face Protection	:	Safety glasses with side-shields.
Hand protection	:	Protective gloves.
Skin and body protection	:	Long sleeved clothing.
Additional Protective Measures	:	Safety shoes.
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Carbon black	3.5 mg/m3	Time Weighted Average (TWA):	Total dust. as carbon black	ACGIH
Carbon black	3.5 mg/m3	PEL:	Total dust. as carbon black	OSHA Z1
Rutile, antimony chromium buff	0.5 mg/m3	Time Weighted Average (TWA):		MX OEL
	0.5 mg/m3	Time Weighted Average (TWA):	Total dust. as Cr	ACGIH
Rutile, antimony chromium buff	0.5 mg/m3	PEL:	Total dust. as Cr	OSHA Z1
Rutile, antimony chromium buff	0.5 mg/m3	Time Weighted Average (TWA):		MX OEL
	0.5 mg/m3	Time Weighted Average (TWA):	Dust. as Sb	ACGIH
Rutile, antimony chromium buff	0.5 mg/m3	PEL:	Total dust. as Sb	OSHA Z1
Rutile, antimony chromium buff	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	MX OEL
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):	Total dust.	ACGIH
Titanium dioxide	15 mg/m3	PEL:	Total dust.	OSHA Z1

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

#### MATERIAL SAFETY DATA SHEET

# 10095055 GRAY UV

Version Number 1.0 Revision Date 05/22/2002			Page 4 of 7 Print Date 11/4/2011
Form Appearance Color Odor Melting point/range Boiling Point: Water solubility	<ul> <li>Solid</li> <li>Pellets</li> <li>GREY</li> <li>Very faint</li> <li>Not determined</li> <li>Not applicable</li> <li>Insoluble</li> </ul>	Evaporation rate Specific Gravity Bulk density Vapor pressure Vapor density pH	<ul> <li>Not applicable.</li> <li>Not determined</li> <li>Not established</li> <li>Not applicable</li> <li>Not applicable</li> <li>Not applicable</li> </ul>
	10. STABILITY AND	REACTIVITY	
Stability	: Stable.		
Hazardous Polymerization	: Will not occur.		

5		
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

#### **11. TOXICOLOGICAL INFORMATION**

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

**Toxicity Overview** 

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1333-86-4	Carbon black	Systemic effects	Eyes, Respiratory system.
68186-90-3	Rutile, antimony chromium buff	Irritant	Eyes, Skin.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

LC50 / LD50

This product contains the following components which in their pure form have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
1333-86-4	Carbon black	Oral LD50	>15,400 mg/kg	rat
		Dermal LD50	> 3 gm/kg	rabbit

Carcinogenicity:

This product contains the following components which in their pure form have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
1333-86-4	Carbon black	no	2B	no





MATERIAL SAFETY DATA SHEET

# 10095055 GRAY UV

Version Number 1.0

Page 5 of 7

|--|

ision Date 05/22/2002			Pri	nt Date 11/4/2011
	1		2	
68186-90-3 Rutile, buff	antimony chromium	no	3	no
IARC Carcinogen Classification 1 - The component is carcinoge 2A - The component is probabl 2B - The component is possibly NTP Carcinogen Classification 1 - The component is known to 2 - The component is reasonabl <u>Additional Health Hazard Inf</u> Carbon black 1333-86-4 Ca response observed in the refer exposure. However, the IARC "There is sufficient evidence i this evaluation, along with the overall evaluation is that "Ca has not been listed as a carcin and Health Administration (C criteria document on carbon I hydrocarbon) levels greater th <u>Additional Health Hazard Inf</u> Rutile, antimony chromium b Symptoms may include redne skin contact may include: anti-	enic to humans. y carcinogenic to humany carcinogenic to humany carcinogenic to humany s: be a human carcinogen. y anticipated to be a hum formation: arcinogenicity: Many in renced rat studies is specent C evaluation in Monogra in experimental animal eir evaluation of inadequation of inadequation pron Black is possibly of ogen by the National To DSHA). The National To DSH	nan carcinogen. nhalation toxicolo ecies specific and o raph Volume 65, i s for the carcinog juate evidence of o carcinogenic to hu oxicology Prograr institute of Occupa t only carbon blac d suspect carcinog cause eye irritatio , and other skin da pimply rash).	does not correla ssued in April 1 enicity of carbo carcinogenicity imans (Group 2 n (NTP) or the ( ational Safety a k with PAH (po gens.	ate to human 1996 concluded tha n black''. Based o in humans, IARC' 2B). Carbon Black Occupational Safet nd Health (NIOSE olynuclear aromati
	12. ECOLOGICAL	INFORMATION		
Persistence and degradability				
,	: Not readily biodeg	radable.		

**Bioaccumulation Potential** : Chemicals are not readily available as they are bound within the matrix of the polymer.

Additional advice

: No data available.

#### **13. DISPOSAL CONSIDERATIONS**

Product	: Like most thermoplastics the product can be recycled. Where possible, recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.	
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation	[



MATERIAL SAFETY DATA SHEET

# 10095055 GRAY UV

ion Number 1.0 sion Date 05/22/2002	Page 6 Print Date 11/4/2	
	and disposal in accordance with applicable federal, state/provincial and local regulations.	
	14. TRANSPORT INFORMATION	
U.S. D.O.T. / CA T.D.G. Classification (Non-bulk ground)	Not regulated for transportation.	
ICAO/IATA	: Not regulated for transportation.	
IMO / IMDG	: Not regulated for transportation.	
	15. REGULATORY INFORMATION	
US Regulations:		
OSHA Status	: Classified as hazardous based on components.	
TSCA Status	: All components of this product are listed on the TSCA inventory or an exempt.	
California Proposition 65	: This product does not contain a substance listed by California Prop 65	
Canadian Regulations:		
WHMIS Classification	: D2B	
WHMIS Ingredient Disc	losure List	
CAS-No. 1333-86-4 1309-37-1 68186-90-3		
DSL	: Listed.	
National Inventories:		
Australia AICS	: Listed.	
China IECS	: Listed.	
Europe EINECS	: Not determined.	
Japan ENCS	: Not determined.	
Korea KECI	: Listed.	
Philippines PICCS	: Listed.	



MATERIAL SAFETY DATA SHEET

# 10095055 GRAY UV

Version Number 1.0 Revision Date 05/22/2002 Page 7 of 7 Print Date 11/4/2011

### **16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.