

MATERIAL SAFETY DATA SHEET

GREEN NT 6052

Version Number 1.0 Revision Date 06/06/2002 Page 1 of 6 Print Date 11/4/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	GREEN NT 6052
Product code	:	CC10017260
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Silica, amorphous	7631-86-9	1 - 5
Titanium dioxide	13463-67-7	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.



MATERIAL SAFETY DATA SHEET

GREEN NT 6052

ion Number 1.0 sion Date 06/06/2002	Page 2 Print Date 11/4/2
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist, or in all cases of doubt, seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist, or in all cases of doubt, seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for a least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	 Not applicable Not applicable Not relevant Carbon dioxide blanket, Water spray, dry powder, foam.
Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. None
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should no be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 1 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	: Keep containers dry and tightly closed to avoid moisture absorption



MATERIAL SAFETY DATA SHEET

GREEN NT 6052

				Print Da	Page ate 11/4/
	a	nd contamination. Keep i	n a dry, cool place.		
8. E	XPOSURE	CONTROLS / PERSON	AL PROTECTIO	DN	
Respiratory protection	: N	o personal respiratory pro	tective equipment	normally rec	quired.
Eye/Face Protection	: Safety glasses with side-shields.				
Hand protection	: P	rotective gloves.			
Skin and body protection	: L	Long sleeved clothing.			
Additional Protective Measures	: S	afety shoes.			
General Hygiene Considerations		andle in accordance with ash hands before breaks			ety practic
Engineering measures	: Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.				
Exposure limit(s)					
Components	Value	Exposure time	Exposure	e type	List:
Silica, amorphous	20 mppcf	PEL:	Total d		OSHA
Silica, amorphous	20 mppcf	PEL:	Total d	ust.	Z3
	1.1		Total d	ust.	Z3
Silica, amorphous	20 mppcf	PEL: Time Weighted Averag	Total d	ust. ust.	Z3 ACGIH
Silica, amorphous Titanium dioxide	20 mppcf 10 mg/m3 15 mg/m3	PEL: Time Weighted Averag (TWA):	Total d ge Total d Total d	ust. ust.	
Silica, amorphous Titanium dioxide Titanium dioxide	20 mppcf 10 mg/m3 15 mg/m3 9. PHYSIC	PEL: Time Weighted Averag (TWA): PEL: CAL AND CHEMICAL	Total d ge Total d Total d PROPERTIES	ust. ust.	Z3 ACGIH OSHA Z
Silica, amorphous Titanium dioxide Titanium dioxide	20 mppcf 10 mg/m3 15 mg/m3 9. PHYSIC : Solid	PEL: Time Weighted Averag (TWA): PEL: CAL AND CHEMICAL	Total d ge Total d Total d PROPERTIES	ust. ust. : Not a	Z3 ACGIH OSHA Z pplicable.
Silica, amorphous Titanium dioxide Titanium dioxide Form Appearance	20 mppcf 10 mg/m3 15 mg/m3 9. PHYSIC : Solic : Pelle	PEL: Time Weighted Averag (TWA): PEL: CAL AND CHEMICAL I Events SI	Total d ge Total d Total d PROPERTIES	ust. ust. : Not aj : Not d	Z3 ACGIH OSHA Z pplicable.
Silica, amorphous Titanium dioxide Titanium dioxide Form Appearance Color	20 mppcf 10 mg/m3 15 mg/m3 9. PHYSIC : Solic : Pelle : GRE	PEL: Time Weighted Averag (TWA): PEL: CAL AND CHEMICAL I E ¹ Sts Sp EN Bi	Total d Total d Total d Total d PROPERTIES	ust. ust. : Not aj : Not de : Not es	Z3 ACGIH OSHA Z pplicable. etermined stablished
Silica, amorphous Titanium dioxide Titanium dioxide Form Appearance Color Odor	20 mppcf 10 mg/m3 15 mg/m3 9. PHYSIC : Solic : Pelle : GRE : Very	PEL: Time Weighted Averag (TWA): PEL: CAL AND CHEMICAL CAL AND CHEMICAL EN EN Faint	Total d Total d Total d Total d PROPERTIES vaporation rate pecific Gravity ilk density apor pressure	ust. ust. : Not aj : Not de : Not es : Not aj	Z3 ACGIH OSHA Z pplicable. etermined stablished pplicable
Silica, amorphous Titanium dioxide Titanium dioxide Form Appearance Color Odor Melting point/range	20 mppcf 10 mg/m3 15 mg/m3 9. PHYSIC : Solid : Pelle : GRE : Very : Not of	PEL: Time Weighted Averag (TWA): PEL: CAL AND CHEMICAL CAL AND CHEMICAL EN Bi EN Bi faint V determined V	Total d Total d Total d Total d PROPERTIES vaporation rate pecific Gravity ilk density apor pressure apor density	ust. ust. : Not aj : Not de : Not es : Not aj : Not aj	Z3 ACGIH OSHA Z pplicable. etermined stablished pplicable pplicable
Silica, amorphous Titanium dioxide Titanium dioxide Titanium dioxide Form Appearance Color Odor Melting point/range Boiling Point:	20 mppcf 10 mg/m3 15 mg/m3 9. PHYSIC : Solid : Pelle : GRE : Very : Not a : Not a	PEL: Time Weighted Averag (TWA): PEL: CAL AND CHEMICAL CAL AND CHEMICAL EN Bit EN Bit faint V determined V applicable pI	Total d Total d Total d Total d PROPERTIES vaporation rate pecific Gravity ilk density apor pressure apor density	ust. ust. : Not aj : Not de : Not es : Not aj : Not aj	Z3 ACGIH OSHA Z pplicable. etermined stablished pplicable
Silica, amorphous Titanium dioxide Titanium dioxide Form Appearance Color Odor Melting point/range	20 mppcf 10 mg/m3 15 mg/m3 9. PHYSIC : Solid : Pelle : GRE : Very : Not of	PEL: Time Weighted Averag (TWA): PEL: CAL AND CHEMICAL CAL AND CHEMICAL EN Bit EN Bit faint V determined V applicable pI	Total d Total d Total d Total d PROPERTIES vaporation rate pecific Gravity ilk density apor pressure apor density	ust. ust. : Not aj : Not de : Not es : Not aj : Not aj	Z3 ACGIH OSHA Z pplicable. etermined stablished pplicable pplicable
Silica, amorphous Titanium dioxide Titanium dioxide Titanium dioxide Form Appearance Color Odor Melting point/range Boiling Point:	20 mppcf 10 mg/m3 15 mg/m3 9. PHYSIC : Solic : Pelle : GRE : Very : Not c : Not c : Insol	PEL: Time Weighted Averag (TWA): PEL: CAL AND CHEMICAL CAL AND CHEMICAL EN Bit EN Bit faint V determined V applicable pI	Total d Total d Total d Total d PROPERTIES vaporation rate pecific Gravity ilk density apor pressure apor density I	ust. ust. : Not aj : Not de : Not es : Not aj : Not aj	Z3 ACGIH OSHA Z pplicable. etermined stablished pplicable pplicable
Silica, amorphous Titanium dioxide Titanium dioxide Titanium dioxide Form Appearance Color Odor Melting point/range Boiling Point:	20 mppcf 10 mg/m3 15 mg/m3 9. PHYSIC : Solic : Pelle : GRE : Very : Not c : Insol 10. S	PEL: Time Weighted Averag (TWA): PEL: CAL AND CHEMICAL CAL AND CHEMICAL E EN Bi EN Bi faint V determined V applicable pH uble	Total d Total d Total d Total d PROPERTIES vaporation rate pecific Gravity ilk density apor pressure apor density I	ust. ust. : Not aj : Not de : Not es : Not aj : Not aj	Z3 ACGIH OSHA Z pplicable. etermined stablished pplicable pplicable
Silica, amorphous Titanium dioxide Titanium dioxide Titanium dioxide Form Appearance Color Odor Melting point/range Boiling Point: Water solubility	20 mppcf 10 mg/m3 15 mg/m3 9. PHYSIC : Solid : Pelle : GRE : Very : Not a : Insol 10. S : S	PEL: Time Weighted Averag (TWA): PEL: CAL AND CHEMICAL CAL AND CHEMICAL EN SI EN Bit faint Videtermined Videtermin	Total d Total d Total d Total d PROPERTIES vaporation rate pecific Gravity ilk density apor pressure apor density I	ust. ust. : Not aj : Not de : Not es : Not aj : Not aj	Z3 ACGIH OSHA Z pplicable. etermined stablished pplicable pplicable



MATERIAL SAFETY DATA SHEET

GREEN NT 6052

rsion Number 1.0 vision Date 06/06/2002			Page 4 c Print Date <i>11/4/</i> 20	
Incompatible Materials	: Incompatible w	vith strong acids an	d oxidizing agents.	
Hazardous decomposition products			pnoxide (CO), oxides of nitrogen and smoke are all possible.	
	11. TOXICOLOGI	CAL INFORMAT	TION	
health data for the indivi- Toxicity Overview	dual components which cor	nprise the mixture.	osure effects listed are based on exist	
CAS-No.	Chemical Name	Effect	Target Organ	
7631-86-9	Silica, amorphous	Irritant	Eyes, Respiratory system.	
13463-67-7	Titanium dioxide	Systemic effects		
	12. ECOLOGICA	AL INFORMATIO	ON	
Persistence and degrada	bility : Not readily bio	degradable.		
Environmental Toxicity : Chemicals are not readily available as they are bound within the matrix of the polymer.				
Bioaccumulation Potent	ial : Chemicals are of the polymer.		e as they are bound within the matrix	
Additional advice	: No data availat	ole.		
	13. DISPOSAL C	CONSIDERATIO	NS	
Product	possible, recyc generator of wa classification, t	: Like most thermoplastics the product can be recycled. Where possible, recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.		
Contaminated packaging : Recycling is preferred when possible. The generator of waste n has the responsibility for proper waste classification, transporta and disposal in accordance with applicable federal, state/provin and local regulations.		vaste classification, transportation		
	14. TRANSPOR	T INFORMATIO	N	
U.S. D.O.T. / CA T.D.C Classification (Non-bull ground)	-	or transportation.		
ICAO/IATA	: Not regulated f	or transportation.		
		4/6		



MATERIAL SAFETY DATA SHEET

GREEN	NT	6052
GREEN	IN I	UUJZ

Version Number 1.0 Revision Date 06/06/2002	Page 5 of 6 Print Date 11/4/2011		
IMO / IMDG :	Not regulated for transportation.		
15. REGULATORY INFORMATION			
US Regulations:			
OSHA Status :	Classified as hazardous based on components.		
TSCA Status :	All components of this product are listed on the TSCA inventory or are exempt.		
US. EPA CERCLA Hazardous Sub	ostances (40 CFR 302)		
Not applicable			
California Proposition : 65	This product does not contain a substance listed by California Prop 65.		
Canadian Regulations:			
WHMIS Classification :	D2B		
WHMIS Ingredient Disclose	ure List		
CAS-No. 7631-86-9			
DSL :	Listed.		
National Inventories:			
Australia AICS :	Not determined.		
China IECS :	Not determined.		
Europe EINECS :	Not determined.		
Japan ENCS :	Not determined.		
Korea KECI :	Not determined.		
Philippines PICCS :	Not determined.		
	16. OTHER INFORMATION		
	5/6		



MATERIAL SAFETY DATA SHEET

GREEN NT 6052

Version Number 1.0 Revision Date 06/06/2002 Page 6 of 6 Print Date 11/4/2011

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.