

MATERIAL SAFETY DATA SHEET

WHITE

Version Number 1.0 Revision Date 06/10/2002 Page 1 of 6 Print Date 11/4/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	WHITE
Product code	:	CC10017465
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Calcium carbonate	1317-65-3	10 - 30
Titanium dioxide	13463-67-7	30 - 60

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to even
Skin	eyes. : Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.



MATERIAL SAFETY DATA SHEET

WHITE

sion Date 06/10/2002	Print Date 11/4/2
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist, or in all cases or doubt, seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist, or in all cases of doubt, seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seel medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	 Not applicable Not applicable Not relevant Carbon dioxide blanket, Water spray, dry powder, foam.
Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. None
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	: Keep containers dry and tightly closed to avoid moisture absorption



MATERIAL SAFETY DATA SHEET

WHITE

ion Number 1.0 sion Date 06/10/2002			Print	Page 3 Date 11/4/2
	aı	nd contamination. Keep in a	dry, cool place.	
8. E	XPOSURE	CONTROLS / PERSONAL	L PROTECTION	
Respiratory protection	: N	o personal respiratory protec	tive equipment normally	required.
Eye/Face Protection	: S	afety glasses with side-shield	ls.	
Hand protection	: P	rotective gloves.		
Skin and body protection	: L	ong sleeved clothing.		
Additional Protective Measures	: Safety shoes.			
General Hygiene Considerations		andle in accordance with goo Vash hands before breaks and		afety practic
Engineering measures	: Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.			
Exposure limit(s)				
Components	Value	Exposure time	Exposure type	List:
Calcium carbonate	10 mg/m3	Time Weighted Average (TWA):	Total dust.	ACGIH
Calcium carbonate	5 mg/m3	PEL:	Respirable dust.	OSHA Z
	15 mg/m3	PEL:	Total dust.	OSHA ZI
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):	Total dust.	ACGIH
Titanium dioxide	15 mg/m3	PEL:	Total dust.	OSHA ZI
	9. PHYSIC	CAL AND CHEMICAL PR	OPERTIES	
Form	: Solid	Evan	oration rate : Not	applicable.
Appearance	: Pelle			determined
Color	: WHI		-	established
Odor	: Very		•	applicable
Melting point/range	•			applicable
Boiling Point:	: Not a	applicable pH		applicable
Water solubility	: Insol			11
	10. 8	TABILITY AND REACTI	VITY	
Stability	: S	table.		
Hazardous Polymerization	1 : W	/ill not occur.		
Conditions to avoid	: K	eep away from oxidizing age	ents and open flame. To a	avoid thermal



MATERIAL SAFETY DATA SHEET

sion Number 1.0 ision Date 06/10/2	2002			Page 4 Print Date 11/4/2
		decompositio	on, do not overheat.	
Incompatible Mate	rials :	Incompatible	with strong acids and o	oxidizing agents.
Hazardous decomp products	osition :			oxide (CO), oxides of nitrogen nd smoke are all possible.
	11. T	OXICOLOO	GICAL INFORMATIO	ON
health data for the i	individual compo	nents which c	omprise the mixture.	ure effects listed are based on exi-
				have the following characteristic
CAS-No.		cal Name	Effect	Target Organ
1317-65-3	Calcium car	bonate	Irritant	Eyes, Skin.
12462 67 7	T: (1.	Systemic effects	Eyes, Skin, Respiratory system
13463-67-7	Titanium di	oxide	Systemic effects	Respiratory system.
	12.	ECOLOGI	CAL INFORMATION	1
Persistence and deg	gradability :	Not readily b	viodegradable.	
		Chemicals are not readily available as they are bound within the matrix of the polymer.		
Bioaccumulation Potential :		Chemicals are not readily available as they are bound within the matrix of the polymer.		
Additional advice :		No data avai	lable.	
	13	. DISPOSAL	CONSIDERATIONS	5
Product :		: Like most thermoplastics the product can be recycled. Where possible, recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.		
		Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.		
	1/	. TRANSPO	PRT INFORMATION	
	14			



MATERIAL SAFETY DATA SHEET

WHITE				
Version Number 1.0 Revision Date 06/10/2002	Page 5 of 6 Print Date 11/4/2011			
ICAO/IATA :	Not regulated for transportation.			
IMO / IMDG :	Not regulated for transportation.			
15	5. REGULATORY INFORMATION			
US Regulations:				
OSHA Status :	Classified as hazardous based on components.			
TSCA Status :	All components of this product are listed on the TSCA inventory or are exempt.			
US. EPA CERCLA Hazardous Sub	stances (40 CFR 302)			
Not applicable				
California Proposition : 65	This product does not contain a substance listed by California Prop 65.			
Canadian Regulations:				
WHMIS Classification :	D2A			
WHMIS Ingredient Disclosure List				
CAS-No. 1333-86-4 557-05-1				
DSL :	Listed.			
National Inventories:				
Australia AICS :	Listed.			
China IECS :	Listed.			
Europe EINECS :	Not determined.			
Japan ENCS :	Not determined.			
Korea KECI :	Listed.			
Philippines PICCS :	Listed.			



MATERIAL SAFETY DATA SHEET

WHITE

Version Number 1.0 Revision Date 06/10/2002 Page 6 of 6 Print Date 11/4/2011

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.