

MATERIAL SAFETY DATA SHEET MIDNIGHT

Version Number 1.1 Revision Date 01/21/2004

Page 1 of 8 Print Date 11/13/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	MIDNIGHT
Product code	:	CC10018334
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight %
Iron oxide	1309-37-1	1 - 5
Titanium dioxide	13463-67-7	1 - 5
Calcium carbonate	1317-65-3	5 - 10
Carbon black	1333-86-4	5 - 10
Rutile, antimony chromium buff	68186-90-3	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation	: Particulates, like other inert materials can be mechanically irritating. Excessive inhalation of product vapors, especially during heating or processing, may be irritating to respiratory system.
Ingestion Eyes	May be harmful if swallowed.Particulates, like other inert materials can be mechanically irritating.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.



MATERIAL SAFETY DATA SHEET **MIDNIGHT**

Version Number 1.1 Revision Date 01/21/2004 Page 2 of 8 Print Date 11/13/2011

Medical Conditions Aggravated by Exposure:	: None known.			
	4. FIRST AID MEASURES			
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases doubt seek medical advice.	of		
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.			
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for least 15 minutes. If eye irritation persists, seek medical attention.	at		
Skin	: Wash off with soap and plenty of water. If skin irritation persists s medical attention.	eel		
	5. FIRE-FIGHTING MEASURES			
Flash point	: Not applicable			
Flammable Limits				
Upper explosion limit	: Not applicable			
Lower explosion limit	: Not applicable			
Autoignition temperature	Not applicable			
Suitable extinguishing media	: Carbon dioxide blanket, water spray, dry powder, foamnone.			
Special Fire Fighting	: Fullface self-contained breathing apparatus (SCBA) used in positiv	/e		
Procedures	pressure mode should be worn to prevent inhalation of airborne			
	contaminants.			
Unusual Fire/Explosion	: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen			
Hazards	(NOx), other hazardous materials, and smoke are all possible. Magemit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fi conditions.			
	5. ACCIDENTAL RELEASE MEASURES			
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.			
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.	ıot		
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material i plastic, cardboard or metal containers for disposal. Refer to Sectior of this MSDS for proper disposal methods.			



MATERIAL SAFETY DATA SHEET MIDNIGHT

Version Number 1.1 Revision Date 01/21/2004 Page 3 of 8 Print Date 11/13/2011

Handling	: Take measures to prevent the build up of electrostatic charge Heat only in areas with appropriate exhaust ventilation.
Storage	 Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.
8. EXI	POSURE CONTROLS / PERSONAL PROTECTION
Respiratory protection	: No personal respiratory protective equipment normally required.
Eye/Face Protection	: Safety glasses with side-shields.
Hand protection	: Protective gloves.
Skin and body protection	: Long sleeved clothing.
Additional Protective Measures	: Safety shoes.
General Hygiene Considerations	: Handle in accordance with good industrial hygiene and safety practice Wash hands before breaks and at the end of workday.
Engineering measures	: Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.



MATERIAL SAFETY DATA SHEET *MIDNIGHT*

Version Number 1.1

Revision Date 01/21/2004

Page 4 of 8 Print Date 11/13/2011

Components	Value	Exposure time	Exposure type	List:
Calcium carbonate	Calcium carbonate 5 mg/m3 PEL:		Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
Carbon black	3.5 mg/m3	Time Weighted Average	Total dust. as carbon	ACGIH
		(TWA):	black	
	3.5 mg/m3	PEL:	Total dust. as carbon	OSHA Z1
			black	
Iron oxide	5 mg/m3	Time Weighted Average	Dust and fume. as Fe	ACGIH
		(TWA):		
Rutile, antimony	1 mg/m3	PEL:		OSHA Z1
chromium buff				
	0.5 mg/m3	PEL:	as Sb	OSHA Z1
	0.5 mg/m3	Time Weighted Average	as Cr	ACGIH
		(TWA):		
	0.5 mg/m3	Time Weighted Average	as Sb	ACGIH
		(TWA):		
Titanium dioxide	10 mg/m3	Time Weighted Average		ACGIH
		(TWA):		
	15 mg/m3	PEL:	Total dust.	OSHA Z1

9. PHYSICAL AND CHEMICAL PROPERTIES

- Form Appearance Color Odor Melting point/range Boiling Point: Water solubility
- Solid
 Pellets
 GREY
 Very faint
 Not determined
 Not applicable
 Insoluble

Evaporation rate Specific Gravity: Bulk density Vapor pressure Vapour density pH : Not applicable

- : Not determined
- : Not established
- : Not applicable
- : Not applicable
- : Not applicable

10. STABILITY AND REACTIVITY

Stability Hazardous Polymerization	:	Stable. Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Avoid contact with strong oxidizers. Also, avoid contact with acetal or acetal copolymers and with amine containing materials during processing. At processing conditions, these materials are mutually destructive and involve rapid degradation. Thoroughly purge and mechanically clean processing equipment to avoid even trace quantities of these materials from coming in contact with each other. Prevent cross contamination of feedstocks.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating (approximately 30 minutes



MATERIAL SAFETY DATA SHEET MIDNIGHT

Version Number 1.1 Revision Date 01/21/2004 Page 5 of 8 Print Date 11/13/2011

or more) above 392 °F (200 °C) or short term heating at 482 °F (250 °C) may result in product decomposition and evolution of carbon monoxide and hydrogen chloride.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1309-37-1	Iron oxide	Systemic effects	Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory system.
1333-86-4	Carbon black	Systemic effects	Eyes, Respiratory system.
68186-90-3	Rutile, antimony	Irritant	Eyes, Skin, Respiratory system.
	chromium buff		

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
1333-86-4	Carbon black	Oral LD50	>15,400 mg/kg	rat
		Dermal LD50	> 3 gm/kg	rabbit

Additional Health Hazard Information:

Carbon black 1333-86-4 Carcinogenicity: Many inhalation toxicologists believe that the tumor response observed in the referenced rat studies is species specific and does not correlate to human exposure. However, the IARC evaluation in Monograph Volume 65, issued in April 1996 concluded that, "There is sufficient evidence in experimental animals for the carcinogenicity of carbon black". Based on this evaluation, along with their evaluation of inadequate evidence of carcinogenicity in humans, IARC's overall evaluation is that "Carbon Black is possibly carcinogenic to humans (Group 2B). The IARC 2B listing only pertains to airborne, unbound carbon black particles of respirable size. Carbon Black has not been listed as a carcinogen by the National Toxicology Program (NTP) or the Occupational Safety and Health Administration (OSHA). The National Institute of Occupational Safety and Health (NIOSH) criteria document on carbon black recommends that only carbon black with PAH (polynuclear aromatic hydrocarbon) levels greater than 0.1% be considered suspect carcinogens.

Additional Health Hazard Information:

Rutile, antimony chromium buff 68186-90-3 Can cause eye irritation. Can cause skin irritation. Symptoms may include redness and burning of skin, and other skin damage. Additional symptoms of skin contact may include: antimony measles (a red, pimply rash).

12. ECOLOGICAL INFORMATION

Persistence and degradability

: Not readily biodegradable.



MATERIAL SAFETY DATA SHEET MIDNIGHT

rsion Number 1.1 evision Date 01/21/2004	Page 6 of Print Date 11/13/20
Environmental Toxicity	: Chemicals are not readily available as they are bound within the matrix of the polymer.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the matrix of the polymer.
Additional advice	: No data available
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA (air)	: Refer to specific regulation.
IMO / IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
	: All components of this product are listed on or exempt from the TSCA
TSCA Status	Inventory.
TSCA Status US. EPA CERCLA Hazardou	Inventory.
	Inventory.
US. EPA CERCLA Hazardou Not applicable	Inventory. Is Substances (40 CFR 302)
US. EPA CERCLA Hazardou	Inventory. Is Substances (40 CFR 302)

<u>One</u>

MATERIAL SAFETY DATA SHEET *MIDNIGHT*

Version Number 1.1 Revision Date 01/21/2004

Page 7 of 8 Print Date 11/13/2011

Not applicable

SARA Title III Section 313 Toxic Chemicals:

Chemical Name	CAS-No.	Weight %
CHROMIUM III COMPOUNDSANTIMONY	68186-90-3	10.25
COMPOUNDS		

Canadian Regulations:

National Pollutant Release Inventory (NPRI)

Chemical Name	CAS-No.	Weight %	NPRI ID#
Rutile, antimony chromium buff	68186-90-3	10.25	68
Rutile, antimony chromium buff	68186-90-3	10.25	17

WHMIS Classification : D2A

WHMIS Ingredient Disclosure List

_	
(CAS-No.
	1333-86-4
	1309-37-1
(68186-90-3

DSL

All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

Australia AICS	:	Not determined
China IECS	:	Not determined
Europe EINECS	:	Not determined
Japan ENCS	:	Not determined
Korea KECI	:	Not determined
Philippines PICCS	:	Not determined

:

16. OTHER INFORMATION



MATERIAL SAFETY DATA SHEET MIDNIGHT

Version Number 1.1 Revision Date 01/21/2004 Page 8 of 8 Print Date *11/13/2011*

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.