

MATERIAL SAFETY DATA SHEET

PG18388 WT PE

Version Number 1.0 Revision Date 06/21/2002 Page 1 of 5 Print Date 11/5/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	PG18388 WT PE
Product code	:	CC10018388
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Titanium dioxide	13463-67-7	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.



MATERIAL SAFETY DATA SHEET

PG18388 WT PE

ion Number 1.0 sion Date 06/21/2002	Page : Print Date 11/5/
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist, or in all cases doubt, seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist, or in all cases of doubt, seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for a least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	 Not applicable Not applicable Not relevant Carbon dioxide blanket, Water spray, dry powder, foam.
Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. None
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 7 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	: Keep containers dry and tightly closed to avoid moisture absorption



MATERIAL SAFETY DATA SHEET

PG18388 WT PE

ision Date 06/21/2002			Print	Page 3 Date 11/5/2	
	aı	nd contamination. Keep in a	dry, cool place.		
8. H	XPOSURE	CONTROLS / PERSONAL	PROTECTION		
Respiratory protection	: N	lo personal respiratory protect	tive equipment normally	required.	
Eye/Face Protection	: Safety glasses with side-shields.				
Hand protection	: P	rotective gloves.			
Skin and body protection	: L	ong sleeved clothing.			
Additional Protective Measures	: Sa	afety shoes.			
General Hygiene Considerations	: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.				
Engineering measures		: Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.			
Exposure limit(s)					
Components	Value	Exposure time	Exposure type	List:	
Titanium dioxide	Value 10 mg/m3	Exposure time Time Weighted Average (TWA):	Exposure type Total dust.	List: ACGIH	
		Time Weighted Average			
Titanium dioxide	10 mg/m3 15 mg/m3	Time Weighted Average (TWA):	Total dust. Total dust.	ACGIH	
Titanium dioxide	10 mg/m3 15 mg/m3	Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PR	Total dust. Total dust. OPERTIES	ACGIH	
Titanium dioxide Titanium dioxide	10 mg/m3 15 mg/m3 9. PHYSIC	Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PR	Total dust. Total dust. OPERTIES oration rate : Not	ACGIH OSHA Z1	
Titanium dioxide Titanium dioxide	10 mg/m3 15 mg/m3 9. PHYSIC : Solid	Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PR d Evapo ets Speci	Total dust. Total dust. OPERTIES Dration rate : Not fic Gravity	ACGIH OSHA Z1	
Titanium dioxide Titanium dioxide Form Appearance Color Odor	10 mg/m3 15 mg/m3 9. PHYSIC : Solid : Pelle : GRE : Very	Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PR E Evaports EN Speci EN Bulk faint Vapo	Total dust. Total dust. OPERTIES oration rate : Not fic Gravity : Not density : Not r pressure : Not	ACGIH OSHA Z1 t applicable. t determined t established t applicable	
Titanium dioxide Titanium dioxide Titanium dioxide Form Appearance Color Odor Melting point/range	10 mg/m3 15 mg/m3 9. PHYSIC : Solid : Pelle : GRE : Very : Not c	Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PR E Evaports EN Speci EN Bulk faint Vaports determined Vaports	Total dust. Total dust. OPERTIES oration rate : Not fic Gravity : Not density : Not r pressure : Not r density : Not r density : Not	ACGIH OSHA Z1 applicable. t determined t established t applicable t applicable	
Titanium dioxide Titanium dioxide Titanium dioxide Form Appearance Color Odor Melting point/range Boiling Point:	10 mg/m3 15 mg/m3 9. PHYSIC : Solid : Pelle : GRE : Very : Not c : Not a	Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PR t Evapo ts Speci EN Bulk faint Vapo determined Vapo applicable pH	Total dust. Total dust. OPERTIES oration rate : Not fic Gravity : Not density : Not r pressure : Not r density : Not r density : Not	ACGIH OSHA Z1 t applicable. t determined t established t applicable	
Titanium dioxide Titanium dioxide Titanium dioxide Form Appearance Color Odor Melting point/range	10 mg/m3 15 mg/m3 9. PHYSIC : Solid : Pelle : GRE : Very : Not c	Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PR t Evapo ts Speci EN Bulk faint Vapo determined Vapo applicable pH	Total dust. Total dust. OPERTIES oration rate : Not fic Gravity : Not density : Not r pressure : Not r density : Not r density : Not	ACGIH OSHA Z1 applicable. t determined t established t applicable t applicable	
Titanium dioxide Titanium dioxide Titanium dioxide Form Appearance Color Odor Melting point/range Boiling Point:	10 mg/m3 15 mg/m3 9. PHYSIC : Solid : Pelle : GRE : Very : Not c : Not a : Insol	Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PR t Evapo ts Speci EN Bulk faint Vapo determined Vapo applicable pH	Total dust. Total dust. OPERTIES oration rate : Not fic Gravity : Not density : Not r pressure : Not c density : Not r density : Not	ACGIH OSHA Z1 applicable. t determined t established t applicable t applicable	
Titanium dioxide Titanium dioxide Titanium dioxide Form Appearance Color Odor Melting point/range Boiling Point:	10 mg/m3 15 mg/m3 9. PHYSIC : Solid : Pelle : GRE : Very : Not c : Not a : Insol 10. S	Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PR d Evapo ets Speci EN Bulk faint Vapo determined Vapo applicable pH luble	Total dust. Total dust. OPERTIES oration rate : Not density : Not r pressure : Not c density : Not it density : Not c density : Not c density : Not	ACGIH OSHA Z1 applicable. t determined t established t applicable t applicable	
Titanium dioxide Titanium dioxide Titanium dioxide Form Appearance Color Odor Melting point/range Boiling Point: Water solubility	10 mg/m3 15 mg/m3 9. PHYSIC : Solid : Pelle : GRE : Very : Not c : Not a : Insol 10. S	Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PR the Evaport tes Speci EN Bulk of faint Vaport determined Vaport applicable pH uble	Total dust. Total dust. OPERTIES oration rate : Not density : Not r pressure : Not c density : Not it density : Not c density : Not c density : Not	ACGIH OSHA Z1 applicable. t determined t established applicable t applicable	
Titanium dioxide Titanium dioxide Titanium dioxide Form Appearance Color Odor Melting point/range Boiling Point: Water solubility Stability	10 mg/m3 15 mg/m3 9. PHYSIC : Solid : Pelle : GRE : Very : Not c : Not a : Insol 10. S n : W : K	Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PR I Evapo ts Speci EN Bulk faint Vapo determined Vapo applicable pH luble STABILITY AND REACTI table.	Total dust. Total dust. Total dust. OPERTIES oration rate : Not fic Gravity : Not density : Not r pressure : Not r density : Not VITY VITY	ACGIH OSHA Z1 applicable. determined testablished applicable applicable applicable	



MATERIAL SAFETY DATA SHEET

PG18388 WT PE

Version Number 1.0 Revision Date 06/21/2002 Page 4 of 5 Print Date 11/5/2011

Hazardous decomposition products

: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ			
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.			
	12. ECOLOGI	CAL INFORMATION	1			
Persistence and degrad	lability : Not readily b	iodegradable.				
Environmental Toxicit		 Chemicals are not readily available as they are bound within the matrix of the polymer. Chemicals are not readily available as they are bound within the matrix of the polymer. 				
Bioaccumulation Pote						
Additional advice	: No data avail	lable.				
	13. DISPOSAL	CONSIDERATIONS				
Product Contaminated packagi	ng : Recycling is has the respo and disposal	: Like most thermoplastics the product can be recycled. Where possible, recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.				
	14. TRANSPO	RT INFORMATION				
U.S. D.O.T. / CA T.D. Classification (Non-bu ground)	e	l for transportation.				
ICAO/IATA	: Not regulated	l for transportation.				
IMO / IMDG	: Not regulated	l for transportation.				
	15. REGULAT	ORY INFORMATION	J			

MATERIAL SAFETY DATA SHEET



PG18388 WT PE

Version Number 1.0 Revision Date 06/21/2002		Page 5 of 5 Print Date 11/5/2011
US Regulations:		
OSHA Status	:	Classified as hazardous based on components.
TSCA Status	:	All components of this product are listed on the TSCA inventory or are exempt.
US. EPA CERCLA Hazardous S	Sub	stances (40 CFR 302)
Not applicable		
California Proposition 65	:	This product does not contain a substance listed by California Prop 65.
Canadian Regulations:		
WHMIS Classification	:	D2B
DSL	:	Listed.
National Inventories:		
Australia AICS	:	Listed.
China IECS	:	Listed.
Europe EINECS	:	Not determined.
Japan ENCS	:	Listed.
Korea KECI	:	Listed.
Philippines PICCS	:	Listed.
		16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.