

MATERIAL SAFETY DATA SHEET

STONE/ GRAY/ BLACK

Version Number 1.0 Revision Date 06/22/2002 Page 1 of 6 Print Date 11/5/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	STONE/ GRAY/ BLACK
Product code	:	CC10018667
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
C.I. Pigment Yellow 53	8007-18-9	1 - 5
Silica, amorphous	7631-86-9	1 - 5
Titanium dioxide	13463-67-7	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact		
Acute exposure			
Inhalation	: Resin particles, like other inert materials, can be mechanically irritating.		
Ingestion	: May be harmful if swallowed.		
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.		
Skin	: Experience shows no unusual dermatitis hazard from routine handling.		
Chronic exposure	: Refer to Section 11 for Toxicological Information.		



MATERIAL SAFETY DATA SHEET

STONE/ GRAY/ BLACK

sion Date 06/22/2002	Print Date 11/5/2
Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist, or in all cases of doubt, seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist, or in all cases of doubt, seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	 Not applicable Not applicable Not relevant Carbon dioxide blanket, Water spray, dry powder, foam.
Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. None
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should no be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 1 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.



MATERIAL SAFETY DATA SHEET

STONE/ GRAY/ BLACK

Version Number 1.0 Revision Date 06/22/2002 Page 3 of 6 Print Date 11/5/2011

Storage	:	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.	
8. EXPOSURE CONTROLS / PERSONAL PROTECTION			
Respiratory protection	:	No personal respiratory protective equipment normally required.	
Eye/Face Protection	:	Safety glasses with side-shields.	
Hand protection	:	Protective gloves.	
Skin and body protection	:	Long sleeved clothing.	
Additional Protective Measures	:	Safety shoes.	
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.	
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.	

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
C.I. Pigment Yellow	0.2 mg/m3	Time Weighted Average	as Ni	ACGIH
53		(TWA):		
C.I. Pigment Yellow	1 mg/m3	PEL:	as Ni	OSHA Z1
53				
C.I. Pigment Yellow	0.5 mg/m3	Time Weighted Average	as Sb	ACGIH
53		(TWA):		
C.I. Pigment Yellow	0.5 mg/m3	PEL:	as Sb	OSHA Z1
53				
Silica, amorphous	20 mppcf	PEL:	Total dust.	OSHA
Silica, amorphous	20 mppcf	PEL:	Total dust.	Z3
Titanium dioxide	10 mg/m3	Time Weighted Average	Total dust.	ACGIH
		(TWA):		
Titanium dioxide	15 mg/m3	PEL:	Total dust.	OSHA Z1

9. PHYSICAL AND CHEMICAL PROPERTIES

Form Appearance Color Odor Melting point/range Boiling Point: Water solubility Solid
Pellets
GREY
Very faint
Not determined
Not applicable
Insoluble

Evaporation rate Specific Gravity Bulk density Vapor pressure Vapor density pH Not applicable.
Not determined
Not established
Not applicable
Not applicable
Not applicable



MATERIAL SAFETY DATA SHEET

STONE/ GRAY/ BLACK

Version Number 1.0 Revision Date 06/22/2002 Page 4 of 6 Print Date 11/5/2011

		10	. STABILITY AND REACTIVITY
Stability		:	Stable.
Hazardous	Polymerization	:	Will not occur.
Conditions	to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatib	le Materials	:	Incompatible with strong acids and oxidizing agents.
Hazardous products	decomposition	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
8007-18-9	C.I. Pigment Yellow 53	Irritant	Eyes, Skin.
		sensitizer	Skin.
7631-86-9	Silica, amorphous	Irritant	Eyes, Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

Carcinogenicity:

This product contains the following components which in their pure form have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
8007-18-9	C.I. Pigment Yellow 53	no	1	2

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

Additional Health Hazard Information:

C.I. Pigment Yellow 53 8007-18-9 Skin sensitizer "nickel itch", with pulmonary, brain, liver, kidney andmuscle effects.

12. ECOLOGICAL INFORMATION



MATERIAL SAFETY DATA SHEET

STONE/ GRAY/ BLACK

sion Number 1.0 vision Date 06/22/2002	Page 5 0 Print Date 11/5/20
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the matrix of the polymer.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the matrix of the polymer.
Additional advice	: No data available.
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastics the product can be recycled. Where possible, recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. D.O.T. / CA T.D.G. Classification (Non-bulk ground)	: Not regulated for transportation.
ICAO/IATA	: Not regulated for transportation.
IMO / IMDG	: Not regulated for transportation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on the TSCA inventory or are exempt.
US. EPA CERCLA Hazardous	Substances (40 CFR 302)
Not applicable	



MATERIAL SAFETY DATA SHEET

STONE/ GRAY/ BLACK

Version Number 1.0 Revision Date 06/22/2002 Page 6 of 6 Print Date 11/5/2011

California Proposition 65

: WARNING! This product contains a chemical known in the State of California to cause cancer.

SARA Title III Section 313 Toxic Chemicals:

Chemical Name	CAS-No.	Weight %
NICKEL COMPOUNDS	8007-18-9	3.30
ANTIMONY COMPOUNDS		

Canadian Regulations:

WHMIS Classification : D2B

WHMIS Ingredient Disclosure List

CAS-No.	
8007-18-9	
7631-86-9	

DSL

: Not determined.

National Inventories:

Australia AICS	:	Listed.
China IECS	:	Not determined.
Europe EINECS	:	Not determined.
Japan ENCS	:	Not determined.
Korea KECI	:	Not determined.
Philippines PICCS	:	Not determined.

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.