

MATERIAL SAFETY DATA SHEET

RED

Version Number 1.0 Revision Date 07/15/2002 Page 1 of 5 Print Date 11/5/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	RED
Product code	:	CC10019101
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Titanium dioxide	13463-67-7	1 - 5

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.



MATERIAL SAFETY DATA SHEET

RED

sion Date 07/15/2002	Print Date 11/5/2
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist, or in all cases of doubt, seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist, or in all cases of doubt, seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 Not applicable Not applicable Not relevant Carbon dioxide blanket, Water spray, dry powder, foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. None
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	: Keep containers dry and tightly closed to avoid moisture absorption



MATERIAL SAFETY DATA SHEET

RED

				nt Date 11/5/2	
	а	and contamination. Keep in a c	ry, cool place.		
8. E	XPOSURE	E CONTROLS / PERSONAL	PROTECTION		
Respiratory protection	: 1	No personal respiratory protect	ve equipment normall	y required.	
Eye/Face Protection	: 5	Safety glasses with side-shields.			
Hand protection	: I	Protective gloves.			
Skin and body protection	: I	: Long sleeved clothing.			
Additional Protective Measures	: 5	Safety shoes.	fety shoes.		
General Hygiene Considerations		Handle in accordance with good industrial hygiene and safety practice Wash hands before breaks and at the end of workday.			
Engineering measures		: Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.			
Exposure limit(s)					
Components	Value	Exposure time	Exposure type	List:	
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):	Total dust.	ACGIH	
Titanium dioxide	15 mg/m3	PEL:	Total dust.	OSHA Z1	
	9. PHYSI	CAL AND CHEMICAL PRO	DPERTIES		
				r. 1. 1.	
Form Appearance	: Soli : Pelle			lot applicable.	
Color	: REL	1		lot established	
Odor			2	lot applicable	
Melting point/range				lot applicable	
Boiling Point:		applicable pH		lot applicable	
Water solubility	: Insoluble			TT	
2			71/1787		
	10.	STABILITY AND REACTIV	/11 1		
Stability		STABILITY AND REACTIV	/11 1		
	: S				
Stability	: S n : V : H	Stable.	its and open flame. To	o avoid thermal	



MATERIAL SAFETY DATA SHEET

RED

Version Number 1.0 Revision Date 07/15/2002

Page 4 of 5 Print Date 11/5/2011

Hazardous decomposition products

: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ		
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.		
	12. ECOLOGIO	CAL INFORMATION	1		
Persistence and degrad	ability : Not readily b	iodegradable.			
Environmental Toxicit	Chemicals ar of the polyme		is they are bound within the matri		
Bioaccumulation Poter		: Chemicals are not readily available as they are bound within the matrix of the polymer.			
Additional advice	: No data avail	lable.			
	13. DISPOSAL	CONSIDERATIONS	9		
Product Contaminated packagii	possible, recy generator of classification applicable fe has the respo	ycling is preferred to di waste material has the r i, transportation and dis deral, state/provincial a preferred when possible nsibility for proper was in accordance with app	ct can be recycled. Where sposal or incineration. The esponsibility for proper waste posal in accordance with nd local regulations. e. The generator of waste materia te classification, transportation licable federal, state/provincial		
	14. TRANSPO	ORT INFORMATION			
U.S. DOT / CA TDG Classification	: Not regulated	1 for transportation.			
ICAO/IATA	: Not regulated	: Not regulated for transportation.			
IMO / IMDG	: Not regulated	l for transportation.			

MATERIAL SAFETY DATA SHEET



RED Version Number 1.0 Page 5 of 5 Print Date 11/5/2011 Revision Date 07/15/2002 US Regulations: **OSHA Status** : Classified as hazardous based on components. **TSCA Status** All components of this product are listed on the TSCA inventory or are : exempt. US. EPA CERCLA Hazardous Substances (40 CFR 302) Not applicable California Proposition : This product does not contain a substance listed by California Prop 65. 65 Canadian Regulations: WHMIS Classification : D2B DSL : Listed. National Inventories: Australia AICS : Listed. China IECS Listed. ÷ **Europe EINECS** Not determined. Japan ENCS Not determined. : Korea KECI Not determined. : **Philippines PICCS** Not determined. :

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.