

MATERIAL SAFETY DATA SHEET

YELLOW SHAKE AND POUR

Version Number 1.0 Revision Date 07/01/2002 Page 1 of 5 Print Date 11/5/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	YELLOW SHAKE AND POUR
Product code	:	CC10019164
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Titanium dioxide	13463-67-7	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.



MATERIAL SAFETY DATA SHEET

YELLOW SHAKE AND POUR

Version Number 1.0 Revision Date 07/01/2002 Page 2 of 5 Print Date 11/5/2011

		4. FIRST AID MEASURES	
Inhalation		Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist, or in all cases of doubt, seek medical advice.	
Ingestion	:	Do not induce vomiting without medical advice. When symptoms persist, or in all cases of doubt, seek medical advice.	
Eyes	:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.	
Skin	:	Wash off with soap and plenty of water. If skin irritation persists seek medical attention.	
		5. FIRE-FIGHTING MEASURES	
Flash point	:	Not applicable	
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	::	Not applicable Not applicable Not relevant Carbon dioxide blanket, Water spray, dry powder, foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. None	
	6. A	CCIDENTAL RELEASE MEASURES	
Personal precautions	:	Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.	
Environmental precautions	:	Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.	
Methods for cleaning up	:	Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.	
		7. HANDLING AND STORAGE	
Handling	:	Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.	
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption	



MATERIAL SAFETY DATA SHEET

YELLOW SHAKE AND POUR

Version Number 1.0 Revision Date 07/01/2002 Page 3 of 5 Print Date 11/5/2011

8. F	XPOSURE	CONTROLS / PER	SONAL	PROTECTION	
Respiratory protection	: N	No personal respiratory protective equipment normally required.			
Eye/Face Protection	: S	Safety glasses with side-shields.			
Hand protection	: P	Protective gloves.			
Skin and body protection	: L	ong sleeved clothing			
Additional Protective Measures	: Safety shoes.				
General Hygiene Considerations		: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.			
Engineering measures	s : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.				
Exposure limit(s)					
Components	Value	Exposure time		Exposure type	List:
Titanium dioxide	10 mg/m3	*		Total dust.	ACGIH
Titanium dioxide	15 mg/m3	PEL:		Total dust.	OSHA Z1
	9 PHVSI	CAL AND CHEMI	AL PRC	PFRTIFS	
	7.11101				
Form	: Solie				ot applicable.
Appearance	: Pelle				ot determined
Color		LOW	Bulk d		ot established
Odor	: Very faint				ot applicable
Melting point/range		determined			ot applicable
Boiling Point:		applicable	pН	: N	ot applicable
Water solubility	: Inso	luble			
	10. 9	STABILITY AND R	REACTIV	YITY	
Stability	: S	table.			
Hazardous Polymerization	n : V	Vill not occur.			
Conditions to avoid		Keep away from oxidi ecomposition, do not		ts and open flame. To	avoid thermal



MATERIAL SAFETY DATA SHEET

YELLOW SHAKE AND POUR

Version Number 1.0 Revision Date 07/01/2002 Page 4 of 5 Print Date 11/5/2011

Hazardous decomposition products

: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ			
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.			
	12. ECOLOGIC	CAL INFORMATION	1			
Persistence and degrada	bility : Not readily bi	odegradable.				
Environmental Toxicity		: Chemicals are not readily available as they are bound within the matrix of the polymer.				
Bioaccumulation Poten		: Chemicals are not readily available as they are bound within the matrix of the polymer.				
Additional advice	: No data availa	able.				
	13. DISPOSAL	CONSIDERATIONS				
Product Contaminated packagin	possible, recy generator of v classification, applicable fed g : Recycling is p has the respor and disposal i	 Like most thermoplastics the product can be recycled. Where possible, recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal. 				
	14. TRANSPO	RT INFORMATION				
U.S. DOT / CA TDG Classification	: Not regulated	for transportation.				
ICAO/IATA	: Not regulated	: Not regulated for transportation.				
IMO / IMDG	: Not regulated	for transportation.				



MATERIAL SAFETY DATA SHEET

YELLOW SHAKE AND POUR

Version Number 1.0 Revision Date 07/01/2002		Page 5 of 5 Print Date <i>11/5/2011</i>
US Regulations:		
OSHA Status	:	Classified as hazardous based on components.
TSCA Status	:	All components of this product are listed on the TSCA inventory or are exempt.
US. EPA CERCLA Hazardous	Subs	stances (40 CFR 302)
Not applicable		
California Proposition 65	:	This product does not contain a substance listed by California Prop 65.
Canadian Regulations:		
WHMIS Classification	:	D2B
DSL	:	Listed.
National Inventories:		
Australia AICS	:	Listed.
China IECS	:	Listed.
Europe EINECS	:	Not determined.
Japan ENCS	:	Not determined.
Korea KECI	:	Listed.
Philippines PICCS	:	Listed.
		16. OTHER INFORMATION

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.