

### MATERIAL SAFETY DATA SHEET

# COLOR 13

Version Number 1.0 Revision Date 06/29/2002 Page 1 of 6 Print Date 11/5/2011

# 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	COLOR 13
Product code	:	CC10019175
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

#### 2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Mica	12001-26-2	5 - 10
Titanium dioxide	13463-67-7	10 - 30

### **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

#### POTENTIAL HEALTH EFFECTS

<b>Routes of Exposure:</b>	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes	<ul> <li>Resin particles, like other inert materials, can be mechanically irritating.</li> <li>May be harmful if swallowed.</li> <li>Resin particles, like other inert materials, are mechanically irritating to eyes.</li> </ul>
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.



# MATERIAL SAFETY DATA SHEET

# COLOR 13

ion Number 1.0 sion Date 06/29/2002	Page 2 Print Date 11/5/2
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist, or in all cases o doubt, seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist, or in all cases of doubt, seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
-	
Flammable Limits	NY
Upper explosion limit	: Not applicable
Lower explosion limit	: Not applicable
Autoignition temperature	: Not relevant
Suitable extinguishing media	: Carbon dioxide blanket, Water spray, dry powder, foam.
Special Fire Fighting	: Fullface self-contained breathing apparatus (SCBA) used in positive
Procedures	pressure mode should be worn to prevent inhalation of airborne
Tiocedules	contaminants.
Unusual Fire/Explosion Hazards	: None
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 1 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	: Keep containers dry and tightly closed to avoid moisture absorption





# COLOR 13

			Print	Date 11/5/
	aı	nd contamination. Keep in a c	lry, cool place.	
8. E	XPOSURE	CONTROLS / PERSONAL	PROTECTION	
Respiratory protection	: N	o personal respiratory protect	ive equipment normally	required.
Eye/Face Protection	: S	afety glasses with side-shields		
Hand protection	: P	rotective gloves.		
Skin and body protection	: L	ong sleeved clothing.		
Additional Protective Measures	: Safety shoes.			
General Hygiene Considerations		andle in accordance with good ash hands before breaks and a		safety practic
Engineering measures		leat only in areas with appropr ppropriate exhaust ventilation		Provide
Exposure limit(s)				
Components	Value	Exposure time	Exposure type	List:
Mica	3 mg/m3	Time Weighted Average (TWA):	Total dust.	ACGIH
Mica	20 mppcf	PEL:	Total dust.	OSHA
	10 mg/m3	Time Weighted Average	Total dust.	ACGIH
Titanium dioxide	U	(TWA):		
Titanium dioxide Titanium dioxide	15 mg/m3	•	Total dust.	OSHA Z
	15 mg/m3	(TWA):		OSHA Z
Titanium dioxide	15 mg/m3 9. PHYSIC	(TWA): PEL: CAL AND CHEMICAL PRO	DPERTIES	
Titanium dioxide	15 mg/m3	(TWA): PEL: CAL AND CHEMICAL PRO	DPERTIES	t applicable.
Titanium dioxide	15 mg/m3 9. PHYSIC : Solid	(TWA): PEL: CAL AND CHEMICAL PRO I Evapo sts Specifi	DPERTIES oration rate : Not fic Gravity : Not	t applicable.
Titanium dioxide Form Appearance	15 mg/m3 9. PHYSIC : Solid : Pelle	(TWA): PEL: CAL AND CHEMICAL PRO E Evapo ets Specifi TE Bulk of	DPERTIES ration rate : Not ric Gravity : Not lensity : Not	t applicable. t determined
Form Appearance Color Odor Melting point/range	15 mg/m3 9. PHYSIC : Solid : Pelle : WHI : Very : Not c	(TWA):         PEL:         CAL AND CHEMICAL PRO         I       Evapo         ets       Specif         TE       Bulk c         faint       Vapor         determined       Vapor	<b>DPERTIES</b> oration rate       : Not         fic Gravity       : Not         density       : Not         pressure       : Not         density       : Not	t applicable. t determined t established t applicable t applicable
Form Appearance Color Odor Melting point/range Boiling Point:	15 mg/m3 9. PHYSIC : Solid : Pelle : WHI : Very : Not c : Not a	(TWA):         PEL:         CAL AND CHEMICAL PRO         I       Evapo         ets       Specif         TE       Bulk d         faint       Vapor         determined       Vapor         applicable       pH	<b>DPERTIES</b> oration rate       : Not         fic Gravity       : Not         density       : Not         pressure       : Not         density       : Not	t applicable. t determined t established t applicable
Form Appearance Color Odor Melting point/range	15 mg/m3 9. PHYSIC : Solid : Pelle : WHI : Very : Not c	(TWA):         PEL:         CAL AND CHEMICAL PRO         I       Evapo         ets       Specif         TE       Bulk d         faint       Vapor         determined       Vapor         applicable       pH	<b>DPERTIES</b> oration rate       : Not         fic Gravity       : Not         density       : Not         pressure       : Not         density       : Not	t applicable. t determined t established t applicable t applicable
Titanium dioxide Form Appearance Color Odor Melting point/range Boiling Point:	15 mg/m3 9. PHYSIC : Solid : Pelle : WHI : Very : Not c : Not a : Insol	(TWA):         PEL:         CAL AND CHEMICAL PRO         I       Evapo         ets       Specif         TE       Bulk d         faint       Vapor         determined       Vapor         applicable       pH	DPERTIES ration rate : Not fic Gravity : Not lensity : Not pressure : Not density : Not : Not	t applicable. t determined t established t applicable t applicable
Titanium dioxide Form Appearance Color Odor Melting point/range Boiling Point:	15 mg/m3 9. PHYSIC : Solid : Pelle : WHI : Very : Not c : Not a : Insol 10. S	(TWA):         PEL:         CAL AND CHEMICAL PRO         I       Evapo         ets       Specifi         TE       Bulk c         r faint       Vapor         determined       Vapor         applicable       pH	DPERTIES ration rate : Not fic Gravity : Not lensity : Not pressure : Not density : Not : Not	t applicable. t determined t established t applicable t applicable
Titanium dioxide Form Appearance Color Odor Melting point/range Boiling Point: Water solubility	15 mg/m3 9. PHYSIC : Solid : Pelle : WHI : Very : Not c : Not a : Insol 10. S : St	(TWA):         PEL:         CAL AND CHEMICAL PRO         I       Evapo         ets       Specifi         TE       Bulk down         faint       Vapor         determined       Vapor         applicable       pH         uble       STABILITY AND REACTIVE	DPERTIES ration rate : Not fic Gravity : Not lensity : Not pressure : Not density : Not : Not	t applicable. t determined t established t applicable t applicable



MATERIAL SAFETY DATA SHEET

# **COLOR 13**

Version Number 1.0		Page 4 of 6
Revision Date 06/29/2002		Print Date 11/5/2011
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents.
-		
Hazardous decomposition	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen
products		(NOx), other hazardous materials, and smoke are all possible.
	11	TOXICOLOGICAL INFORMATION

#### TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

<u>Toxicity Overview</u> This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
12001-26-2	Mica	Systemic effects	Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

	12. ECOLOGICAL INFORMATION
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the matrix of the polymer.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the matrix of the polymer.
Additional advice	: No data available.
	13. DISPOSAL CONSIDERATIONS
Product Contaminated packaging	<ul> <li>Like most thermoplastics the product can be recycled. Where possible, recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.</li> <li>Recycling is preferred when possible. The generator of waste material</li> </ul>
	has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT / CA TDG Classification	: Not regulated for transportation.
ICAO/IATA	: Not regulated for transportation.
	4/6



# MATERIAL SAFETY DATA SHEET

# COLOR 13

JLUR 13		
sion Number 1.0 rision Date 06/29/2002		Page 5 of 6 Print Date 11/5/2011
IMO / IMDG	:	Not regulated for transportation.
	15	REGULATORY INFORMATION
US Regulations:		
OSHA Status	:	Classified as hazardous based on components.
TSCA Status	:	All components of this product are listed on the TSCA inventory or are exempt.
US. EPA CERCLA Hazardous	Subs	stances (40 CFR 302)
Not applicable		
California Proposition 65	:	This product does not contain a substance listed by California Prop 65.
Canadian Regulations:		
WHMIS Classification	:	D2B
WHMIS Ingredient Disc	losu	re List
CAS-No. 12001-26-2		
DSL	:	Listed.
National Inventories:		
Australia AICS	:	Listed.
China IECS	:	Listed.
Europe EINECS	:	Not determined.
Japan ENCS	:	Not determined.
Korea KECI	:	Listed.
Philippines PICCS	:	Listed.
		16. OTHER INFORMATION

MATERIAL SAFETY DATA SHEET



# COLOR 13

Version Number 1.0 Revision Date 06/29/2002 Page 6 of 6 Print Date 11/5/2011

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.