

#### MATERIAL SAFETY DATA SHEET

## **GOLD**

 Version Number 1.0
 Page 1 of 6

 Revision Date 07/12/2002
 Print Date 11/5/2011

## 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION

33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY :

TELEPHONE

Product Stewardship (770) 271-5902

: CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure

Emergency telephone number

or accident).

Product name : GOLD
Product code : CC10019279
Chemical Name : Mixture
CAS-No. : Mixture

Product Use : Industrial Applications

## 2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

| Components                     | CAS-No.    | Weight % |
|--------------------------------|------------|----------|
| Rutile, antimony chromium buff | 68186-90-3 | 5 - 10   |
| Mica                           | 12001-26-2 | 10 - 30  |
| Titanium dioxide               | 13463-67-7 | 10 - 30  |

## 3. HAZARDS IDENTIFICATION

## **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

## POTENTIAL HEALTH EFFECTS

Routes of Exposure: : Inhalation, Ingestion, Skin contact

Acute exposure

Inhalation : Resin particles, like other inert materials, can be mechanically irritating.

Ingestion : May be harmful if swallowed.

Eyes : Resin particles, like other inert materials, are mechanically irritating to

eyes.

Skin : Experience shows no unusual dermatitis hazard from routine handling.

**Chronic exposure** : Refer to Section 11 for Toxicological Information.



#### MATERIAL SAFETY DATA SHEET

**GOLD** 

 Version Number 1.0
 Page 2 of 6

 Revision Date 07/12/2002
 Print Date 11/5/2011

**Medical Conditions Aggravated by Exposure:** 

: None known.

4. FIRST AID MEASURES

Inhalation : Move to fresh air in case of accidental inhalation of fumes from

overheating or combustion. When symptoms persist, or in all cases of

doubt, seek medical advice.

Ingestion : Do not induce vomiting without medical advice. When symptoms

persist, or in all cases of doubt, seek medical advice.

Eyes : Rinse immediately with plenty of water, also under the eyelids, for at

least 15 minutes. If eye irritation persists, seek medical attention.

Skin : Wash off with soap and plenty of water. If skin irritation persists seek

medical attention.

5. FIRE-FIGHTING MEASURES

Flash point : Not applicable

Flammable Limits

Upper explosion limit : Not applicable Lower explosion limit : Not applicable Autoignition temperature : Not relevant

Suitable extinguishing media : Carbon dioxide blanket, Water spray, dry powder, foam.

Special Fire Fighting

Procedures

Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne

contaminants.

Unusual Fire/Explosion

Hazards

: None

## 6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Wear appropriate personal protection during cleanup, such as

impervious gloves, boots and coveralls.

Environmental precautions : Should not be released into the environment. The product should not

be allowed to enter drains, water courses or the soil.

Methods for cleaning up : Clean up promptly by sweeping or vacuum. Package all material in

plastic, cardboard or metal containers for disposal. Refer to Section 13

of this MSDS for proper disposal methods.

### 7. HANDLING AND STORAGE

Handling : Take measures to prevent the build up of electrostatic charge. Heat

only in areas with appropriate exhaust ventilation.



### MATERIAL SAFETY DATA SHEET

## **GOLD**

 Version Number 1.0
 Page 3 of 6

 Revision Date 07/12/2002
 Print Date 11/5/2011

Storage : Keep containers dry and tightly closed to avoid moisture absorption

and contamination. Keep in a dry, cool place.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Respiratory protection : No personal respiratory protective equipment normally required.

Eye/Face Protection : Safety glasses with side-shields.

Hand protection : Protective gloves.

Skin and body protection : Long sleeved clothing.

Additional Protective

Measures

: Safety shoes.

General Hygiene : Handle in accordance with good industrial hygiene and safety practice.

Considerations Wash hands before breaks and at the end of workday.

Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide

appropriate exhaust ventilation at machinery.

## Exposure limit(s)

| Components                     | Value     | Exposure time Exposure type  |                   | List:   |
|--------------------------------|-----------|------------------------------|-------------------|---------|
| Mica                           | 3 mg/m3   | Time Weighted Average        | Total dust.       | ACGIH   |
|                                |           | (TWA):                       |                   |         |
| Mica                           | 20 mppcf  | PEL:                         | Total dust.       | OSHA    |
| Rutile, antimony               | 0.5 mg/m3 | Time Weighted Average        |                   | MX OEL  |
| chromium buff                  |           | (TWA):                       |                   |         |
|                                | 0.5 mg/m3 | Time Weighted Average (TWA): | Total dust. as Cr | ACGIH   |
| Rutile, antimony chromium buff | 0.5 mg/m3 | PEL:                         | Total dust. as Cr | OSHA Z1 |
| Rutile, antimony               | 0.5 mg/m3 | Time Weighted Average        |                   | MX OEL  |
| chromium buff                  |           | (TWA):                       |                   |         |
|                                | 0.5 mg/m3 | Time Weighted Average (TWA): | Dust. as Sb       | ACGIH   |
| Rutile, antimony chromium buff | 0.5 mg/m3 | PEL:                         | Total dust. as Sb | OSHA Z1 |
| Rutile, antimony chromium buff | 0.5 mg/m3 | Time Weighted Average (TWA): | as Sb             | MX OEL  |
| Titanium dioxide               | 10 mg/m3  | Time Weighted Average (TWA): | Total dust.       | ACGIH   |
| Titanium dioxide               | 15 mg/m3  | PEL:                         | Total dust.       | OSHA Z1 |

## 9. PHYSICAL AND CHEMICAL PROPERTIES



#### MATERIAL SAFETY DATA SHEET

## **GOLD**

 Version Number 1.0
 Page 4 of 6

 Revision Date 07/12/2002
 Print Date 11/5/2011

: Solid Evaporation rate : Not applicable. Form : Pellets Specific Gravity Not determined Appearance : YELLOW Bulk density : Not established Color : Very faint Vapor pressure : Not applicable Odor Melting point/range : Not determined Vapor density : Not applicable Boiling Point: : Not applicable : Not applicable pΗ

Water solubility : Insoluble

### 10. STABILITY AND REACTIVITY

Stability : Stable.

Hazardous Polymerization : Will not occur.

Conditions to avoid : Keep away from oxidizing agents and open flame. To avoid thermal

decomposition, do not overheat.

Incompatible Materials : Incompatible with strong acids and oxidizing agents.

Hazardous decomposition

products

Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen

(NOx), other hazardous materials, and smoke are all possible.

### 11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

### **Toxicity Overview**

This product contains the following components which in their pure form have the following characteristics:

| CAS-No.    | Chemical Name    | Effect           | Target Organ        |
|------------|------------------|------------------|---------------------|
| 68186-90-3 | Rutile, antimony | Irritant         | Eyes, Skin.         |
|            | chromium buff    |                  |                     |
| 12001-26-2 | Mica             | Systemic effects | Respiratory system. |
| 13463-67-7 | Titanium dioxide | Systemic effects | Respiratory system. |

#### **Additional Health Hazard Information:**

Rutile, antimony chromium buff 68186-90-3 Can cause eye irritation. Can cause skin irritation. Symptoms may include redness and burning of skin, and other skin damage. Additional symptoms of skin contact may include: antimony measles (a red, pimply rash).

## 12. ECOLOGICAL INFORMATION

Persistence and degradability : Not readily biodegradable.

Environmental Toxicity : Chemicals are not readily available as they are bound within the matrix

of the polymer.

Bioaccumulation Potential : Chemicals are not readily available as they are bound within the matrix

of the polymer.



#### MATERIAL SAFETY DATA SHEET

## **GOLD**

 Version Number 1.0
 Page 5 of 6

 Revision Date 07/12/2002
 Print Date 11/5/2011

Additional advice : No data available.

### 13. DISPOSAL CONSIDERATIONS

Product : Like most thermoplastics the product can be recycled. Where

possible, recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.

Contaminated packaging : Recycling is preferred when possible. The generator of waste material

has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial

and local regulations.

## 14. TRANSPORT INFORMATION

U.S. DOT / CA TDG : Not regulated for transportation.

Classification

ICAO/IATA : Not regulated for transportation.

IMO / IMDG : Not regulated for transportation.

## 15. REGULATORY INFORMATION

US Regulations:

OSHA Status : Classified as hazardous based on components.

TSCA Status : All components of this product are listed on the TSCA inventory or are

exempt.

US. EPA CERCLA Hazardous Substances (40 CFR 302)

Not applicable

California Proposition : This product does not contain a substance listed by California Prop 65.

65

SARA Title III Section 313 Toxic Chemicals:



### MATERIAL SAFETY DATA SHEET

# **GOLD**

Version Number 1.0 Revision Date 07/12/2002 Page 6 of 6 Print Date 11/5/2011

| Chemical Name          | CAS-No.    | Weight % |
|------------------------|------------|----------|
| CHROMIUM III COMPOUNDS | 68186-90-3 | 05.07    |
| ANTIMONY COMPOUNDS     |            |          |

Canadian Regulations:

WHMIS Classification : D2B

WHMIS Ingredient Disclosure List

| CAS-No.    |
|------------|
| 12001-26-2 |
| 68186-90-3 |

DSL : Listed.

National Inventories:

Australia AICS : Listed.

China IECS : Listed.

Europe EINECS : Not determined.

Japan ENCS : Not determined.

Korea KECI : Listed.

Philippines PICCS : Listed.

## 16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.