

MATERIAL SAFETY DATA SHEET

PP W/ TALC

Version Number 1.0 Revision Date 07/03/2002 Page 1 of 6 Print Date 11/5/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	PP W/ TALC
Product code	:	CC10019446
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Talc	14807-96-6	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to eves.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.



MATERIAL SAFETY DATA SHEET

PP W/ TALC

sion Date 07/03/2002	Page 2 Print Date 11/5/2
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist, or in all cases o doubt, seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist, or in all cases of doubt, seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	 Not applicable Not applicable Not relevant Carbon dioxide blanket, Water spray, dry powder, foam.
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	: None
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 1 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	: Keep containers dry and tightly closed to avoid moisture absorption

MATERIAL SAFETY DATA SHEET





sion Number 1.0 vision Date 07/03/2002			Print	Page 3 of 6 Date 11/5/2011	
		and contamination. Keep in a d	ry, cool place.		
8.1	EXPOSURI	E CONTROLS / PERSONAL	PROTECTION		
Respiratory protection	:	No personal respiratory protective equipment normally required.			
Eye/Face Protection	:	Safety glasses with side-shields.			
Hand protection	:	Protective gloves.			
Skin and body protection	:	Long sleeved clothing.			
Additional Protective Measures	:	Safety shoes.			
General Hygiene Considerations		: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.			
Engineering measures	: Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.				
Exposure limit(s)					
Components	Value	Exposure time	Exposure type	List:	
Talc	2 mg/m3	Time Weighted Average (TWA):	Respirable dust.	ACGIH	
Talc	20 mppcf	· · · · · · · · · · · · · · · · · · ·	Total dust.	OSHA	

Form Appearance Color Odor Melting point/range Boiling Point: Water solubility	 Solid Pellets NO PIGMENT Very faint Not determined Not applicable Insoluble 	Evaporation rate Specific Gravity Bulk density Vapor pressure Vapor density pH	Not establishedNot applicable
Stability	10. STABILITY AN : Stable.	D REACTIVITY	
Hazardous Polymerization	: Will not occur.		
Conditions to avoid	: Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.		
Incompatible Materials	: Incompatible with strong acids and oxidizing agents.		



MATERIAL SAFETY DATA SHEET

PP W/ TALC

sion Number 1.0 ision Date 07/03/2002	2			Page 4 of Print Date <i>11/5/201</i>	
Hazardous decompositi products	on :			oxide (CO), oxides of nitrogen ad smoke are all possible.	
	11.	TOXICOLOGI	CAL INFORMATIO	DN	
health data for the indiv Toxicity Overview	idual comp	oonents which con	nprise the mixture.	are effects listed are based on existin have the following characteristics:	
CAS-No.	Cha	mical Name Effect Tar		Target Organ	
14807-96-6	Talc		Systemic effects	Eyes, Respiratory system, Skin.	
14007 90 0	Tule		Systemic effects	Lycs, Respiratory system, 5km.	
	1	12. ECOLOGICA	L INFORMATION	I	
Persistence and degrada	bility :	Not readily bio	degradable.		
			Chemicals are not readily available as they are bound within the matrix of the polymer.		
Bioaccumulation Potential : Chemicals are not readily available as they are bound within of the polymer.		s they are bound within the matrix			
Additional advice : No data available.					
	-	13. DISPOSAL C	CONSIDERATIONS		
Product		: Like most thermoplastics the product can be recycled. Where possible, recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.			
Contaminated packaging : Recycling is preferred when poshas the responsibility for proper and disposal in accordance with and local regulations.			ibility for proper was accordance with appl		
		14. TRANSPOR	T INFORMATION		
U.S. DOT / CA TDG Classification	:	Not regulated f	or transportation.		
ICAO/IATA	:	: Not regulated for transportation.			
ICAO/IATA		ε	1		



MATERIAL SAFETY DATA SHEET

PP W/ TALC

Version Number 1.0 Page 5 of 6 Revision Date 07/03/2002 Print Date 11/5/2011 **15. REGULATORY INFORMATION** US Regulations: **OSHA Status** Classified as hazardous based on components. : All components of this product are listed on the TSCA inventory or are **TSCA Status** : exempt. US. EPA CERCLA Hazardous Substances (40 CFR 302) Not applicable California Proposition : This product does not contain a substance listed by California Prop 65. 65 Canadian Regulations: WHMIS Classification : D2A WHMIS Ingredient Disclosure List CAS-No. 14807-96-6 DSL : Listed. National Inventories: Australia AICS : Listed. China IECS Listed. : **Europe EINECS** Not determined. : Japan ENCS Not determined. : Korea KECI : Listed. **Philippines PICCS** : Listed. **16. OTHER INFORMATION**

MATERIAL SAFETY DATA SHEET



PP W/ TALC

Version Number 1.0 Revision Date 07/03/2002 Page 6 of 6 Print Date 11/5/2011

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.