

### MATERIAL SAFETY DATA SHEET

# PINK

Version Number 1.0 Revision Date 07/30/2002 Page 1 of 6 Print Date 11/5/2011

## 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE <b>Emergency telephone number</b>	:	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name Product code Chemical Name CAS-No. Product Use	::	PINK CC10019851 Mixture Mixture Industrial Applications

#### 2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Aluminum	7429-90-5	10 - 30

#### **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

# POTENTIAL HEALTH EFFECTS

: Inhalation, Ingestion, Skin contact			
<ul><li>Resin particles, like other inert materials, can be mechanically irritating.</li><li>May be harmful if swallowed.</li></ul>			
: Resin particles, like other inert materials, are mechanically irritating to eyes.			
: Experience shows no unusual dermatitis hazard from routine handling.			
: Refer to Section 11 for Toxicological Information.			
: None known.			



# MATERIAL SAFETY DATA SHEET

sion Date 07/30/2002	Print Date 11/5/2
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist, or in all cases of doubt, seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist, or in all cases of doubt, seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits	
Upper explosion limit	: Not applicable
Lower explosion limit	: Not applicable
Autoignition temperature	: Not relevant
Suitable extinguishing media	: Carbon dioxide blanket, Water spray, dry powder, foam.
Special Fire Fighting	: Fullface self-contained breathing apparatus (SCBA) used in positive
Procedures	pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	: None
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	: Keep containers dry and tightly closed to avoid moisture absorption



# MATERIAL SAFETY DATA SHEET

ion Number 1.0 sion Date 07/30/2002			Print I	Page 3 //5/2
	a	nd contamination. Keep in a c	lry, cool place.	
8. E	XPOSURE	CONTROLS / PERSONAL	PROTECTION	
Respiratory protection	: N	o personal respiratory protect	ive equipment normally r	equired.
Eye/Face Protection	: S	afety glasses with side-shields		
Hand protection	: P	rotective gloves.		
Skin and body protection	: L	ong sleeved clothing.		
Additional Protective Measures	: S	afety shoes.		
General Hygiene Considerations		andle in accordance with good Vash hands before breaks and		afety practic
Engineering measures		eat only in areas with appropropropriate exhaust ventilation		Provide
Exposure limit(s)				
Components	Value	Exposure time	Exposure type	List:
Aluminum	10 mg/m3	Time Weighted Average (TWA):	Dust.	ACGIH
	5 mg/m3	Time Weighted Average (TWA):	Welding fume. as Al	ACGIH
Aluminum	15 mg/m3	PEL:	Total dust. as Al	OSHA ZI
	5 mg/m3	PEL:	Respirable dust. as Al	OSHA Z
	9. PHYSIC	CAL AND CHEMICAL PRO	<b>DPERTIES</b>	
Form	: Solic			applicable.
Appearance	: Pelle		2	determined
Color Odor	: PINI : Very			established applicable
Melting point/range				applicable
Boiling Point:		applicable pH		applicable
Water solubility	: Insol			
	10. 5	STABILITY AND REACTIV	<b>/ITY</b>	
Stability	: S	table.		
Hazardous Polymerization	n : W	/ill not occur.		
5				



# MATERIAL SAFETY DATA SHEET

ersion Number 1.0 evision Date 07/30/2002	2		Page 4 of Print Date 11/5/20
Incompatible Materials	: Incompatibl	e with strong acids and	oxidizing agents.
Hazardous decomposition products			noxide (CO), oxides of nitrogen and smoke are all possible.
	11. TOXICOLO	GICAL INFORMAT	ION
	en evaluated as a whole f idual components which		sure effects listed are based on existi
This product contains th	ne following components	which in their pure for	n have the following characteristics:
CAS-No.	Chemical Name	Effect	Target Organ
7429-90-5	Aluminum	Irritant	Skin, Respiratory system.
		Systemic effects	Eyes, Skin, Respiratory system.
	12. ECOLOG	ICAL INFORMATIO	N
Persistence and degrada Environmental Toxicity Bioaccumulation Potent Additional advice Product	<ul> <li>Chemicals a of the polyn</li> <li>tial : Chemicals a of the polyn</li> <li>: No data ava</li> <li>13. DISPOSA</li> <li>: Like most the possible, rea generator of classificatio applicable f</li> </ul>	ner. tre not readily available ner. ilable. <b>L CONSIDERATION</b> nermoplastics the prod cycling is preferred to d waste material has the n, transportation and di ederal, state/provincial	uct can be recycled. Where lisposal or incineration. The responsibility for proper waste sposal in accordance with
Contaminated packagin	has the resp and disposa and local re	onsibility for proper wa l in accordance with ap gulations.	aste classification, transportation plicable federal, state/provincial
	14. TRANSPO	ORT INFORMATION	N
U.S. DOT / CA TDG Classification	: Not regulate	ed for transportation.	
ICAO/IATA	: Not regulate	ed for transportation.	



# MATERIAL SAFETY DATA SHEET

sion Number 1.0 ision Date 07/30/2002					Print Dat	Page 5 e 11/5/2
IMO / IMDG	:	Not regulated for	transportation.			
	15.	. REGULATORY	INFORMATIO	N		
US Regulations:						
OSHA Status	:	Classified as haza	ardous based on co	omponents.		
TSCA Status	:	All components of exempt.	of this product are	listed on the T	SCA inver	ntory or ar
US. EPA CERCLA Hazardou	us Subs	stances (40 CFR 30	02)			
Not applicable						
California Proposition	n :	This product does	s not contain a sub	stance listed b	y Californ	ia Prop 65
65						
_		hemicals:				
65 SARA Title III Section 313 T Chemical Nan	Гохіс С ne		CAS-No.	Weight 9	%	
65 SARA Title III Section 313 T Chemical Nan ALUMINUM	Гохіс С ne		CAS-No. 7429-90-5	Weight 9 27.55	6	
65 SARA Title III Section 313 T Chemical Nan ALUMINUM Canadian Regulations:	Γoxic C ne [ (FUM]	E OR DUST)			%	
65 SARA Title III Section 313 T Chemical Nan ALUMINUM	Γoxic C ne [ (FUM]				%	
65 SARA Title III Section 313 T Chemical Nan ALUMINUM Canadian Regulations:	Foxic C ne (FUM)	E OR DUST) D2B			%	
65 SARA Title III Section 313 T Chemical Nan ALUMINUM Canadian Regulations: WHMIS Classificatio	Foxic C ne (FUM)	E OR DUST) D2B			%	
65 SARA Title III Section 313 T Chemical Nan ALUMINUM Canadian Regulations: WHMIS Classificatio WHMIS Ingredient Di CAS-No.	Foxic C ne (FUM)	E OR DUST) D2B			<u>%</u>	
65 SARA Title III Section 313 T Chemical Nan ALUMINUM Canadian Regulations: WHMIS Classificatio WHMIS Ingredient Di CAS-No. 7429-90-5	Foxic C ne (FUM)	E OR DUST) D2B re List			6	
65 SARA Title III Section 313 T Chemical Nan ALUMINUM Canadian Regulations: WHMIS Classificatio WHMIS Ingredient Di CAS-No. 7429-90-5 DSL	Foxic C ne (FUM)	E OR DUST) D2B re List			6	
65 SARA Title III Section 313 T Chemical Nan ALUMINUM Canadian Regulations: WHMIS Classificatio WHMIS Ingredient Di CAS-No. 7429-90-5 DSL National Inventories:	Foxic C ne (FUM) on : isclosur :	E OR DUST) D2B re List Listed.			6	
65 SARA Title III Section 313 T Chemical Nan ALUMINUM Canadian Regulations: WHMIS Classificatio WHMIS Ingredient Di CAS-No. 7429-90-5 DSL National Inventories: Australia AICS	Foxic C ne (FUM) on : visclosur :	E OR DUST) D2B re List Listed. Not determined.			6	



### MATERIAL SAFETY DATA SHEET

# PINK

Version Number 1.0 Revision Date 07/30/2002 Page 6 of 6 Print Date 11/5/2011

Korea KECI : Listed.

Philippines PICCS : Listed.

#### **16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.