

MATERIAL SAFETY DATA SHEET

### PG 19872 GY PP SL

Version Number 1.0 Revision Date 07/15/2002 Page 1 of 5 Print Date 11/5/2011

### 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	PG 19872 GY PP SL
Product code	:	CC10019872
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

#### 2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Titanium dioxide	13463-67-7	10 - 30

### **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

### POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes	<ul> <li>Resin particles, like other inert materials, can be mechanically irritating.</li> <li>May be harmful if swallowed.</li> <li>Resin particles, like other inert materials, are mechanically irritating to eyes.</li> </ul>
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.



MATERIAL SAFETY DATA SHEET

## PG 19872 GY PP SL

Version Number 1.0 Page 2 of 5 Revision Date 07/15/2002 Print Date 11/5/2011 **4. FIRST AID MEASURES** Inhalation Move to fresh air in case of accidental inhalation of fumes from ÷ overheating or combustion. When symptoms persist, or in all cases of doubt, seek medical advice. Ingestion Do not induce vomiting without medical advice. When symptoms : persist, or in all cases of doubt, seek medical advice. Eyes Rinse immediately with plenty of water, also under the eyelids, for at : least 15 minutes. If eye irritation persists, seek medical attention. Skin Wash off with soap and plenty of water. If skin irritation persists seek : medical attention. **5. FIRE-FIGHTING MEASURES** Flash point Not applicable : Flammable Limits Upper explosion limit Not applicable : Lower explosion limit Not applicable : Autoignition temperature Not relevant : Suitable extinguishing media Carbon dioxide blanket, Water spray, dry powder, foam. : Special Fire Fighting Fullface self-contained breathing apparatus (SCBA) used in positive : Procedures pressure mode should be worn to prevent inhalation of airborne contaminants. Unusual Fire/Explosion None · Hazards 6. ACCIDENTAL RELEASE MEASURES Personal precautions : Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls. Environmental precautions Should not be released into the environment. The product should not : be allowed to enter drains, water courses or the soil. Clean up promptly by sweeping or vacuum. Package all material in Methods for cleaning up : plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods. 7. HANDLING AND STORAGE Handling Take measures to prevent the build up of electrostatic charge. Heat : only in areas with appropriate exhaust ventilation. Storage Keep containers dry and tightly closed to avoid moisture absorption •



MATERIAL SAFETY DATA SHEET

# PG 19872 GY PP SL

sion Number 1.0 vision Date 07/15/2002					Print I	Page 3 of Date 11/5/201
	ar	nd contamination. Keep	p in a d	ry, cool place.		
8. E	XPOSURE	CONTROLS / PERSO	ONAL	PROTECTION		
Respiratory protection	: N	: No personal respiratory protective equipment normally required.				
Eye/Face Protection	: Sa	: Safety glasses with side-shields.				
Hand protection	: P1	: Protective gloves.				
Skin and body protection	: Lo	: Long sleeved clothing.				
Additional Protective Measures	: Sa	: Safety shoes.				
General Hygiene Considerations		andle in accordance wir ash hands before break				afety practice.
Engineering measures		: Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.				
Exposure limit(s)						
Components	Value	Exposure time		Exposure typ	e	List:
Titanium dioxide	10 mg/m3	Time Weighted Ave (TWA):	rage	Total dust.		ACGIH
Titanium dioxide	15 mg/m3	PEL:		Total dust.		OSHA Z1
	9. PHYSIC	CAL AND CHEMICA	L PRO	PERTIES		
Form	: Solid			ration rate :		applicable.
Appearance	: Pelle			c Gravity :		determined
Color	: GRE		Bulk d			established
Odor Melting point/range	: Very	letermined				applicable applicable
Boiling Point:			pH	density :		applicable
Water solubility	: Insolu		pm		NOL	applicable
(	10. S	TABILITY AND REA	ACTIV	ТТҮ		
	= = = = =					
Stability	: St	able.				
Stability Hazardous Polymerization						
-	n : W : K	able.			To a	void thermal



MATERIAL SAFETY DATA SHEET

### PG 19872 GY PP SL

Version Number 1.0 Revision Date 07/15/2002 Page 4 of 5 Print Date 11/5/2011

Hazardous decomposition products

: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

### 11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ			
13463-67-7	Titanium dioxide	nium dioxide Systemic effects Respiratory system.				
	12. ECOLOGIO	CAL INFORMATION	J			
Persistence and degrada			·			
Environmental Toxicity	: Chemicals are of the polyme		s they are bound within the matri			
Bioaccumulation Poten		: Chemicals are not readily available as they are bound within the matrix of the polymer.				
Additional advice	: No data avail	able.				
	13. DISPOSAL	CONSIDERATIONS	9			
Product Contaminated packagin	generator of v generator of v classification applicable fec g : Recycling is p has the respon and disposal i	<ul> <li>Like most thermoplastics the product can be recycled. Where possible, recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.</li> <li>Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal.</li> </ul>				
	14. TRANSPO	<b>RT INFORMATION</b>				
U.S. DOT / CA TDG Classification	: Not regulated	for transportation.				
ICAO/IATA	: Not regulated	for transportation.				
IMO / IMDG	: Not regulated	for transportation.				
	15 REGULATO	DRY INFORMATION	N			





# PG 19872 GY PP SL

Version Number 1.0 Revision Date 07/15/2002		Page 5 of 5 Print Date 11/5/2011
US Regulations:		
OSHA Status	:	Classified as hazardous based on components.
TSCA Status	:	All components of this product are listed on the TSCA inventory or are exempt.
US. EPA CERCLA Hazardous	Sub	stances (40 CFR 302)
Not applicable		
	:	This product does not contain a substance listed by California Prop 65.
65		
Canadian Regulations:		
WHMIS Classification	:	D2B
DSL	:	Listed.
National Inventories:		
Australia AICS	:	Listed.
China IECS	:	Listed.
Europe EINECS	:	Not determined.
Japan ENCS	:	Not determined.
Korea KECI	:	Listed.
Philippines PICCS	:	Listed.
		16. OTHER INFORMATION

# 16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.