

## MATERIAL SAFETY DATA SHEET

## Safety Yellow (WP w / UV)

Version Number 1.1 Revision Date 01/21/2004 Page 1 of 7 Print Date *11/13/2011* 

#### 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	Safety Yellow (WP w / UV)
Product code	:	CC10020035
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

#### 2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight %
Phenol,	25973-55-1	1 - 5
2-(2H-benzotriazol-2-yl)-4,6-bis(1,1-dimeth		
ylpropyl)-		
8-Oxa-3,5-dithia-4-stannatetradecanoic acid,	57583-35-4	1 - 5
10-ethyl-4,4-dimethyl-7-oxo-, 2-ethylhexyl		
ester		
Silica, amorphous	7631-86-9	1 - 5
Stannane,	57583-34-3	1 - 5
methyltris(2-ethylhexyloxycarbonylmethylth		
io)-		
Titanium dioxide	13463-67-7	10 - 30

#### **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

#### POTENTIAL HEALTH EFFECTS

<b>Routes of Exposure:</b>	:	Inhalation, Ingestion, Skin contact

#### Acute exposure

Inhalation

: Particulates, like other inert materials can be mechanically irritating.



## MATERIAL SAFETY DATA SHEET Safety Yellow (WP w / UV)

Version Number 1.1 Revision Date 01/21/2004

Ingestion Eyes Skin	<ul> <li>processing, may be irritating to respiratory system.</li> <li>May be harmful if swallowed.</li> <li>Particulates, like other inert materials can be mechanically irritating.</li> <li>Experience shows no unusual dermatitis hazard from routine handling.</li> </ul>
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	<ul> <li>Not applicable</li> <li>Not applicable</li> <li>Not applicable</li> <li>Carbon dioxide blanket, water spray, dry powder, foamnone.</li> </ul>
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.



# MATERIAL SAFETY DATA SHEET Safety Yellow (WP w / UV)

Version Number 1.1 Revision Date 01/21/2004		Page 3 of 7 Print Date 11/13/2011
Environmental precautions	:	Should not be released into the environment. The product should not
		be allowed to enter drains, water courses or the soil.
Methods for cleaning up	:	Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
		7. HANDLING AND STORAGE
Handling	:	Take measures to prevent the build up of electrostatic charge Heat only in areas with appropriate exhaust ventilation.
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.
8. EXPO	SUR	RE CONTROLS / PERSONAL PROTECTION
Respiratory protection	:	No personal respiratory protective equipment normally required.
Eye/Face Protection	:	Safety glasses with side-shields.
Hand protection	:	Protective gloves.
Skin and body protection	:	Long sleeved clothing.
Additional Protective Measures	:	Safety shoes.
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.
Exposure limit(s)		

PolyOne

## MATERIAL SAFETY DATA SHEET **Safety Yellow (WP w / UV)**

Version Number 1.1

Revision Date 01/21/2004

Page 4 of 7 Print Date *11/13/2011* 

Components	Value	Exposure time	Exposure type	List:
8-Oxa-3,5-dithia-4-sta nnatetradecanoic acid, 10-ethyl-4,4-dimethyl- 7-oxo-, 2-ethylhexyl ester	0.1 mg/m3	PEL:	as Sn	OSHA Z1
	0.1 mg/m3	Time Weighted Average (TWA):	as Sn	ACGIH
	0.2 mg/m3	Short Term Exposure Limit (STEL):	as Sn	ACGIH
Silica, amorphous	20 mppcf	PEL:	Total dust.	OSHA
	20 mppcf	PEL:	Total dust.	Z3
Stannane, methyltris(2-ethylhexy loxycarbonylmethylthi o)-	0.1 mg/m3	PEL:	as Sn	OSHA Z1
	0.1 mg/m3	Time Weighted Average (TWA):	as Sn	ACGIH
	0.2 mg/m3	Short Term Exposure Limit (STEL):	as Sn	ACGIH
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):		ACGIH
	15 mg/m3	PEL:	Total dust.	OSHA Z1

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

- Form Appearance Color Odor Melting point/range Boiling Point: Water solubility
- Pellets
  YELLOW
  Very faint
  Not determined
  Not applicable
  Insoluble

: Solid

- Evaporation rate Specific Gravity: Bulk density Vapor pressure Vapour density pH
- Not applicable
  Not determined
  Not established
  Not applicable
  Not applicable
- : Not applicable

### **10. STABILITY AND REACTIVITY**

Stability	: Stable.	
Hazardous Polymerization	: Will not occur.	
Conditions to avoid	: Keep away from oxidizing agents and open flame. To avoid therma decomposition, do not overheat.	al
Incompatible Materials	: Avoid contact with strong oxidizers. Also, avoid contact with acetal acetal copolymers and with amine containing materials during processing. At processing conditions, these materials are mutually destructive and involve rapid degradation. Thoroughly purge and mechanically clean processing equipment to avoid even trace quantities of these materials from coming in contact with each other Prevent cross contamination of feedstocks.	



## MATERIAL SAFETY DATA SHEET Safety Yellow (WP w / UV)

Version Number 1.1 Revision Date 01/21/2004 Page 5 of 7 Print Date *11/13/2011* 

Hazardous decomposition products

:

Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating (approximately 30 minutes or more) above 392 °F (200 °C) or short term heating at 482 °F (250 °C) may result in product decomposition and evolution of carbon monoxide and hydrogen chloride.

#### 11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

#### **Toxicity Overview**

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
25973-55-1	Phenol,	Systemic effects	Kidney, Liver, reproductive
	2-(2H-benzotriazol-2-yl)-4		system.
	,6-bis(1,1-dimethylpropyl)		
	-		
57583-35-4	8-Oxa-3,5-dithia-4-stannat	Irritant	Eyes, Skin.
	etradecanoic acid,		
	10-ethyl-4,4-dimethyl-7-o		
	xo-, 2-ethylhexyl ester		
7631-86-9	Silica, amorphous	Irritant	Eyes, Respiratory system.
57583-34-3	Stannane,	Irritant	Eyes, Skin.
	methyltris(2-ethylhexylox		
	ycarbonylmethylthio)-		
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

#### LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
57583-34-3	Stannane, methyltris(2-ethylhexylox ycarbonylmethylthio)-	Oral LD50	920 mg/kg	rat

#### **12. ECOLOGICAL INFORMATION**

Persistence and degradability	:	Not readily biodegradable.
Environmental Toxicity	:	Chemicals are not readily available as they are bound within the matrix of the polymer.
Bioaccumulation Potential	:	Chemicals are not readily available as they are bound within the matrix of the polymer.
Additional advice	:	No data available



MATERIAL SAFETY DATA SHEET
Safety Yellow (WP w / UV)

Version Number 1.1 Revision Date 01/21/2004 Page 6 of 7 Print Date 11/13/2011

<b>D</b>	
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste materi has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA (air)	: Refer to specific regulation.
IMO / IMDG (maritime)	: Refer to specific regulation.
· · ·	
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSC Inventory.
US. EPA CERCLA Hazardo	us Substances (40 CFR 302)
Not applicable	
California Proposition 65	n : WARNING! This product contains a chemical known to the State o California to cause cancer.
SARA Title III Section 302 I	Extremely Hazardous Substance
Not applicable	
SARA Title III Section 313	Foxic Chemicals:
Not applicable Canadian Regulations:	

PolyOne

## MATERIAL SAFETY DATA SHEET Safety Yellow (WP w / UV)

Version Number 1.1 Revision Date 01/21/2004 Page 7 of 7 Print Date *11/13/2011* 

National Pollutant Release I	nventory (NPRI)
Not applicable	
WHMIS Classification :	D2B
WHMIS Ingredient Disclosu	ure List
CAS-No. 57583-35-4 7631-86-9 57583-34-3	
DSL :	DSL status has not been determined. Quantity use in Canada may be restricted by regulations.
National Inventories:	
Australia AICS :	Not determined
China IECS :	Not determined
Europe EINECS :	Not determined
Japan ENCS :	Not determined
Korea KECI :	Not determined
Philippines PICCS :	Not determined
	16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.