

MATERIAL SAFETY DATA SHEET

SUNRISE

Version Number 1.0 Revision Date 07/25/2002 Page 1 of 5 Print Date 11/5/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	SUNRISE
Product code	:	CC10020471
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Titanium dioxide	13463-67-7	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed.
Eyes Skin	Resin particles, like other inert materials, are mechanically irritating to eyes.Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.
Aggravated by Exposure.	



MATERIAL SAFETY DATA SHEET

SUNRISE

ion Number 1.0 sion Date 07/25/2002	Page 2 Print Date 11/5/2
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist, or in all cases o doubt, seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist, or in all cases of doubt, seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seel medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	 Not applicable Not applicable Not relevant Carbon dioxide blanket, Water spray, dry powder, foam.
Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. None
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 12 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	: Keep containers dry and tightly closed to avoid moisture absorption



MATERIAL SAFETY DATA SHEET

SUNRISE

sion Date 07/25/2002					Print Date	Page 3 11/5/2
	a	nd contamination. 1	Keep in a d	ry, cool place.		
8. E	XPOSURE	CONTROLS / PE	RSONAL	PROTECTION		
Respiratory protection	: N	No personal respiratory protective equipment normally required.				
Eye/Face Protection	: S	afety glasses with s	side-shields.			
Hand protection	: P	: Protective gloves.				
Skin and body protection	: Long sleeved clothing.					
Additional Protective Measures	: Safety shoes.					
General Hygiene Considerations	: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.					
Engineering measures	: Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.					
Exposure limit(s)						
Components	Value	Exposure ti	me	Exposure typ	e I	_ist:
Titanium dioxide	10 mg/m3	Time Weighted A (TWA):	-	Total dust.	A	CGIH
Titanium dioxide	15 mg/m3	PEL:		Total dust.	OS	HA Z1
	9. PHYSIC	CAL AND CHEMI	ICAL PRO	PERTIES		
	· Solid				N. ()	
Form	: Solic	1	Evapor	ration rate :	Not applic	able.
	: Solic : Pelle			cation rate : c Gravity :	Not applic Not deterr	
Form Appearance Color		ets	Specifi	c Gravity :		nined
Appearance	: Pelle	ets LOW	Specifi Bulk d	c Gravity :	Not deterr Not establ	nined ished
Appearance Color	: Pelle : YEL : Very	ets LOW	Specifi Bulk d Vapor	c Gravity : ensity :	Not deterr	nined ished able
Appearance Color Odor	: Pelle : YEL : Very : Not o	ets LOW 7 faint	Specifi Bulk d Vapor	c Gravity : ensity : pressure :	Not detern Not establ Not applic	nined ished able able
Appearance Color Odor Melting point/range Boiling Point:	: Pelle : YEL : Very : Not o	ets LOW / faint determined applicable	Specifi Bulk d Vapor Vapor	c Gravity : ensity : pressure :	Not detern Not establ Not applic Not applic	nined ished able able
Appearance Color Odor Melting point/range	: Pelle : YEL : Very : Not o : Not a : Insol	ets LOW / faint determined applicable	Specifi Bulk d Vapor Vapor pH	c Gravity : ensity : pressure : density : :	Not detern Not establ Not applic Not applic	nined ished able able
Appearance Color Odor Melting point/range Boiling Point: Water solubility	: Pelle : YEL : Very : Not o : Not a : Insol	ets LOW 7 faint determined applicable luble	Specifi Bulk d Vapor Vapor pH	c Gravity : ensity : pressure : density : :	Not detern Not establ Not applic Not applic	nined ished able able
Appearance Color Odor Melting point/range Boiling Point:	: Pelle : YEL : Very : Not a : Not a : Insol 10. S : S	ets LOW 7 faint determined applicable luble STABILITY AND	Specifi Bulk d Vapor Vapor pH	c Gravity : ensity : pressure : density : :	Not detern Not establ Not applic Not applic	nined ished able able
Appearance Color Odor Melting point/range Boiling Point: Water solubility Stability	: Pelle : YEL : Very : Not a : Not a : Insol 10. § : S n : W : K	ets LOW 7 faint determined applicable luble STABILITY AND	Specifi Bulk d Vapor pH REACTIV dizing agen	c Gravity : ensity : pressure : density : TTY TTY	Not deterr Not establ Not applic Not applic Not applic	nined ished cable cable cable



MATERIAL SAFETY DATA SHEET

SUNRISE

Version Number 1.0 Revision Date 07/25/2002 Page 4 of 5 Print Date 11/5/2011

Hazardous decomposition products

: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ			
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.			
	12. ECOLOGIO	CAL INFORMATION	1			
Persistence and degrada	ability : Not readily b	iodegradable.				
Environmental Toxicity		Chemicals are not readily available as they are bound within the matrix of the polymer.				
Bioaccumulation Poten		: Chemicals are not readily available as they are bound within the matrix of the polymer.				
Additional advice	: No data avail	able.				
	13. DISPOSAL	CONSIDERATIONS	9			
Product Contaminated packagin	possible, recy generator of v classification applicable fea g : Recycling is p has the respon and disposal	 Like most thermoplastics the product can be recycled. Where possible, recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal. 				
	14. TRANSPO	RT INFORMATION				
U.S. DOT / CA TDG Classification	: Not regulated	l for transportation.				
ICAO/IATA	: Not regulated	: Not regulated for transportation.				
IMO / IMDG	: Not regulated	l for transportation.				

MATERIAL SAFETY DATA SHEET



SUNRISE Version Number 1.0 Page 5 of 5 Print Date 11/5/2011 Revision Date 07/25/2002 US Regulations: **OSHA Status** : Classified as hazardous based on components. **TSCA Status** All components of this product are listed on the TSCA inventory or are : exempt. US. EPA CERCLA Hazardous Substances (40 CFR 302) Not applicable California Proposition : This product does not contain a substance listed by California Prop 65. 65 Canadian Regulations: WHMIS Classification : D2B DSL : Listed. National Inventories: Australia AICS : Listed. China IECS Listed. : **Europe EINECS** Not determined. Japan ENCS Listed. : Korea KECI Listed. : **Philippines PICCS** : Not determined.

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.