

### MATERIAL SAFETY DATA SHEET

# GREEN

Version Number 1.0 Revision Date 07/29/2002 Page 1 of 5 Print Date 11/5/2011

## 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	GREEN
Product code	:	CC10020685
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

### 2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Titanium dioxide	13463-67-7	10 - 30

#### **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

# POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes	<ul> <li>Resin particles, like other inert materials, can be mechanically irritating.</li> <li>May be harmful if swallowed.</li> <li>Resin particles, like other inert materials, are mechanically irritating to eyes.</li> </ul>
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.



# MATERIAL SAFETY DATA SHEET

# GREEN

	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist, or in all cases o doubt, seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist, or in all cases of doubt, seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seel medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits	
Upper explosion limit	: Not applicable
Lower explosion limit	: Not applicable
Autoignition temperature	: Not relevant
Suitable extinguishing media	: Carbon dioxide blanket, Water spray, dry powder, foam.
Special Fire Fighting	: Fullface self-contained breathing apparatus (SCBA) used in positive
Procedures	pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	: None
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 12 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	: Keep containers dry and tightly closed to avoid moisture absorption



# MATERIAL SAFETY DATA SHEET

# GREEN

sion Date 07/29/2002					Print Da	Page 3 ate 11/5/2
	a	nd contamination. K	eep in a d	ry, cool place.		
8. E	XPOSURE	CONTROLS / PER	RSONAL	PROTECTION		
Respiratory protection	: N	: No personal respiratory protective equipr			nally rec	quired.
Eye/Face Protection	: S	afety glasses with sic	side-shields.			
Hand protection	: Protective gloves.					
Skin and body protection	: Long sleeved clothing.					
Additional Protective Measures	: S	afety shoes.				
General Hygiene Considerations	: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.					
Engineering measures	: Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.					
Exposure limit(s)						
Components	Value	Exposure tin	ne	Exposure typ	e	List:
Titanium dioxide	10 mg/m3	Time Weighted A (TWA):	verage	Total dust.		ACGIH
Titanium dioxide	15 mg/m3	PEL:		Total dust.		OSHA Z1
	0 PHVSI	CAL AND CHEMIC	CAL PRO	PERTIES		
	<i><b>7.1115</b></i>	AL AND CHEMIC				
Form	: Solic			ration rate :	Not a	pplicable.
		1	Evapo			pplicable. etermined
Form Appearance Color	: Solic	l ets	Evapo Specif	ic Gravity :	Not d	
Appearance	: Solic : Pelle : GRE	l ets EN	Evapo Specif Bulk d	ic Gravity : ensity :	Not de Not es	etermined stablished
Appearance Color Odor	: Solic : Pelle : GRE : Very	l ets EN 7 faint	Evapo Specif Bulk d Vapor	ic Gravity : ensity : pressure :	Not de Not es Not aj	etermined stablished pplicable
Appearance Color Odor Melting point/range	: Solic : Pelle : GRE : Very : Not o	l ets EN faint determined	Evapo Specif Bulk d Vapor Vapor	ic Gravity : ensity :	Not de Not es Not aj Not aj	etermined stablished pplicable pplicable
Appearance Color Odor	: Solic : Pelle : GRE : Very : Not o	l EN faint determined applicable	Evapo Specif Bulk d Vapor	ic Gravity : ensity : pressure :	Not de Not es Not aj Not aj	etermined stablished pplicable
Appearance Color Odor Melting point/range Boiling Point:	: Solic : Pelle : GRE : Very : Not : Not : Insol	l EN faint determined applicable	Evapo Specif Bulk d Vapor Vapor pH	ic Gravity : ensity : pressure : density : :	Not de Not es Not aj Not aj	etermined stablished pplicable pplicable
Appearance Color Odor Melting point/range Boiling Point:	: Solid : Pelle : GRE : Very : Not : Not : Insol <b>10. \$</b>	l ets EEN faint determined applicable luble	Evapo Specif Bulk d Vapor Vapor pH	ic Gravity : ensity : pressure : density : :	Not de Not es Not aj Not aj	etermined stablished pplicable pplicable
Appearance Color Odor Melting point/range Boiling Point: Water solubility	: Solid : Pelle : GRE : Very : Not ( : Not ( : Insol <b>10. S</b> : S	l ETS EN faint determined applicable luble STABILITY AND R	Evapo Specif Bulk d Vapor Vapor pH	ic Gravity : ensity : pressure : density : :	Not de Not es Not aj Not aj	etermined stablished pplicable pplicable
Appearance Color Odor Melting point/range Boiling Point: Water solubility Stability	: Solid : Pelle : GRE : Very : Not a : Not a : Insol <b>10. S</b> : S	l ets EN faint determined applicable luble <b>STABILITY AND R</b> table.	Evapo Specif Bulk d Vapor pH REACTIV	ic Gravity : ensity : pressure : density :	Not d Not es Not aj Not aj	etermined stablished pplicable pplicable pplicable



# MATERIAL SAFETY DATA SHEET

# GREEN

Version Number 1.0 Revision Date 07/29/2002 Page 4 of 5 Print Date 11/5/2011

Hazardous decomposition products

: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

### 11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ			
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.			
	12. ECOLOGI	CAL INFORMATION	I			
Persistence and degrad	ability : Not readily b	iodegradable.				
Environmental Toxicit		: Chemicals are not readily available as they are bound within the of the polymer.				
Bioaccumulation Poten		: Chemicals are not readily available as they are bound within the matrix of the polymer.				
Additional advice	: No data avail	lable.				
	13. DISPOSAL	<b>CONSIDERATIONS</b>	9			
Product Contaminated packagin	possible, recy generator of classification applicable fe ng : Recycling is has the respo	ycling is preferred to di waste material has the r i, transportation and dis deral, state/provincial a preferred when possible nsibility for proper was in accordance with app	ct can be recycled. Where sposal or incineration. The responsibility for proper waste posal in accordance with nd local regulations. e. The generator of waste materia ste classification, transportation licable federal, state/provincial			
	14. TRANSPO	ORT INFORMATION				
U.S. DOT / CA TDG Classification	: Not regulated	l for transportation.				
ICAO/IATA	: Not regulated	: Not regulated for transportation.				
IMO / IMDG	: Not regulated	l for transportation.				
	15. REGULAT					

### MATERIAL SAFETY DATA SHEET



# GREEN Version Number 1.0 Page 5 of 5 Print Date 11/5/2011 Revision Date 07/29/2002 US Regulations: **OSHA Status** : Classified as hazardous based on components. **TSCA Status** All components of this product are listed on the TSCA inventory or are : exempt. US. EPA CERCLA Hazardous Substances (40 CFR 302) Not applicable California Proposition : This product does not contain a substance listed by California Prop 65. 65 Canadian Regulations: WHMIS Classification : D2B DSL : Listed. National Inventories: Australia AICS : Listed. China IECS Listed. : **Europe EINECS** Not determined. Japan ENCS Listed. : Korea KECI : Listed. **Philippines PICCS** : Listed.

### **16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.