

MATERIAL SAFETY DATA SHEET

MUSTARD YELLOW

Version Number 1.0 Revision Date 08/23/2002 Page 1 of 7 Print Date 11/5/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	MUSTARD YELLOW
Product code	:	CC10021606
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Carbon black	1333-86-4	0.1 - 1
Silica, amorphous	7631-86-9	1 - 5
Titanium dioxide	13463-67-7	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes Skin	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Particulates, like other inert materials can be mechanically irritating. Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.



MATERIAL SAFETY DATA SHEET

MUSTARD YELLOW

Version Number 1.0 Page 2 of 7 Revision Date 08/23/2002 Print Date 11/5/2011 **4. FIRST AID MEASURES** Inhalation Move to fresh air in case of accidental inhalation of fumes from ÷ overheating or combustion. When symptoms persist, or in all cases of doubt, seek medical advice. Ingestion Do not induce vomiting without medical advice. When symptoms : persist, or in all cases of doubt, seek medical advice. Eyes Rinse immediately with plenty of water, also under the eyelids, for at : least 15 minutes. If eye irritation persists, seek medical attention. Skin Wash off with soap and plenty of water. If skin irritation persists seek : medical attention. **5. FIRE-FIGHTING MEASURES** Flash point Not applicable : Flammable Limits Upper explosion limit Not applicable : Lower explosion limit Not applicable : Autoignition temperature Not relevant : Carbon dioxide blanket, Water spray, dry powder, foam. Suitable extinguishing media : Special Fire Fighting Fullface self-contained breathing apparatus (SCBA) used in positive : Procedures pressure mode should be worn to prevent inhalation of airborne contaminants. Unusual Fire/Explosion · none Hazards 6. ACCIDENTAL RELEASE MEASURES Personal precautions : Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls. Environmental precautions Should not be released into the environment. The product should not : be allowed to enter drains, water courses or the soil. Clean up promptly by scoop or vacuum. Package all material in Methods for cleaning up : plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods. 7. HANDLING AND STORAGE Handling Take measures to prevent the build up of electrostatic charge. Heat : only in areas with appropriate exhaust ventilation. Storage Keep containers dry and tightly closed to avoid moisture absorption ·



MATERIAL SAFETY DATA SHEET

MUSTARD YELLOW

Version Number 1.0 Revision Date 08/23/2002 Page 3 of 7 Print Date 11/5/2011

	aı	nd contamination. Keep in a	dry, cool place.		
8.	EXPOSURE	CONTROLS / PERSONA	L PROTECTION		
Respiratory protection		No personal respiratory protective equipment normally required. If dusty conditions occur wear appropriate respiratory protection.			
Eye/Face Protection : safety glasses					
Hand protection	: P:	rotective gloves.			
Skin and body protection	n : L	ong sleeved clothing.			
Additional Protective Measures	: S	afety shoes.			
General Hygiene Considerations	pi	Vash hands and face before b roduct. Handle in accordanc ractice for diagnostics.			
Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.					
Exposure limit(s)					
Components	Value	Exposure time	Exposure type	List:	
Components Carbon black	Value 3.5 mg/m3	Exposure time Time Weighted Average	Exposure type Total dust. as carbon	List: ACGIH	
		Time Weighted Average	Total dust. as carbon		
Carbon black	3.5 mg/m3 3.5 mg/m3 20 mppcf	Time Weighted Average (TWA):	Total dust. as carbon black Total dust. as carbon	ACGIH	
Carbon black Carbon black Silica, amorphous Silica, amorphous	3.5 mg/m3 3.5 mg/m3	Time Weighted Average (TWA): PEL: PEL: PEL:	Total dust. as carbon black Total dust. as carbon black	ACGIH OSHA Z1	
Carbon black Carbon black Silica, amorphous	3.5 mg/m3 3.5 mg/m3 20 mppcf	Time Weighted Average (TWA): PEL: PEL:	Total dust. as carbon black Total dust. as carbon black Total dust.	ACGIH OSHA Z1 OSHA	
Carbon black Carbon black Silica, amorphous Silica, amorphous	3.5 mg/m3 3.5 mg/m3 20 mppcf 20 mppcf	Time Weighted Average (TWA): PEL: PEL: PEL: Time Weighted Average	Total dust. as carbon blackTotal dust. as carbon blackTotal dust.Total dust.Total dust.Total dust.	ACGIH OSHA Z1 OSHA Z3	
Carbon black Carbon black Silica, amorphous Silica, amorphous Titanium dioxide	3.5 mg/m3 3.5 mg/m3 20 mppcf 20 mppcf 10 mg/m3 15 mg/m3	Time Weighted Average (TWA): PEL: PEL: PEL: Time Weighted Average (TWA):	Total dust. as carbon black Total dust. as carbon black Total dust.	ACGIH OSHA Z1 OSHA Z3 ACGIH	
Carbon black Carbon black Silica, amorphous Silica, amorphous Titanium dioxide Titanium dioxide	3.5 mg/m3 3.5 mg/m3 20 mppcf 20 mppcf 10 mg/m3 15 mg/m3 9. PHYSIC	Time Weighted Average (TWA): PEL: PEL: PEL: Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PI	Total dust. as carbon black Total dust. as carbon black Total dust. Total dust. Total dust. Total dust. Total dust. Total dust. SOPERTIES	ACGIH OSHA Z1 OSHA Z3 ACGIH OSHA Z1	
Carbon black Carbon black Silica, amorphous Silica, amorphous Titanium dioxide Titanium dioxide	3.5 mg/m3 3.5 mg/m3 20 mppcf 20 mppcf 10 mg/m3 15 mg/m3 9. PHYSIC : Solid	Time Weighted Average (TWA): PEL: PEL: PEL: Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PI	Total dust. as carbon black Total dust. as carbon black Total dust. as carbon black Total dust. SOPERTIES poration rate : Not	ACGIH OSHA Z1 OSHA Z3 ACGIH OSHA Z1 applicable.	
Carbon black Carbon black Silica, amorphous Silica, amorphous Titanium dioxide Titanium dioxide Form Appearance	3.5 mg/m3 3.5 mg/m3 20 mppcf 20 mppcf 10 mg/m3 15 mg/m3 9. PHYSIC : Solid : flake	Time Weighted Average (TWA): PEL: PEL: Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PI	Total dust. as carbon black Total dust. as carbon black Total dust. as carbon black Total dust. Soperation rate : Not cific Gravity : Not	ACGIH OSHA Z1 OSHA Z3 ACGIH OSHA Z1	
Carbon black Carbon black Silica, amorphous Silica, amorphous Titanium dioxide Titanium dioxide Form Appearance Color	3.5 mg/m3 3.5 mg/m3 20 mppcf 20 mppcf 10 mg/m3 15 mg/m3 9. PHYSIC : Solid : flake : YEL	Time Weighted Average (TWA): PEL: PEL: Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PI I Evaj s Spec LOW Bulk	Total dust. as carbon black Total dust. as carbon black Total dust. as carbon black Total dust. Soperation rate : Not tific Gravity : Not t density : Not	ACGIH OSHA Z1 OSHA Z3 ACGIH OSHA Z1 applicable. determined	
Carbon black Carbon black Silica, amorphous Silica, amorphous Titanium dioxide Titanium dioxide Form Appearance Color Odor	3.5 mg/m3 3.5 mg/m3 20 mppcf 20 mppcf 10 mg/m3 15 mg/m3 9. PHYSIC : Solid : flake : YEL : Very	Time Weighted Average (TWA): PEL: PEL: Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PI I Evaj s Spec LOW Bulk faint Vap	Total dust. as carbon black Total dust. as carbon black Total dust. as carbon black Total dust. Soperation rate : Not tific Gravity : Not tor pressure : Not	ACGIH OSHA Z1 OSHA Z3 ACGIH OSHA Z1 applicable. determined determined	
Carbon black Carbon black Silica, amorphous Silica, amorphous Titanium dioxide	3.5 mg/m3 3.5 mg/m3 20 mppcf 20 mppcf 10 mg/m3 15 mg/m3 9. PHYSIC : Solid : flake : YEL : Very : Grea	Time Weighted Average (TWA): PEL: PEL: Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PI I Evaj s Spec LOW Bulk faint Vap	Total dust. as carbon black Total dust. as carbon black Total dust. as carbon black Total dust. Soperation rate : Not String Gravity : Not tor pressure : Not or density : Not	ACGIH OSHA Z1 OSHA Z3 ACGIH OSHA Z1 applicable. determined determined	
Carbon black Carbon black Silica, amorphous Silica, amorphous Titanium dioxide Titanium dioxide Form Appearance Color Odor Melting point/range	3.5 mg/m3 3.5 mg/m3 20 mppcf 20 mppcf 10 mg/m3 15 mg/m3 9. PHYSIC : Solid : flake : YEL : Very : Grea	Time Weighted Average (TWA): PEL: PEL: Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PI s Spect LOW Bulk faint Vap ter than 130 °C Vap applicable pH	Total dust. as carbon black Total dust. as carbon black Total dust. as carbon black Total dust. Soperation rate : Not String Gravity : Not tor pressure : Not or density : Not	ACGIH OSHA Z1 OSHA Z3 ACGIH OSHA Z1 OSHA Z1	
Carbon black Carbon black Silica, amorphous Silica, amorphous Titanium dioxide Titanium dioxide Titanium dioxide Form Appearance Color Odor Melting point/range Boiling Point:	3.5 mg/m3 3.5 mg/m3 20 mppcf 20 mppcf 10 mg/m3 15 mg/m3 9. PHYSIC : Solid : flake : YEL : Very : Grea : Not a : Insol	Time Weighted Average (TWA): PEL: PEL: Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PI s Spect LOW Bulk faint Vap ter than 130 °C Vap applicable pH	Total dust. as carbon black Total dust. as carbon black Total dust. as carbon black Total dust. Second control dust. ROPERTIES poration rate : Not tor pressure : Not cor density : Not : Not	ACGIH OSHA Z1 OSHA Z3 ACGIH OSHA Z1 OSHA Z1	



MATERIAL SAFETY DATA SHEET

MUSTARD YELLOW

Version Number 1.0 Revision Date 08/23/2002		Page 4 of 7 Print Date 11/5/2011
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), dense black smoke.
	44	

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1333-86-4	Carbon black	Systemic effects	Eyes, Respiratory system.
7631-86-9	Silica, amorphous	Irritant	Eyes, Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

LC50 / LD50

This product contains the following components which in their pure form have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
1333-86-4	Carbon black	Oral LD50	>15,400 mg/kg	rat
		Dermal LD50	> 3 gm/kg	rabbit

Carcinogenicity:

This product contains the following components which in their pure form have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
1333-86-4	Carbon black	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

- 1 The component is known to be a human carcinogen.
- 2 The component is reasonably anticipated to be a human carcinogen.

Additional Health Hazard Information:



MATERIAL SAFETY DATA SHEET

MUSTARD YELLOW

 Version Number 1.0
 Page 5 of 7

 Revision Date 08/23/2002
 Print Date 11/5/2011

Carbon black 1333-86-4 Carcinogenicity: Many inhalation toxicologists believe that the tumor response observed in the referenced rat studies is species specific and does not correlate to human exposure. However, the IARC evaluation in Monograph Volume 65, issued in April 1996 concluded that, "There is sufficient evidence in experimental animals for the carcinogenicity of carbon black". Based on this evaluation, along with their evaluation of inadequate evidence of carcinogenicity in humans, IARC's overall evaluation is that "Carbon Black is possibly carcinogenic to humans (Group 2B). Carbon Black has not been listed as a carcinogen by the National Toxicology Program (NTP) or the Occupational Safety and Health Administration (OSHA). The National Institute of Occupational Safety and Health (NIOSH) criteria document on carbon black recommends that only carbon black with PAH (polynuclear aromatic hydrocarbon) levels greater than 0.1% be considered suspect carcinogens.

	12. ECOLOGICAL INFORMATION
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the matrix of the polymer.
Bioaccumulation Potential	: Not inherently biodegradable.
Additional advice	: Chemicals are not readily available as they are bound within the matrix of the polymer.
	13. DISPOSAL CONSIDERATIONS
Product	: Where possible, recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT / CA TDG Classification	: Not regulated for transportation.
ICAO/IATA	: Not regulated for transportation.
IMO / IMDG	: Not regulated for transportation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.



MATERIAL SAFETY DATA SHEET

MUSTARD YELLOW

Version Number 1.0 Revision Date 08/23/2002	Page 6 of 7 Print Date 11/5/2011
TSCA Status :	All components of this product are listed on the TSCA inventory or are exempt.
US. EPA CERCLA Hazardous Sub	ostances (40 CFR 302)
Not applicable	
California Proposition : 65	This product does not contain a substance listed by California Prop 65.
Canadian Regulations:	
WHMIS Classification :	D2A
WHMIS Ingredient Disclosu	ure List
CAS-No. 7631-86-9	
DSL :	Listed.
National Inventories:	
Australia AICS :	Not determined.
China IECS :	Not determined.
Europe EINECS :	Not determined.
Japan ENCS :	Not determined.
Korea KECI :	Not determined.
Philippines PICCS :	Not determined.
	16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

MATERIAL SAFETY DATA SHEET

MUSTARD YELLOW

Version Number 1.0 Revision Date 08/23/2002



Page 7 of 7 Print Date 11/5/2011