

MATERIAL SAFETY DATA SHEET

RED

Version Number 1.1 Revision Date 04/07/2004 Page 1 of 5 Print Date 11/14/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone number	:	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	RED
Product code	:	CC10021650
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

There are no known hazardous components above regulatory thresholds in this product.

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Route	es of Exposure:	: Inhalation, Ingestion, Skin contact
Acute	exposure	
	Inhalation Ingestion Eyes Skin	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to eyes. Experience shows no unusual dermatitis hazard from routine handling.
Medic	nic exposure cal Conditions avated by Exposure:	Refer to Section 11 for Toxicological Information.None known.
		4. FIRST AID MEASURES



MATERIAL SAFETY DATA SHEET

RED

ion Number 1.1 sion Date 04/07/2004	Page 2 Print Date 11/14/2		
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.		
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.		
Eyes	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.		
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.		
	5. FIRE-FIGHTING MEASURES		
Flash point	: Not applicable		
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	 Not applicable Not applicable Not applicable Carbon dioxide blanket, water spray, dry powder, foamnone. 		
Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. 		
	6. ACCIDENTAL RELEASE MEASURES		
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.		
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.		
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.		
	7. HANDLING AND STORAGE		
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.		
Storage	: Keep containers dry and tightly closed to avoid moisture absorption		



MATERIAL SAFETY DATA SHEET

RED

Version Number 1.1 Revision Date 04/07/2004

Page 3 of 5 Print Date 11/14/2011

Respiratory protection	: No personal respin	ratory protective equipment normally required.		
Eye/Face Protection	: Safety glasses wit	Safety glasses with side-shields.		
Hand protection	: Protective gloves.	Protective gloves.		
Skin and body protection	: Long sleeved clot	Long sleeved clothing.		
Additional Protective Measures	: Safety shoes.			
General Hygiene Considerations		Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.		
Engineering measures		Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.		
Exposure limit(s)				
There are no known hazardou	s components above regu	latory thresholds in this product.		
9.	PHYSICAL AND CHE	MICAL PROPERTIES		
Form Appearance Color Odor Melting point/range Boiling Point: Water solubility	 Solid Pellets RED Very faint Not determined Not applicable Insoluble 	Evaporation rate:Not applicableSpecific Gravity::Not determinedBulk density:Not establishedVapor pressure:Not applicableVapour density:Not applicablepH:Not applicable		
	10. STABILITY AN	D REACTIVITY		
Stability	: Stable.			
Hazardous Polymerization	: Will not occur.			
Conditions to avoid		Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.		
	: Incompatible with	strong acids and oxidizing agents.		
Incompatible Materials		CO2), carbon monoxide (CO), oxides of nitrogen		
		rdous materials, and smoke are all possible.		



MATERIAL SAFETY DATA SHEET

RED

Version Number 1.1 Revision Date 04/07/2004 Page 4 of 5 Print Date 11/14/2011

There are no known hazardous components above regulatory thresholds in this product.

Persistence and degradability	: Not readily biodegradable.	
reisistence and degradability	. Not readily blodegradable.	
Environmental Toxicity	: Chemicals are not readily available as they are bound within the of the polymer.	
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the matrix of the polymer.	
Additional advice	: No data available	
	13. DISPOSAL CONSIDERATIONS	
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.	
Contaminated packaging	: Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.	
	14. TRANSPORT INFORMATION	
U.S. DOT Classification	: Not regulated for transportation.	
ICAO/IATA (air)	: Refer to specific regulation.	
IMO / IMDG (maritime)	: Refer to specific regulation.	
	15. REGULATORY INFORMATION	
US Regulations:		
OSHA Status	: There are no known hazardous components above regulatory thresholds in this product.	
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.	
US. EPA CERCLA Hazardous	Substances (40 CFR 302)	
Not applicable		



MATERIAL SAFETY DATA SHEET

RED

ersion Number 1.1 evision Date 04/07/2004		Print Date	Page 5 of 11/14/201
California Proposition 65	: This product does not contain a substance lis	ted by California	a Prop 65.
SARA Title III Section 302 Ext	remely Hazardous Substance		
Not applicable			
SARA Title III Section 313 Tox	ic Chemicals:		
Not applicable Canadian Regulations:			
National Pollutant Relea	e Inventory (NPRI)		
Not applicable			
WHMIS Classification	: Not controlled.		
DSL	: All components of this product are on the C Substances List (DSL) or are exempt.	anadian Domest	ic
National Inventories:			
Australia AICS	: Listed		
China IECS	: Listed		
Europe EINECS	: Listed		
Japan ENCS	: Listed		
Korea KECI	: Listed		

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.