

MATERIAL SAFETY DATA SHEET

GRAPHITE ABS

Version Number 1.0 Revision Date 08/20/2002 Page 1 of 7 Print Date 11/5/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	GRAPHITE ABS
Product code	:	CC10021778
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Aluminum	7429-90-5	1 - 5
Carbon black	1333-86-4	1 - 5
Titanium dioxide	13463-67-7	1 - 5
Mica	12001-26-2	5 - 10

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion	Resin particles, like other inert materials, can be mechanically irritating.May be harmful if swallowed.
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.





GRAPHITE ABS Version Number 1.0 Page 2 of 7 Revision Date 08/20/2002 Print Date 11/5/2011 **Medical Conditions** : None known. Aggravated by Exposure: 4. FIRST AID MEASURES Inhalation Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist, or in all cases of doubt, seek medical advice. Do not induce vomiting without medical advice. When symptoms Ingestion : persist, or in all cases of doubt, seek medical advice. Eyes : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention. Skin : Wash off with soap and plenty of water. If skin irritation persists seek medical attention. **5. FIRE-FIGHTING MEASURES** Flash point : Not applicable Flammable Limits Upper explosion limit Not applicable : Lower explosion limit Not applicable : Autoignition temperature Not relevant : Suitable extinguishing media : Carbon dioxide blanket, Water spray, dry powder, foam. Special Fire Fighting Fullface self-contained breathing apparatus (SCBA) used in positive : Procedures pressure mode should be worn to prevent inhalation of airborne contaminants. Unusual Fire/Explosion None • Hazards 6. ACCIDENTAL RELEASE MEASURES Personal precautions : Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls. Environmental precautions Should not be released into the environment. The product should not : be allowed to enter drains, water courses or the soil. Methods for cleaning up Clean up promptly by sweeping or vacuum. Package all material in : plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods. 7. HANDLING AND STORAGE Handling Take measures to prevent the build up of electrostatic charge. Heat · only in areas with appropriate exhaust ventilation.

MATERIAL SAFETY DATA SHEET

GRAPHITE ABS



/ersion Number 1.0 Revision Date 08/20/2002		Page 3 of 7 Print Date 11/5/2011
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.
8. EXI	POSUE	RE CONTROLS / PERSONAL PROTECTION
Respiratory protection	:	No personal respiratory protective equipment normally required.
Eye/Face Protection	:	Safety glasses with side-shields.
Hand protection	:	Protective gloves.
Skin and body protection	:	Long sleeved clothing.
Additional Protective Measures	:	Safety shoes.
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Aluminum	10 mg/m3	Time Weighted Average	Dust.	ACGIH
		(TWA):		
	5 mg/m3	Time Weighted Average	Welding fume. as Al	ACGIH
		(TWA):		
Aluminum	15 mg/m3	PEL:	Total dust. as Al	OSHA Z1
	5 mg/m3	PEL:	Respirable dust. as Al	OSHA Z1
Carbon black	3.5 mg/m3	Time Weighted Average	Total dust. as carbon	ACGIH
		(TWA):	black	
Carbon black	3.5 mg/m3	PEL:	Total dust. as carbon	OSHA Z1
			black	
Mica	3 mg/m3	Time Weighted Average	Total dust.	ACGIH
		(TWA):		
Mica	20 mppcf	PEL:	Total dust.	OSHA
Titanium dioxide	10 mg/m3	Time Weighted Average	Total dust.	ACGIH
		(TWA):		
Titanium dioxide	15 mg/m3	PEL:	Total dust.	OSHA Z1

9. PHYSICAL AND CHEMICAL PROPERTIES

Form Appearance Color Odor

: Solid : Pellets : GREY : Very faint

Evaporation rate:Not applicable.Specific Gravity:Not determinedBulk density:Not establishedVapor pressure:Not applicable



MATERIAL SAFETY DATA SHEET

GRAPHITE ABS

Version Number 1.0 Revision Date 08/20/2002		Page 4 of 7 Print Date 11/5/2011
Melting point/range Boiling Point: Water solubility	 Not determined Vapor density Not applicable pH Insoluble 	Not applicableNot applicable
	10. STABILITY AND REACTIVITY	
Stability	: Stable.	
Hazardous Polymerization	: Will not occur.	
Conditions to avoid	: Keep away from oxidizing agents and open fl decomposition, do not overheat.	ame. To avoid thermal
Incompatible Materials	: Incompatible with strong acids and oxidizing	agents.
Hazardous decomposition products	: Carbon dioxide (CO2), carbon monoxide (CO (NOx), other hazardous materials, and smoke	U U

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
7429-90-5	Aluminum	Irritant	Skin, Respiratory system.
		Systemic effects	Eyes, Skin, Respiratory system.
1333-86-4	Carbon black	Systemic effects	Eyes, Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.
12001-26-2	Mica	Systemic effects	Respiratory system.

LC50 / LD50

This product contains the following components which in their pure form have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
1333-86-4	Carbon black	Oral LD50	>15,400 mg/kg	rat
		Dermal LD50	> 3 gm/kg	rabbit

Carcinogenicity:

This product contains the following components which in their pure form have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
1333-86-4	Carbon black	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.



MATERIAL SAFETY DATA SHEET

GRAPHITE ABS

Version Number 1.0 Revision Date 08/20/2002 Page 5 of 7 Print Date 11/5/2011

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

Additional Health Hazard Information:

Carbon black 1333-86-4 Carcinogenicity: Many inhalation toxicologists believe that the tumor response observed in the referenced rat studies is species specific and does not correlate to human exposure. However, the IARC evaluation in Monograph Volume 65, issued in April 1996 concluded that, "There is sufficient evidence in experimental animals for the carcinogenicity of carbon black". Based on this evaluation, along with their evaluation of inadequate evidence of carcinogenicity in humans, IARC's overall evaluation is that "Carbon Black is possibly carcinogenic to humans (Group 2B). Carbon Black has not been listed as a carcinogen by the National Toxicology Program (NTP) or the Occupational Safety and Health Administration (OSHA). The National Institute of Occupational Safety and Health (NIOSH) criteria document on carbon black recommends that only carbon black with PAH (polynuclear aromatic hydrocarbon) levels greater than 0.1% be considered suspect carcinogens.

Persistence and degradability	: Not readily biodegradable.
rensistence and degradability	. Not readily blodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the matrix of the polymer.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the matrix of the polymer.
Additional advice	: No data available.
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastics the product can be recycled. Where possible, recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT / CA TDG Classification	: Not regulated for transportation.
ICAO/IATA	: Not regulated for transportation.



MATERIAL SAFETY DATA SHEET

GRAPHITE ABS

			Print [Date 11/5/
IMO / IMDG	: Not regulated f	or transportation.		
	15. REGULATO	RY INFORMATIO	DN	
US Regulations:				
OSHA Status	: Classified as ha	azardous based on c	omponents.	
TSCA Status	: All component exempt.	s of this product are	listed on the TSCA inv	ventory or a
US. EPA CERCLA Hazardo	us Substances (40 CFR	302)		
Not applicable				
California Propositio	n : This product do	bes not contain a sub	ostance listed by Califo	ornia Prop 6
65	1		5	1
SARA Title III Section 313	Toxic Chemicals:			
Chemical Nat	me	CAS-No.	Weight %	
Chemical Nat ALUMINUM		CAS-No. 7429-90-5	Weight % 03.93	
Chemical Nar ALUMINUM Canadian Regulations:	me I (FUME OR DUST)]
Chemical Nat ALUMINUM Canadian Regulations: WHMIS Classification	me I (FUME OR DUST) on : D2A]
Chemical Nar ALUMINUM Canadian Regulations:	me I (FUME OR DUST) on : D2A			
Chemical Nat ALUMINUM Canadian Regulations: WHMIS Classificatio WHMIS Ingredient D CAS-No. 7429-90-5 1333-86-4	me I (FUME OR DUST) on : D2A			
Chemical Nat ALUMINUM Canadian Regulations: WHMIS Classificatio WHMIS Ingredient D CAS-No. 7429-90-5 1333-86-4 12001-26-2	me I (FUME OR DUST) on : D2A Disclosure List			
Chemical Nat ALUMINUM Canadian Regulations: WHMIS Classification WHMIS Ingredient D CAS-No. 7429-90-5 1333-86-4 12001-26-2 DSL	me I (FUME OR DUST) on : D2A Disclosure List			
Chemical Nat ALUMINUM Canadian Regulations: WHMIS Classification WHMIS Ingredient D CAS-No. 7429-90-5 1333-86-4 12001-26-2 DSL National Inventories:	me I (FUME OR DUST) on : D2A Disclosure List . Listed.			
Chemical Nat ALUMINUM Canadian Regulations: WHMIS Classification WHMIS Ingredient D CAS-No. 7429-90-5 1333-86-4 12001-26-2 DSL National Inventories: Australia AICS	me I (FUME OR DUST) on : D2A Disclosure List : Listed. : Listed.	7429-90-5		

MATERIAL SAFETY DATA SHEET

GRAPHITE ABS

Version Number 1.0 Revision Date 08/20/2002

Korea KECI

P	bh	zO	ne	
-				

Page 7 of 7

Print Date 11/5/2011

: Listed.

Philippines PICCS : Listed.

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.