

MATERIAL SAFETY DATA SHEET

BRICK 492

Version Number 1.0 Revision Date 09/16/2002 Page 1 of 6 Print Date 11/6/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE Emergency telephone number	:	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name Product code Chemical Name CAS-No. Product Use	::	BRICK 492 CC10023336 Mixture Mixture Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Titanium dioxide	13463-67-7	1 - 5

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact		
Acute exposure			
Inhalation Ingestion Eyes	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to ever 		
Skin	eyes. : Experience shows no unusual dermatitis hazard from routine handling.		
Chronic exposure	: Refer to Section 11 for Toxicological Information.		
Medical Conditions Aggravated by Exposure:	: None known.		



MATERIAL SAFETY DATA SHEET

BRICK 492

ion Number 1.0 sion Date 09/16/2002	Page 2 Print Date 11/6/2
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist, or in all cases o doubt, seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist, or in all cases of doubt, seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seel medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	 Not applicable Not applicable Not relevant Carbon dioxide blanket, Water spray, dry powder, foam.
Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. None
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 12 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	: Keep containers dry and tightly closed to avoid moisture absorption





BRICK 492

sion Date 09/16/2002				Print	Date 11/6/
	a	nd contamination. Keep in	n a dry, cool place.		
8. E	XPOSURE	CONTROLS / PERSON	AL PROTECTIO	N	
Respiratory protection	: N	lo personal respiratory pro	tective equipment n	ormally	required.
Eye/Face Protection	: S	Safety glasses with side-shields.			
Hand protection	: P	Protective gloves.			
Skin and body protection	: L	ong sleeved clothing.	ong sleeved clothing.		
Additional Protective Measures	: S	afety shoes.			
General Hygiene Considerations	: Handle in accordance with good industrial hygiene and safety practice Wash hands before breaks and at the end of workday.				
Engineering measures		: Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.			
Exposure limit(s)					
Components	Value	Exposure time	Exposure	type	List:
Titanium dioxide	10 mg/m3	Time Weighted Averag (TWA):	ge Dust.		ACGIH
Titanium dioxide	15 mg/m3	PEL:	Total du	st.	OSHA Z
	9. PHYSIC	CAL AND CHEMICAL	PROPERTIES		
Form Appearance Color Odor Melting point/range	: Not o	ets Sp D Bu V faint Va	vaporation rate ecific Gravity ilk density apor pressure apor density I	: Not : Not : Not : Not	applicable. determined established applicable applicable applicable
Boiling Point: Water solubility	: Insol				
Boiling Point:	: Insol		TIVITY		
Boiling Point:	: Insol 10. S	luble	TIVITY		
Boiling Point: Water solubility	: Insol 10. S : S	luble STABILITY AND REAC	TIVITY		
Boiling Point: Water solubility Stability	: Insol 10. § : S n : W : K	luble STABILITY AND REAC table.	agents and open flar	ne. To a	woid therma



MATERIAL SAFETY DATA SHEET

BRICK 492

Version Number 1.0 Revision Date 09/16/2002 Page 4 of 6 Print Date 11/6/2011

Hazardous decomposition products

: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No. 13463-67-7	Chemical Name Titanium dioxide	Effect Systemic effects	Target OrganRespiratory system.			
	12. ECOLOGIO	CAL INFORMATION	1			
Persistence and degrada	ability : Not readily b	iodegradable.				
Environmental Toxicity		: Chemicals are not readily available as they are bound within the matrix of the polymer.				
Bioaccumulation Poten		: Chemicals are not readily available as they are bound within the matrix of the polymer.				
Additional advice	: No data avail	able.				
	13. DISPOSAL	CONSIDERATIONS	5			
Product Contaminated packagir	possible, recy generator of v classification applicable fea ag : Recycling is p has the respon and disposal	 Like most thermoplastics the product can be recycled. Where possible, recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. 				
	14. TRANSPO	RT INFORMATION				
U.S. DOT Classificatio	n : Not regulated	l for transportation.				
ICAO/IATA	: Not regulated	l for transportation.				
IMO / IMDG	: Not regulated	l for transportation.				
	15. REGULATO	ORY INFORMATION	N			

MATERIAL SAFETY DATA SHEET



BRICK 492						
Version Number 1.0 Revision Date 09/16/2002		Page 5 of 6 Print Date 11/6/2011				
US Regulations:						
OSHA Status	:	Classified as hazardous based on components.				
TSCA Status	:	All components of this product are listed on the TSCA inventory or are exempt.				
US. EPA CERCLA Hazardous	US. EPA CERCLA Hazardous Substances (40 CFR 302)					
Not applicable						
California Proposition 65	:	This product does not contain a substance listed by California Prop 65.				
Canadian Regulations:						
WHMIS Classification	:	D2B				
DSL	:	Listed.				
National Inventories:						
Australia AICS	:	Listed.				
China IECS	:	Listed.				
Europe EINECS	:	Not determined.				
Japan ENCS	:	Not determined.				
Korea KECI	:	Listed.				
Philippines PICCS	:	Listed.				
		16. OTHER INFORMATION				

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

MATERIAL SAFETY DATA SHEET

BRICK 492

Version Number 1.0 Revision Date 09/16/2002



Page 6 of 6 Print Date 11/6/2011