

MATERIAL SAFETY DATA SHEET

10037907 YELLOW W/UV

Version Number 1.0 Revision Date 09/21/2002 Page 1 of 7 Print Date 11/6/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	10037907 YELLOW W/UV
Product code	:	CC10023679
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Titanium dioxide	13463-67-7	1 - 5
Chrome yellow (Lead chromate pigment)	1344-37-2	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.



MATERIAL SAFETY DATA SHEET

10037907 YELLOW W/UV

Version Number 1.0 Revision Date 09/21/2002 Page 2 of 7 Print Date 11/6/2011

		4. FIRST AID MEASURES
Inhalation	:	Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist, or in all cases of doubt, seek medical advice.
Ingestion	:	Do not induce vomiting without medical advice. When symptoms persist, or in all cases of doubt, seek medical advice.
Eyes	:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	:	Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
		5. FIRE-FIGHTING MEASURES
Flash point	:	Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	: : :	Not applicable Not applicable Not relevant Carbon dioxide blanket, Water spray, dry powder, foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. None
	6. A	CCIDENTAL RELEASE MEASURES
Personal precautions	:	Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	:	Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	:	Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
		7. HANDLING AND STORAGE
Handling	:	Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption



MATERIAL SAFETY DATA SHEET

10037907 YELLOW W/UV

Version Number 1.0 Revision Date 09/21/2002 Page 3 of 7 Print Date 11/6/2011

STID					
JUR	8. EXPOSURE CONTROLS / PERSONAL PROTECTION				
:	No personal respiratory protective equipment normally required.				
:	Safety glasses with side-shields.				
:	Protective gloves.				
:	Long sleeved clothing.				
:	Safety shoes.				
:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.				
:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.				
	:::::::::::::::::::::::::::::::::::::::				

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Chrome yellow (Lead	0.01	Time Weighted Average	as Cr(VI)	ACGIH
chromate pigment)	mg/m3	(TWA):		
Chrome yellow (Lead	1 mg/m3	PEL:	as Cr	OSHA Z1
chromate pigment)				
Chrome yellow (Lead	0.05	Time Weighted Average	as Pb	ACGIH
chromate pigment)	mg/m3	(TWA):		
Chrome yellow (Lead	0.05	Time Weighted Average	as Pb	OSHA
chromate pigment)	mg/m3	(TWA):		
	0.03	OSHA Action level:	as Pb	OSHA
	mg/m3			
	0.1 mg/m3	Ceiling Limit Value:	as chromate	OSHA Z2
	0.01	Time Weighted Average	as Cr(VI)	ACGIH
	mg/m3	(TWA):		
Chrome yellow (Lead	0.05	Time Weighted Average	as Pb	ACGIH
chromate pigment)	mg/m3	(TWA):		
Titanium dioxide	10 mg/m3	Time Weighted Average	Dust.	ACGIH
	_	(TWA):		
Titanium dioxide	15 mg/m3	PEL:	Total dust.	OSHA Z1

9. PHYSICAL AND CHEMICAL PROPERTIES

Form Appearance Color Odor SolidPelletsYELLOWVery faint

Evaporation rate Specific Gravity Bulk density Vapor pressure

Not applicable.Not determinedNot establishedNot applicable



MATERIAL SAFETY DATA SHEET

10037907 YELLOW W/UV

Version Number 1.0 Revision Date 09/21/2002		Page 4 of 7 Print Date 11/6/2011
Melting point/range Boiling Point: Water solubility	 Not determined Vapor density Not applicable pH Insoluble 	Not applicableNot applicable
	10. STABILITY AND REACTIVITY	
Stability	: Stable.	
Hazardous Polymerization	: Will not occur.	
Conditions to avoid	: Keep away from oxidizing agents and open a decomposition, do not overheat.	flame. To avoid thermal
Incompatible Materials	: Incompatible with strong acids and oxidizing	g agents.
Hazardous decomposition products	: Carbon dioxide (CO2), carbon monoxide (C (NOx), other hazardous materials, and smok	

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.
1344-37-2	Chrome yellow (Lead chromate pigment)	Systemic effects	central nervous system, reproductive system.

Carcinogenicity:

This product contains the following components which in their pure form have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
1344-37-2	Chrome yellow (Lead	no	1	1
	chromate pigment)			

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

Additional Health Hazard Information:



MATERIAL SAFETY DATA SHEET

10037907 YELLOW W/UV

Version Number 1.0 Revision Date 09/21/2002 Page 5 of 7 Print Date 11/6/2011

Chrome yellow (Lead chromate pigment) 1344-37-2 Systemic effects include neurotoxic, teratogenic, fetotoxic and reproductive with abdominal pain, anemia, pallor, decreased hand grip strength with characteristic "wrist drop".

Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the matri of the polymer.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the matri of the polymer.
Additional advice	: No data available.
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastics the product can be recycled. Where possible, recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Refer to specific regulation.
ICAO/IATA	: Refer to specific regulation.
IMO / IMDG	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on the TSCA inventory or ar exempt.
US. EPA CERCLA Hazardous	Substances (40 CFR 302)
Not applicable	



MATERIAL SAFETY DATA SHEET

10037907 YELLOW W/UV

Version Number 1.0 Revision Date 09/21/2002 Page 6 of 7 Print Date 11/6/2011

California Proposition : WARNING! This product contains a chemical known in the State of 65 California to cause cancer., WARNING! This product contains a chemical known in the State of California to cause birth defects or other reproductive harm.

SARA Title III Section 313 Toxic Chemicals:

Chemical Name	CAS-No.	Weight %
CHROMIUM VI COMPOUNDS	1344-37-2	16.29
LEAD COMPOUNDS, INORGANIC		
CHROMIUM VI COMPOUNDS	12656-85-8	00.04
LEAD COMPOUNDS, INORGANIC		

Canadian Regulations:

WHMIS Classification : D2A

WHMIS Ingredient Disclosure List

[CAS-No.
	1344-37-2

DSL

: Listed.

National Inventories:

- Australia AICS: Listed.China IECS: Listed.
 - _____
- Europe EINECS : Not determined.
- Japan ENCS : Not determined.
- Korea KECI : Not determined.
- Philippines PICCS : Not determined.

16. OTHER INFORMATION



MATERIAL SAFETY DATA SHEET

10037907 YELLOW W/UV

Version Number 1.0 Revision Date 09/21/2002 Page 7 of 7 Print Date 11/6/2011

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.