

MATERIAL SAFETY DATA SHEET

ORANGE

Version Number 1.0 Revision Date 10/04/2002 Page 1 of 6 Print Date 11/6/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	ORANGE
Product code	:	CC10023884
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Titanium dioxide	13463-67-7	5 - 10

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.



MATERIAL SAFETY DATA SHEET

ORANGE

sion Date 10/04/2002	Print Date 11/6/2
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist, or in all cases or doubt, seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist, or in all cases of doubt, seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seel medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
r nuon ponne	
Flammable Limits	
Upper explosion limit	: Not applicable
Lower explosion limit	: Not applicable
Autoignition temperature	: Not relevant
Suitable extinguishing media	: Carbon dioxide blanket, Water spray, dry powder, foam.
Special Fire Fighting	: Fullface self-contained breathing apparatus (SCBA) used in positive
Procedures	pressure mode should be worn to prevent inhalation of airborne
Tiocodulos	contaminants.
Unusual Fire/Explosion Hazards	: None
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	: Keep containers dry and tightly closed to avoid moisture absorption





ORANGE

					Print D	0ate 11/6/
	a	nd contamination. K	eep in a d	ry, cool place.		
8. E	XPOSURE	CONTROLS / PER	SONAL	PROTECTION		
Respiratory protection	: N	lo personal respirator	y protecti	ve equipment norm	nally re	equired.
Eye/Face Protection	: S	afety glasses with sic	le-shields			
Hand protection	: Protective gloves.					
Skin and body protection	: Long sleeved clothing.					
Additional Protective Measures	: S	: Safety shoes.				
General Hygiene Considerations		landle in accordance Vash hands before br				fety practic
Engineering measures	: Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.					
Exposure limit(s)						
Components	Value	Exposure tin	ne	Exposure typ	e	List:
Titanium dioxide	10 mg/m3	Time Weighted A (TWA):	verage	Dust.		ACGIH
Titanium dioxide	15 mg/m3	PEL:		Total dust.		OSHA Z
	9. PHYSIC	CAL AND CHEMI	CAL PRO	PERTIES		
Form	: Solid	1	Evanor	ration rate :	Not a	applicable.
Appearance	: Pelle			c Gravity :		letermined
Color		NGE	Bulk d			established
Odor	: Very					pplicable
Melting point/range		determined		density :		applicable
Boiling Point:		applicable	pН	:		applicable
Water solubility	: Insol		P		11001	
	10. 8	STABILITY AND R	EACTIV	ITY		
Stability		STABILITY AND R table.	EACTIV	TTY		
Stability Hazardous Polymerization	: S		EACTIV	TTY		
-	: S n : W : K	table.	zing agen	ts and open flame.	To av	oid therma



MATERIAL SAFETY DATA SHEET

ORANGE

Version Number 1.0 Revision Date 10/04/2002 Page 4 of 6 Print Date 11/6/2011

Hazardous decomposition products

: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ			
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.			
	12. ECOLOGIO	CAL INFORMATION	I			
Persistence and degrad	ability : Not readily b	iodegradable.				
Environmental Toxicit		: Chemicals are not readily available as they are bound within the matrix of the polymer.				
Bioaccumulation Poten		: Chemicals are not readily available as they are bound within the matrix of the polymer.				
Additional advice	: No data avail	able.				
	13. DISPOSAL	CONSIDERATIONS	5			
Product Contaminated packagir	possible, recy generator of v classification applicable fee ng : Recycling is p has the respon	cling is preferred to dis waste material has the r , transportation and dis deral, state/provincial a preferred when possible nsibility for proper was in accordance with app	ct can be recycled. Where sposal or incineration. The esponsibility for proper waste posal in accordance with nd local regulations. e. The generator of waste materia te classification, transportation licable federal, state/provincial			
		RT INFORMATION				
	14. IKAN51 0	KI INFORMATION				
U.S. DOT Classificatio	n : Refer to spec	ific regulation.				
ICAO/IATA	: Refer to spec	ific regulation.				
IMO / IMDG	: Refer to spec	ific regulation.				
	15. REGULATO	ORY INFORMATION	Ň			

MATERIAL SAFETY DATA SHEET



ORANGE	
Version Number 1.0 Revision Date 10/04/2002	Page 5 of 6 Print Date 11/6/2011
US Regulations:	
OSHA Status :	Classified as hazardous based on components.
TSCA Status :	All components of this product are listed on the TSCA inventory or are exempt.
US. EPA CERCLA Hazardous Sub	stances (40 CFR 302)
Not applicable	
California Proposition : 65	This product does not contain a substance listed by California Prop 65.
Canadian Regulations:	
WHMIS Classification :	D2B
WHMIS Ingredient Disclosu	ire List
CAS-No. 150-13-0	
DSL :	Listed.
National Inventories:	
Australia AICS :	Listed.
China IECS :	Listed.
Europe EINECS :	Not determined.
Japan ENCS :	Listed.
Korea KECI :	Listed.
Philippines PICCS :	Listed.
	16. OTHER INFORMATION

MATERIAL SAFETY DATA SHEET



ORANGE

Version Number 1.0 Revision Date 10/04/2002 Page 6 of 6 Print Date 11/6/2011

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.