

## MATERIAL SAFETY DATA SHEET WOOD EFFECT 4645C

Version Number 1.2 Revision Date 02/04/2004

Page 1 of 6 Print Date 11/13/2011

### 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	WOOD EFFECT 4645C
Product code	:	CC10024795
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

#### 2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight %
Iron oxide	1309-37-1	1 - 5
Titanium dioxide	13463-67-7	10 - 30

### 3. HAZARDS IDENTIFICATION

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

#### POTENTIAL HEALTH EFFECTS

<b>Routes of Exposure:</b>	: Inhalation, Ingestion, Skin contact		
Acute exposure			
Inhalation Ingestion Eyes	<ul> <li>Resin particles, like other inert materials, can be mechanically irritating.</li> <li>May be harmful if swallowed.</li> <li>Resin particles, like other inert materials, are mechanically irritating to eves.</li> </ul>		
Skin	: Experience shows no unusual dermatitis hazard from routine handling.		
Chronic exposure	: Refer to Section 11 for Toxicological Information.		



## MATERIAL SAFETY DATA SHEET WOOD EFFECT 4645C

Version Number 1.2 Revision Date 02/04/2004 Page 2 of 6 Print Date 11/13/2011

Aggravated by Exposure:	
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seel medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature	<ul> <li>Not applicable</li> <li>Not applicable</li> <li>Not applicable</li> </ul>
Suitable extinguishing media	: Carbon dioxide blanket, water spray, dry powder, foamnone.
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	<ul> <li>Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.</li> </ul>
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 12 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge Heat only in areas with appropriate exhaust ventilation.



# MATERIAL SAFETY DATA SHEET WOOD EFFECT 4645C

Version Number 1.2 Revision Date 02/04/2004 Page 3 of 6 Print Date 11/13/2011

Storage : Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place. 8. EXPOSURE CONTROLS / PERSONAL PROTECTION Respiratory protection : No personal respiratory protective equipment normally required. Eye/Face Protection Safety glasses with side-shields. : Hand protection Protective gloves. : Skin and body protection : Long sleeved clothing. Additional Protective Safety shoes. : Measures Handle in accordance with good industrial hygiene and safety practice. General Hygiene : Considerations Wash hands before breaks and at the end of workday. Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery. Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Iron oxide	5 mg/m3	Time Weighted Average	Dust and fume. as Fe	ACGIH
		(TWA):		
Titanium dioxide	10 mg/m3	Time Weighted Average		ACGIH
		(TWA):		
	15 mg/m3	PEL:	Total dust.	OSHA Z1

9. PHYSICAL AND CHEMICAL PROPERTIES	
	1

Form	: Solid	Evaporation rate	: Not applicable
Appearance	: Pellets	Specific Gravity:	: Not determined
Color	: BROWN	Bulk density	: Not established
Odor	: Very faint	Vapor pressure	: Not applicable
Melting point/range	: Not determined	Vapour density	: Not applicable
Boiling Point:	: Not applicable	pH	: Not applicable
Water solubility	: Insoluble		
	10. STABILITY AN	DREACTIVITY	
		DREACTIVITI	
Stability	: Stable.		
Stability Hazardous Polymerization			
·	: Stable. : Will not occur.	exidizing agents and open fl	ame. To avoid thermal





# MATERIAL SAFETY DATA SHEET WOOD EFFECT 4645C

Version Number 1.2 Revision Date 02/04/2004 Page 4 of 6 Print Date 11/13/2011

		decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

### 11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

**Toxicity Overview** 

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1309-37-1	Iron oxide	Systemic effects	Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

	12. ECOLOGICAL INFORMATION
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the matrix of the polymer.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the matrix of the polymer.
Additional advice	: No data available
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification ICAO/IATA (air)	<ul><li>Not regulated for transportation.</li><li>Refer to specific regulation.</li></ul>

PolyOne.

## MATERIAL SAFETY DATA SHEET WOOD EFFECT 4645C

Version Number 1.2 Revision Date 02/04/2004 Page 5 of 6 Print Date 11/13/2011

	15. REGULATOR	Y INFORMATION	
US Regulations:			
OSHA Status	: Classified as haz	ardous based on compon	ents.
TSCA Status	: All components Inventory.	of this product are listed	on or exempt from the TSCA
US. EPA CERCLA Hazard	ous Substances (40 CFR 3	302)	
Not applicable			
California Propositio 65	on : This product doe	es not contain a substance	listed by California Prop 65
SARA Title III Section 302	Extremely Hazardous Sul	bstance	
Not applicable			
SARA Title III Section 313	Toxic Chemicals:		
	Toxic Chemicals:	CAS-No.	Weight %
SARA Title III Section 313 Chemical Name ZINC COMPOUNI		CAS-No. 68187-51-9	Weight % 12.14
Chemical Name			
Chemical Name ZINC COMPOUNI Canadian Regulations:	DS		
Chemical Name ZINC COMPOUNI Canadian Regulations:			
Chemical Name ZINC COMPOUNI Canadian Regulations:	DS elease Inventory (NPRI)		
Chemical Name ZINC COMPOUNI Canadian Regulations: National Pollutant R	DS elease Inventory (NPRI) ion : D2B		
Chemical Name ZINC COMPOUNI Canadian Regulations: National Pollutant R WHMIS Classificati	DS elease Inventory (NPRI) ion : D2B		
Chemical Name ZINC COMPOUNI Canadian Regulations: National Pollutant R WHMIS Classificati WHMIS Ingredient I CAS-No.	DS elease Inventory (NPRI) ion : D2B Disclosure List . All components		12.14
Chemical Name ZINC COMPOUNI Canadian Regulations: National Pollutant R WHMIS Classificati WHMIS Ingredient I CAS-No. 1309-37-1	DS elease Inventory (NPRI) ion : D2B Disclosure List . All components	68187-51-9 of this product are on the	12.14



# MATERIAL SAFETY DATA SHEET WOOD EFFECT 4645C

Version Number 1.2 Revision Date 02/04/2004 Page 6 of 6 Print Date *11/13/2011* 

:	Listed
:	Listed
:	Not determined
:	Listed
:	Listed
	:

#### **16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.