

MATERIAL SAFETY DATA SHEET

TRANSPARENT

Version Number 1.0 Revision Date 10/29/2002 Page 1 of 6 Print Date 11/6/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	TRANSPARENT
Product code	:	CC10024987
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Barium sulfate	7727-43-7	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.



MATERIAL SAFETY DATA SHEET

TRANSPARENT

ion Number 1.0 sion Date 10/29/2002	Page 2 Print Date 11/6/
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for a least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	 Not applicable Not applicable Not relevant Carbon dioxide blanket, Water spray, dry powder, foam.
Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. None
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 1 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	: Keep containers dry and tightly closed to avoid moisture absorption



MATERIAL SAFETY DATA SHEET

TRANSPARENT

ision Date 10/29/2002				Print I	Page 3 Date 11/6/2
	aı	nd contamination. Keep	in a dry, cool place.		
8. EX	KPOSURE	CONTROLS / PERSO	NAL PROTECTIO	N	
Respiratory protection	: N	o personal respiratory pr	otective equipment r	normally r	equired.
Eye/Face Protection	: Sa	afety glasses with side-sh	nields.		
Hand protection	: P	rotective gloves.			
Skin and body protection	: L	ong sleeved clothing.			
Additional Protective Measures	: Sa	afety shoes.			
General Hygiene Considerations		andle in accordance with ash hands before breaks			afety practice
Engineering measures	: Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.				
Exposure limit(s)					
Components	Value	Exposure time	Exposure	type	List:
*	10 mg/m3	Time Weighted Avera (TWA):			ACGIH
Barium sulfate	5 mg/m3	PEL:	Respirable f	raction.	OSHA Z1
	15 mg/m3	PEL:	Total du	ıst.	OSHA Z1
	0 DUVSI	AL AND CHEMICAL	PROPERTIES		
	9. FHISK	AL AND CHENICAL			
			vaporation rate	· Not	applicable
Form	: Solid	l E	vaporation rate		applicable.
Form Appearance	: Solid : Pelle	l E ts S	pecific Gravity	: Not	determined
Form Appearance Color	: Solid : Pelle : NO F	I E ts S PIGMENT B	pecific Gravity sulk density	: Not : Not	determined established
Form Appearance Color Odor	: Solid : Pelle : NO F : Very	I E ts S PIGMENT B faint V	pecific Gravity sulk density apor pressure	: Not : Not : Not	determined established applicable
Form Appearance Color Odor Melting point/range	: Solid : Pelle : NO I : Very : Not c	l E ts S PIGMENT B faint V determined V	pecific Gravity Sulk density Vapor pressure Vapor density	: Not : Not : Not : Not	determined established applicable applicable
Form Appearance Color Odor	: Solid : Pelle : NO I : Very : Not c	l E ts S PIGMENT B faint V determined V applicable p	pecific Gravity sulk density apor pressure	: Not : Not : Not : Not	determined established applicable
Form Appearance Color Odor Melting point/range Boiling Point:	: Solid : Pelle : NO I : Very : Not c : Not a : Insol	l E ts S PIGMENT B faint V determined V applicable p	pecific Gravity Sulk density Yapor pressure Yapor density H	: Not : Not : Not : Not	determined established applicable applicable
Form Appearance Color Odor Melting point/range Boiling Point:	: Solid : Pelle : NO F : Very : Not c : Not a : Insol 10. S	I E ts S PIGMENT B faint V determined V applicable p uble	pecific Gravity Sulk density Yapor pressure Yapor density H	: Not : Not : Not : Not	determined established applicable applicable
Form Appearance Color Odor Melting point/range Boiling Point: Water solubility	: Solid : Pelle : NO F : Very : Not c : Not z : Insol 10. S : St	I E ts S PIGMENT B faint V determined V applicable p uble STABILITY AND REA	pecific Gravity Sulk density Yapor pressure Yapor density H	: Not : Not : Not : Not	determined established applicable applicable
Form Appearance Color Odor Melting point/range Boiling Point: Water solubility Stability	: Solid : Pelle : NO F : Very : Not c : Not a : Insol 10. S : St : W : W	I E ts S PIGMENT B faint V letermined V applicable p uble STABILITY AND REA table.	pecific Gravity bulk density apor pressure apor density H CTIVITY	: Not : Not : Not : Not	determined established applicable applicable applicable



MATERIAL SAFETY DATA SHEET

TRANSPARENT

Version Number 1.0 Revision Date 10/29/2002 Page 4 of 6 Print Date 11/6/2011

Hazardous decomposition products

: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
7727-43-7	Barium sulfate	Irritant	Respiratory system.
		Systemic effects	Eyes, Respiratory system.

12. ECOLOGICAL INFORMATION

Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the matrix of the polymer.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the matrix of the polymer.
Additional advice	: No data available.
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastics the product can be recycled. Where possible, recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Refer to specific regulation.
ICAO/IATA	: Refer to specific regulation.
IMO / IMDG	: Refer to specific regulation.



MATERIAL SAFETY DATA SHEET

TRANSPARENT

Version Number 1.0 Page 5 of 6 Print Date 11/6/2011 Revision Date 10/29/2002 **15. REGULATORY INFORMATION** US Regulations: **OSHA Status** Classified as hazardous based on components. : **TSCA Status** All components of this product are listed on the TSCA inventory or are : exempt. US. EPA CERCLA Hazardous Substances (40 CFR 302) Not applicable California Proposition : This product does not contain a substance listed by California Prop 65. 65 Canadian Regulations: WHMIS Classification : Not controlled. DSL Listed. : National Inventories: Australia AICS Not determined. • China IECS Not determined. : **Europe EINECS** Not determined. : Japan ENCS Not determined. : Korea KECI Not determined. • Philippines PICCS Not determined. :

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

MATERIAL SAFETY DATA SHEET

TRANSPARENT

Version Number 1.0 Revision Date 10/29/2002



Page 6 of 6 Print Date 11/6/2011