

MATERIAL SAFETY DATA SHEET

DARK NISSON

Version Number 1.0 Revision Date 11/06/2002 Page 1 of 7 Print Date 11/6/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	DARK NISSON
Product code	:	CC10025862
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
C.I. Pigment Green 50	68186-85-6	1 - 5
C.I. Pigment Yellow 53	8007-18-9	1 - 5
Carbon black	1333-86-4	1 - 5
Titanium dioxide	13463-67-7	1 - 5

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to eves.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.

MATERIAL SAFETY DATA SHEET





sion Number 1.0 ision Date 11/06/2002	Page 2 Print Date 11/6/2
Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases or doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 Not applicable Not applicable Not relevant Carbon dioxide blanket, Water spray, dry powder, foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. None
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 1 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat

MATERIAL SAFETY DATA SHEET



DARK NISSON Page 3 of 7 Version Number 1.0 Revision Date 11/06/2002 Print Date 11/6/2011 only in areas with appropriate exhaust ventilation. : Keep containers dry and tightly closed to avoid moisture absorption Storage and contamination. Keep in a dry, cool place. 8. EXPOSURE CONTROLS / PERSONAL PROTECTION : No personal respiratory protective equipment normally required. Respiratory protection Eye/Face Protection Safety glasses with side-shields. : Hand protection Protective gloves. : Skin and body protection Long sleeved clothing. : Additional Protective Safety shoes. : Measures General Hygiene Handle in accordance with good industrial hygiene and safety practice. : Considerations Wash hands before breaks and at the end of workday. Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
C.I. Pigment Green 50	0.02	Time Weighted Average	as Co	ACGIH
	mg/m3	(TWA):		
C.I. Pigment Yellow 53	1 mg/m3	PEL:	as Ni	OSHA Z1
C.I. Pigment Yellow 53	0.5 mg/m3	PEL:	as Sb	OSHA Z1
C.I. Pigment Yellow 53	0.2 mg/m3	Time Weighted Average (TWA):	as Ni	ACGIH
C.I. Pigment Yellow 53	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	ACGIH
Carbon black	3.5 mg/m3	Time Weighted Average (TWA):	Total dust. as carbon black	ACGIH
Carbon black	3.5 mg/m3	PEL:	Total dust. as carbon black	OSHA Z1
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):	Dust.	ACGIH
Titanium dioxide	15 mg/m3	PEL:	Total dust.	OSHA Z1

9. PHYSICAL AND CHEMICAL PROPERTIES

Form Appearance : Solid : Pellets Evaporation rate Specific Gravity Not applicable.Not determined

MATERIAL SAFETY DATA SHEET

DARK NISSON

Pol	yOne.
•	

		Page 4 of 7 Print Date <i>11/6/2011</i>
: GREY : Very faint : Not determined : Not applicable	Bulk density Vapor pressure Vapor density pH	
	D REACTIVITY	
10. STADILITT AN	DREACTIVITI	
: Stable.		
: Will not occur.		
		flame. To avoid thermal
: Incompatible with	strong acids and oxidizing	g agents.
	 Very faint Not determined Not applicable Insoluble 10. STABILITY AN Stable. Will not occur. Keep away from of decomposition, do Incompatible with Carbon dioxide (O) 	 Very faint Vapor pressure Not determined Vapor density Not applicable pH Insoluble 10. STABILITY AND REACTIVITY Stable. Will not occur. Keep away from oxidizing agents and open decomposition, do not overheat. Incompatible with strong acids and oxidizing

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
68186-85-6	C.I. Pigment Green 50	Irritant	Eyes, Skin.
8007-18-9	C.I. Pigment Yellow 53	Irritant	Eyes, Skin.
		sensitizer	Skin.
1333-86-4	Carbon black	Systemic effects	Eyes, Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

LC50 / LD50

This product contains the following components which in their pure form have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
1333-86-4	Carbon black	Oral LD50	>15,400 mg/kg	rat
		Dermal LD50	> 3 gm/kg	rabbit

Carcinogenicity:

This product contains the following components which in their pure form have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
68186-85-6	C.I. Pigment Green 50	no	2B	no
8007-18-9	C.I. Pigment Yellow 53	no	1	2
1333-86-4	Carbon black	no	2B	no



DARK NISSON

Version Number 1.0 Revision Date 11/06/2002 Page 5 of 7 Print Date 11/6/2011

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

Additional Health Hazard Information:

C.I. Pigment Yellow 53 8007-18-9 Skin sensitizer "nickel itch", with pulmonary, brain, liver, kidney andmuscle effects.

Additional Health Hazard Information:

Carbon black 1333-86-4 Carcinogenicity: Many inhalation toxicologists believe that the tumor response observed in the referenced rat studies is species specific and does not correlate to human exposure. However, the IARC evaluation in Monograph Volume 65, issued in April 1996 concluded that, "There is sufficient evidence in experimental animals for the carcinogenicity of carbon black". Based on this evaluation, along with their evaluation of inadequate evidence of carcinogenicity in humans, IARC's overall evaluation is that "Carbon Black is possibly carcinogenic to humans (Group 2B). Carbon Black has not been listed as a carcinogen by the National Toxicology Program (NTP) or the Occupational Safety and Health Administration (OSHA). The National Institute of Occupational Safety and Health (NIOSH) criteria document on carbon black recommends that only carbon black with PAH (polynuclear aromatic hydrocarbon) levels greater than 0.1% be considered suspect carcinogens.

Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the matrix of the polymer.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the matrix of the polymer.
Additional advice	: No data available.
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastics the product can be recycled. Where possible, recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.

PolyOne.



MATERIAL SAFETY DATA SHEET

DARK NISSON

Version Number 1.0 Revision Date 11/06/2002 Page 6 of 7 Print Date 11/6/2011

	14. TRANSPO	RT INFORMATION	I	
U.S. DOT Classification	: Refer to speci	fic regulation.		
ІСАОЛАТА	_	fic regulation.		
	-	-		
IMO / IMDG	: Refer to speci	fic regulation.		
	15. REGULATO	ORY INFORMATIO	N	
US Regulations:				
OSHA Status	: Classified as l	hazardous based on co	omponents.	
TSCA Status	: All component exempt.	nts of this product are l	isted on the TSCA inve	ntory or are
US. EPA CERCLA Hazardou	s Substances (40 CFI	R 302)		
Not applicable				
California Proposition			a chemical known to the	he State of
California Proposition 65 SARA Title III Section 313 T	California to o		a chemical known to t	ne State of
65	California to o oxic Chemicals:			he State of
65 SARA Title III Section 313 T Chemical Nam COBALT COM	California to o oxic Chemicals: ne MPOUNDS	cause cancer. CAS-No. 68186-85-6	a chemical known to the weight %	ne State of
65 SARA Title III Section 313 T Chemical Nam COBALT COM NICKEL COM	California to o oxic Chemicals: ne MPOUNDS	cause cancer.	Weight %	ne State of
65 SARA Title III Section 313 T Chemical Nam COBALT COM NICKEL COM ANTIMONY C	California to o oxic Chemicals: te MPOUNDS IPOUNDS	cause cancer. CAS-No. 68186-85-6	Weight % 03.67	ne State of
65 SARA Title III Section 313 T Chemical Nam COBALT COM NICKEL COM	California to o oxic Chemicals: te MPOUNDS IPOUNDS	cause cancer. CAS-No. 68186-85-6	Weight % 03.67	he State of
65 SARA Title III Section 313 T Chemical Nam COBALT COM NICKEL COM ANTIMONY C	California to o oxic Chemicals: ne MPOUNDS IPOUNDS COMPOUNDS	cause cancer. CAS-No. 68186-85-6	Weight % 03.67	he State of
65 SARA Title III Section 313 T Chemical Nam COBALT COM NICKEL COM ANTIMONY O Canadian Regulations:	California to o oxic Chemicals: ne MPOUNDS IPOUNDS COMPOUNDS n : D2A	cause cancer. CAS-No. 68186-85-6	Weight % 03.67	he State of
65 SARA Title III Section 313 T Chemical Nam COBALT COM NICKEL COM ANTIMONY O Canadian Regulations: WHMIS Classification	California to o oxic Chemicals: ne MPOUNDS IPOUNDS COMPOUNDS n : D2A	cause cancer. CAS-No. 68186-85-6	Weight % 03.67	he State of

MATERIAL SAFETY DATA SHEET

DARK NISSON

Version Number 1.0 Revision Date 11/06/2002 Page 7 of 7 Print Date 11/6/2011

National Inventories:

Australia AICS	:	Listed.
China IECS	:	Listed.
Europe EINECS	:	Not determined.
Japan ENCS	:	Not determined.
Korea KECI	:	Listed.
Philippines PICCS	:	Listed.

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

