PolvOne

MATERIAL SAFETY DATA SHEET **PG 26495 BU PP AS**

Version Number 1.2 Revision Date 11/16/2007

Page 1 of 7 Print Date 12/2/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

| Telephone:Emergency telephone: | Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident). |
|--------------------------------|---|
| Product name : | PG 26495 BU PP AS |
| Product code : | CC10026495 |
| Chemical Name : | Mixture |
| CAS-No. : | Mixture |
| Product Use : | Industrial Applications |

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

| Components | CAS-No. | Weight % |
|---|-------------|----------|
| Lauric acid diethanolamide condensate | 120-40-1 | 1 - 5 |
| Glyceryl monostearate | 31566-31-1 | 1 - 5 |
| Silica, amorphous | 7631-86-9 | 1 - 5 |
| Silica, amorphous, precipitated and gel | 112926-00-8 | 1 - 5 |
| Titanium dioxide | 13463-67-7 | 10 - 30 |

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

| : Inhalation, Ingestion, Skin contact |
|---|
| |
| : Resin particles, like other inert materials, can be mechanically irritating. |
| : May be harmful if swallowed. |
| : Resin particles, like other inert materials, are mechanically irritating to eyes. |
| : Experience shows no unusual dermatitis hazard from routine handling. |
| |

PolyOne.

MATERIAL SAFETY DATA SHEET **PG 26495 BU PP AS**

Version Number 1.2 Revision Date 11/16/2007 Page 2 of 7 Print Date 12/2/2011

| Medical Conditions | : None known. |
|-------------------------------------|---|
| Aggravated by Exposure: | |
| | 4. FIRST AID MEASURES |
| Inhalation | : Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice. |
| Ingestion | : Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice. |
| Eyes | : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention. |
| Skin | : Wash off with soap and plenty of water. If skin irritation persists seek medical attention. |
| | 5. FIRE-FIGHTING MEASURES |
| Flash point | : Not applicable |
| Flammable Limits | |
| Upper explosion limit | : Not applicable |
| Lower explosion limit | : Not applicable |
| Autoignition temperature | : Not applicable |
| Suitable extinguishing media | : Carbon dioxide blanket, Water spray, Dry powder, Foam. |
| Special Fire Fighting Procedures | : Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne |
| | contaminants. |
| Unusual Fire/Explosion Hazards | : Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. |
| | 6. ACCIDENTAL RELEASE MEASURES |
| Personal precautions | : Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls. |
| Environmental precautions | : Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil. |
| Methods for cleaning up | : Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods. |
| | 7. HANDLING AND STORAGE |

PolyOne.

MATERIAL SAFETY DATA SHEET **PG 26495 BU PP AS**

| Version Number 1.2 Revision Date 11/16/2007 | | Page 3 of 7 Print Date 12/2/2011 |
|--|-------|---|
| Handling | : | Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation. |
| Storage | : | Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place. |
| 8. EXI | POSUE | RE CONTROLS / PERSONAL PROTECTION |
| Respiratory protection | : | No personal respiratory protective equipment normally required. |
| Eye/Face Protection | : | Safety glasses with side-shields |
| Hand protection | : | Protective gloves |
| Skin and body protection | : | Long sleeved clothing |
| Additional Protective Measures | : | Safety shoes |
| General Hygiene Considerations | : | Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. |
| Engineering measures | : | Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery. |

Exposure limit(s)


| Components | Value | Exposure time | Exposure type | List: |
|---|-----------|-----------------------------------|------------------------|---------|
| Glyceryl monostearate | 10 mg/m3 | Time Weighted Average (TWA): | | ACGIH |
| Silica, amorphous | 0.8 mg/m3 | Time Weighted Average (TWA): | | Z3 |
| | 10 mg/m3 | Time Weighted Average (TWA): | Inhalable particulate. | MX OEL |
| | 3 mg/m3 | Time Weighted Average (TWA): | Respirable dust. | MX OEL |
| Silica, amorphous, precipitated and gel | 10 mg/m3 | Time Weighted Average (TWA): | | MX OEL |
| | 0.8 mg/m3 | Time Weighted Average (TWA): | | Z3 |
| Titanium dioxide | 10 mg/m3 | Time Weighted Average (TWA): | | ACGIH |
| | 15 mg/m3 | PEL: | Total dust. | OSHA Z1 |
| | 10 mg/m3 | Time Weighted Average (TWA): | as Ti | MX OEL |
| | 20 mg/m3 | Short Term Exposure Limit (STEL): | as Ti | MX OEL |

9. PHYSICAL AND CHEMICAL PROPERTIES

PolyOne

MATERIAL SAFETY DATA SHEET **PG 26495 BU PP AS**

Version Number 1.2 Revision Date 11/16/2007



| Stability | : | Stable. |
|----------------------------------|---|--|
| Hazardous Polymerization | : | Will not occur. |
| Conditions to avoid | : | Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat. |
| Incompatible Materials | : | Incompatible with strong acids and oxidizing agents. |
| Hazardous decomposition products | : | Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. |

10. STABILITY AND REACTIVITY

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

| CAS-No. | Chemical Name | Effect | Target Organ |
|-------------|----------------------------|------------------|---------------------------|
| 120-40-1 | Lauric acid diethanolamide | Irritant | Eyes, Skin. |
| | condensate | | |
| 7631-86-9 | Silica, amorphous | Irritant | Eyes, Respiratory system. |
| 112926-00-8 | Silica, amorphous, | Irritant | Respiratory system, Eyes. |
| | precipitated and gel | | |
| 13463-67-7 | Titanium dioxide | Systemic effects | Respiratory system. |

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

| CAS-No. | Chemical Name | Route | Value | Species |
|-----------|----------------------------|-----------|-------------|----------|
| 120-40-1 | Lauric acid diethanolamide | Oral LD50 | 2,700 mg/kg | rat |
| | condensate | | | |
| 7631-86-9 | Silica, amorphous | Oral | 15,000 | mouserat |
| | | LD50Oral | mg/kg22,500 | |
| | | LD50 | mg/kg | |

Carcinogenicity

PolyOne

MATERIAL SAFETY DATA SHEET **PG 26495 BU PP AS**

Version Number 1.2 Revision Date 11/16/2007 Page 5 of 7 Print Date 12/2/2011

This product contains the following components which, in their pure form, have the following carcinogenicity data:

| CAS-No. | Chemical Name | OSHA | IARC | NTP |
|------------|------------------|------|------|-----|
| 13463-67-7 | Titanium dioxide | no | 2B | no |

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

| Persistence and degradability | : Not readily biodegradable. |
|-------------------------------|---|
| reisistence and degradability | . Not readily blodegradable. |
| Environmental Toxicity | : Chemicals are not readily available as they are bound within the polymer matrix. |
| Bioaccumulation Potential | : Chemicals are not readily available as they are bound within the polymer matrix. |
| Additional advice | : No data available |
| | 13. DISPOSAL CONSIDERATIONS |
| Product | : Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. |
| Contaminated packaging | : Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. |
| | 14. TRANSPORT INFORMATION |
| U.S. DOT Classification | : Not regulated for transportation. |
| | |
| ICAO/IATA (air) | : Refer to specific regulation. |
| IMO / IMDG (maritime) | : Refer to specific regulation. |
| | 15. REGULATORY INFORMATION |

PolyOne.

MATERIAL SAFETY DATA SHEET **PG 26495 BU PP AS**

| sion Number 1.2 ision Date 11/16/2007 | Page 6 Print Date 12/2/2 |
|--|--|
| US Regulations: | |
| OSHA Status | : Classified as hazardous based on components. |
| TSCA Status | : All components of this product are listed on or exempt from the TSCA Inventory. |
| US. EPA CERCLA Hazardo | ous Substances (40 CFR 302) |
| Not applicable | |
| | |
| California Propositio 65 | on : Not applicable |
| SARA Title III Section 302 I | Extremely Hazardous Substance |
| Unless specific chemicals are | re identified under this section, this product is Not Applicable under this regula |
| | |
| SARA Title III Section 313 | Toxic Chemicals: |
| Unless specific chemicals are | re identified under this section, this product is Not Applicable under this regula |
| Canadian Regulations: | |
| National Pollutant Re | elease Inventory (NPRI) |
| Not applicable | |
| WHMIS Classification | on : D2A |
| WHMIS Ingredient D | Disclosure List |
| CAS-No. 7631-86-9 | 3 |
| 112926-00-8 | |
| DSL | : All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt. |
| | |
| DSL | |

PolyOne

MATERIAL SAFETY DATA SHEET **PG 26495 BU PP AS**

Version Number 1.2 Revision Date 11/16/2007

Page 7 of 7 Print Date 12/2/2011

Europe EINECS:ListedJapan ENCS:Not determinedKorea KECI:ListedPhilippines PICCS:Listed

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.