

MATERIAL SAFETY DATA SHEET

RED

Version Number 1.0 Revision Date 12/09/2002 Page 1 of 7 Print Date 11/7/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	RED
Product code	:	CC10026612
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Titanium dioxide	13463-67-7	1 - 5
Molybdate orange (Lead chromate pigment)	12656-85-8	30 - 60

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.



MATERIAL SAFETY DATA SHEET

RED

Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases or doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting	 Not applicable Not applicable Not relevant Carbon dioxide blanket, Water spray, dry powder, foam. Fullface self-contained breathing apparatus (SCBA) used in positive
Procedures Unusual Fire/Explosion Hazards	pressure mode should be worn to prevent inhalation of airborne contaminants.None
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 1 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.

RED

MATERIAL SAFETY DATA SHEET





Version Number 1.0 Page 3 of 7 Print Date 11/7/2011 Revision Date 12/09/2002 Storage Keep containers dry and tightly closed to avoid moisture absorption : and contamination. Keep in a dry, cool place. 8. EXPOSURE CONTROLS / PERSONAL PROTECTION Respiratory protection No personal respiratory protective equipment normally required. : Eye/Face Protection Safety glasses with side-shields. : Protective gloves. Hand protection : Skin and body protection : Long sleeved clothing. Additional Protective Safety shoes. : Measures General Hygiene Handle in accordance with good industrial hygiene and safety practice. : Considerations Wash hands before breaks and at the end of workday. Heat only in areas with appropriate exhaust ventilation. Provide Engineering measures : appropriate exhaust ventilation at machinery.

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Molybdate orange	1 mg/m3	PEL:	as Cr	OSHA Z1
(Lead chromate				
pigment)				
Molybdate orange	0.05	Time Weighted Average	as Pb	OSHA
(Lead chromate	mg/m3	(TWA):		
pigment)				
	0.10	Ceiling Limit Value:	as CrO3	OSHA Z2
	mg/m3			
Molybdate orange	0.01	Time Weighted Average	as Cr(VI)	ACGIH
(Lead chromate	mg/m3	(TWA):		
pigment)				
Molybdate orange	0.05	Time Weighted Average	as Pb	ACGIH
(Lead chromate	mg/m3	(TWA):		
pigment)				
Titanium dioxide	10 mg/m3	Time Weighted Average	Dust.	ACGIH
	_	(TWA):		
Titanium dioxide	15 mg/m3	PEL:	Total dust.	OSHA Z1

9. PHYSICAL AND CHEMICAL PROPERTIES

- Form Appearance Color
- : Solid : Pellets : RED

Evaporation rate Specific Gravity Bulk density

: Not applicable. Not determined : : Not established

MATERIAL SAFETY DATA SHEET



RED

Version Number 1.0 Revision Date 12/09/2002		Page 4 of 7 Print Date 11/7/2011
Odor Melting point/range Boiling Point: Water solubility	 Very faint Vapor pressure Not determined Vapor density Not applicable pH Insoluble 	Not applicableNot applicableNot applicable
	10. STABILITY AND REACTIVITY	
Stability	: Stable.	
Hazardous Polymerization	: Will not occur.	
Conditions to avoid	: Keep away from oxidizing agents and open f decomposition, do not overheat.	lame. To avoid thermal
Incompatible Materials	: Incompatible with strong acids and oxidizing	; agents.
Hazardous decomposition products	: Carbon dioxide (CO2), carbon monoxide (CO (NOx), other hazardous materials, and smoke	· ·
	11 TOVICOLOCICAL INFORMATION	

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.
12656-85-8	Molybdate orange (Lead chromate pigment)	Irritant	Eyes, Skin.
		Systemic effects	central nervous system, reproductive system.

Carcinogenicity:

This product contains the following components which in their pure form have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
12656-85-8	Molybdate orange (Lead	no	no	1
	chromate pigment)			

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.



MATERIAL SAFETY DATA SHEET

RED

Version Number 1.0 Revision Date 12/09/2002 Page 5 of 7 Print Date 11/7/2011

Additional Health Hazard Information:

Molybdate orange (Lead chromate pigment) 12656-85-8 Systemic effects include neurotoxic, teratogenic, fetotoxic and reproductive with abdominal pain, anemia, pallor, decreased hand grip strength with characteristic "wrist drop".

	12. ECOLOGICAL INFORMATION
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the matrix of the polymer.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the matrix of the polymer.
Additional advice	: No data available.
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastics the product can be recycled. Where possible, recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Refer to specific regulation.
ICAO/IATA	: Refer to specific regulation.
IMO / IMDG	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardous	Substances (40 CFR 302)

MATERIAL SAFETY DATA SHEET

RED

Version Number 1.0 Revision Date 12/09/2002 PolyOne.

Page 6 of 7

Print Date 11/7/2011

Not applicable	

California Proposition : 65

: WARNING! This product contains a chemical known to the State of California to cause cancer., WARNING! This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

SARA Title III Section 313 Toxic Chemicals:

Chemical Name	CAS-No.	Weight %
CHROMIUM VI COMPOUNDS	12656-85-8	45.80
LEAD COMPOUNDS, INORGANIC		

Canadian Regulations:

WHMIS Classification : D2B

WHMIS Ingredient Disclosure List

CAS-No.	
12656-85-8	

DSL

All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

Australia AICS	:	Not determined.
China IECS	:	Listed.
Europe EINECS	:	Not determined.

Japan ENCS : Not determined.

Korea KECI : Not determined.

:

Philippines PICCS : Not determined.

16. OTHER INFORMATION



MATERIAL SAFETY DATA SHEET

RED

Version Number 1.0 Revision Date 12/09/2002 Page 7 of 7 Print Date 11/7/2011

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.