

MATERIAL SAFETY DATA SHEET

TURQUOISE 312U

Version Number 1.0 Revision Date 11/20/2002 Page 1 of 6 Print Date 11/6/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	TURQUOISE 312U
Product code	:	CC10026842
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Titanium dioxide	13463-67-7	5 - 10

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	Routes of Exposure: : Inhalation, Ingestion, Skin contact	
Acute exposure		
Inhalation Ingestion Eyes Skin	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to eyes. Experience shows no unusual dermatitis hazard from routine handling. 	
Chronic exposure Medical Conditions Aggravated by Exposure:	Refer to Section 11 for Toxicological Information.None known.	



MATERIAL SAFETY DATA SHEET

TURQUOISE 312U

Version Number 1.0 Page 2 of 6 Revision Date 11/20/2002 Print Date 11/6/2011 **4. FIRST AID MEASURES** Inhalation Move to fresh air in case of accidental inhalation of fumes from ÷ overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice. Ingestion Do not induce vomiting without medical advice. When symptoms : persist or in all cases of doubt seek medical advice. Eyes Rinse immediately with plenty of water, also under the eyelids, for at : least 15 minutes. If eye irritation persists, seek medical attention. Skin Wash off with soap and plenty of water. If skin irritation persists seek : medical attention. **5. FIRE-FIGHTING MEASURES** Flash point Not applicable : Flammable Limits Upper explosion limit Not applicable : Lower explosion limit Not applicable : Autoignition temperature Not relevant : Carbon dioxide blanket, Water spray, dry powder, foam. Suitable extinguishing media : Special Fire Fighting Fullface self-contained breathing apparatus (SCBA) used in positive : Procedures pressure mode should be worn to prevent inhalation of airborne contaminants. Unusual Fire/Explosion None · Hazards 6. ACCIDENTAL RELEASE MEASURES Personal precautions : Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls. Environmental precautions Should not be released into the environment. The product should not : be allowed to enter drains, water courses or the soil. Clean up promptly by sweeping or vacuum. Package all material in Methods for cleaning up : plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods. 7. HANDLING AND STORAGE Handling Take measures to prevent the build up of electrostatic charge. Heat : only in areas with appropriate exhaust ventilation. Storage Keep containers dry and tightly closed to avoid moisture absorption ·



MATERIAL SAFETY DATA SHEET

TURQUOISE 312U

contamination. Keep in a contamination. Keep in a contamination. Keep in a contract of the sective gloves. personal respiratory protection of the sective gloves. g sleeved clothing. ty shoes. dle in accordance with good h hands before breaks and a sective glove in a contained with appropriopriate exhaust ventilation Exposure time Time Weighted Average (TWA):	PROTECTION ive equipment normally r I industrial hygiene and s at the end of workday. iate exhaust ventilation.	afety practice Provide
bersonal respiratory protects ty glasses with side-shields ective gloves. g sleeved clothing. ty shoes. dle in accordance with good h hands before breaks and a t only in areas with appropr opriate exhaust ventilation Exposure time Time Weighted Average	ive equipment normally n l industrial hygiene and s at the end of workday. iate exhaust ventilation. at machinery. Exposure type	afety practice Provide
ty glasses with side-shields ective gloves. g sleeved clothing. ty shoes. dle in accordance with good h hands before breaks and a t only in areas with appropr opriate exhaust ventilation Exposure time Time Weighted Average	I industrial hygiene and s at the end of workday. iate exhaust ventilation. at machinery. Exposure type	afety practice Provide
ective gloves. g sleeved clothing. ty shoes. dle in accordance with good h hands before breaks and a t only in areas with appropr opriate exhaust ventilation <u>Exposure time</u> Time Weighted Average	l industrial hygiene and s at the end of workday. iate exhaust ventilation. at machinery. Exposure type	Provide List:
g sleeved clothing. ty shoes. dle in accordance with good h hands before breaks and a t only in areas with appropr copriate exhaust ventilation <u>Exposure time</u> Time Weighted Average	at the end of workday. iate exhaust ventilation. at machinery. Exposure type	Provide List:
ty shoes. dle in accordance with good h hands before breaks and a t only in areas with appropr opriate exhaust ventilation <u>Exposure time</u> Time Weighted Average	at the end of workday. iate exhaust ventilation. at machinery. Exposure type	Provide List:
dle in accordance with good h hands before breaks and t only in areas with appropr opriate exhaust ventilation Exposure time Time Weighted Average	at the end of workday. iate exhaust ventilation. at machinery. Exposure type	Provide List:
h hands before breaks and a t only in areas with appropr opriate exhaust ventilation Exposure time Time Weighted Average	at the end of workday. iate exhaust ventilation. at machinery. Exposure type	Provide List:
Exposure time Time Weighted Average	at machinery. Exposure type	List:
Time Weighted Average		
Time Weighted Average		
Time Weighted Average		
UWA):		ACGIH
PEL:	Total dust.	OSHA Z1
L AND CHEMICAL PRO	PERTIES	
E	notion note . Not	
		applicable.
		established
	2	applicable
		applicable
licable pH		applicable
le		appneadle
ABILITY AND REACTIV	/ITY	
le.		
not occur.		
		woid thermal
omposition, do not overheat		
		ep away from oxidizing agents and open flame. To a composition, do not overheat.



MATERIAL SAFETY DATA SHEET

TURQUOISE 312U

Version Number 1.0 Revision Date 11/20/2002 Page 4 of 6 Print Date 11/6/2011

Hazardous decomposition products

: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

	12. ECOLOGIO	CAL INFORMATION	1			
Persistence and degrada	bility : Not readily b	iodegradable.				
Environmental Toxicity		 Chemicals are not readily available as they are bound within the matrix of the polymer. Chemicals are not readily available as they are bound within the matrix of the polymer. 				
Bioaccumulation Potent						
Additional advice	: No data avail	: No data available.				
	13. DISPOSAL	CONSIDERATIONS	9			
Product Contaminated packaging	g : Recycling is has the respo and disposal	 Like most thermoplastics the product can be recycled. Where possible, recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. 				
	14. TRANSPO	RT INFORMATION				
U.S. DOT Classificatior	n : Refer to spec	ific regulation.				
ICAO/IATA	: Refer to spec	: Refer to specific regulation.				
IMO / IMDG	: Refer to spec	ific regulation.				
	15. REGULAT	ORY INFORMATION	N			

MATERIAL SAFETY DATA SHEET





TURQUUISE 3120		
Version Number 1.0 Revision Date 11/20/2002		Page 5 of 6 Print Date 11/6/2011
US Regulations:		
OSHA Status	:	Classified as hazardous based on components.
TSCA Status	:	All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardous Su	ubs	stances (40 CFR 302)
Not applicable		
California Proposition 65	:	This product does not contain a substance listed by California Prop 65.
Canadian Regulations:		
WHMIS Classification	:	D2B
DSL	:	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.
National Inventories:		
Australia AICS	:	Listed.
China IECS	:	Listed.
Europe EINECS	:	Not determined.
Japan ENCS	:	Listed.
Korea KECI	:	Listed.
Philippines PICCS	:	Listed.
		16 OTHER INFORMATION

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

MATERIAL SAFETY DATA SHEET

TURQUOISE 312U

Version Number 1.0 Revision Date 11/20/2002



Page 6 of 6 Print Date 11/6/2011