

MATERIAL SAFETY DATA SHEET

PINK 670

Version Number 1.0 Revision Date 12/02/2002 Page 1 of 6 Print Date 11/7/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	PINK 670
Product code	:	CC10027223
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Titanium dioxide	13463-67-7	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.



MATERIAL SAFETY DATA SHEET

PINK 670

sion Date 12/02/2002	Print Date 11/7/2
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seel medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits	
Upper explosion limit	: Not applicable
Lower explosion limit	: Not applicable
Autoignition temperature	: Not relevant
Suitable extinguishing media	: Carbon dioxide blanket, Water spray, dry powder, foam.
Special Fire Fighting	: Fullface self-contained breathing apparatus (SCBA) used in positive
Procedures	pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	: None
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 12 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	: Keep containers dry and tightly closed to avoid moisture absorption

MATERIAL SAFETY DATA SHEET

PINK 670



sion Number 1.0 ision Date 12/02/2002			Print	Page 3 Date 11/7/2	
	aı	nd contamination. Keep in a c	lry, cool place.		
8. H	XPOSURE	CONTROLS / PERSONAL	PROTECTION		
Respiratory protection	: N	o personal respiratory protect	ive equipment normally r	required.	
Eye/Face Protection	: S	afety glasses with side-shields			
Hand protection	: P	rotective gloves.			
Skin and body protection	: L	ong sleeved clothing.			
Additional Protective Measures	: Safety shoes.				
General Hygiene Considerations	: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.				
Engineering measures		: Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.			
Exposure limit(s)					
Components	Value	Exposure time	Exposure type	List:	
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):	Dust.	ACGIH	
Titanium dioxide	15 mg/m3	PEL:	Total dust.	OSHA Z1	
	9. PHYSIC	CAL AND CHEMICAL PRO	OPERTIES		
Form Appearance Color Odor Melting point/range Pailing Daint	: Not a	ts Specif K Bulk c faint Vapor	ic Gravity: Notlensity: Notpressure: Notdensity: Not	applicable. determined established applicable applicable applicable	
Boiling Point: Water solubility	: Insol	uble			
			/ITY		
	10. 8	uble	VITY		
Water solubility	10. S	uble	VITY		
Water solubility Stability	<u>10.8</u> : S n : W : K	uble	nts and open flame. To a	void thermal	



MATERIAL SAFETY DATA SHEET

PINK 670

Version Number 1.0 Revision Date 12/02/2002 Page 4 of 6 Print Date 11/7/2011

Hazardous decomposition products

: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.			
	12. ECOLOGI	CAL INFORMATION	N			
Persistence and degrad		piodegradable.	`			
Environmental Toxicit		: Chemicals are not readily available as they are bound within the matrix of the polymer.				
Bioaccumulation Poten		: Chemicals are not readily available as they are bound within the matrix of the polymer.				
Additional advice	: No data avai	lable.				
	13. DISPOSAL	CONSIDERATIONS	5			
Product Contaminated packagin	possible, rec generator of classification applicable fe ng : Recycling is has the respo and disposal	 Like most thermoplastics the product can be recycled. Where possible, recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal. 				
	14. TRANSPO	ORT INFORMATION				
U.S. DOT Classificatio	on : Refer to spec	rific regulation.				
ICAO/IATA	: Refer to spec	cific regulation.				
IMO / IMDG	: Refer to spec	cific regulation.				
	15. REGULAT	ORY INFORMATION	N			

4/6

MATERIAL SAFETY DATA SHEET



PINK 670		
Version Number 1.0 Revision Date 12/02/2002		Page 5 of 6 Print Date 11/7/2011
US Regulations:		
OSHA Status	:	Classified as hazardous based on components.
TSCA Status	:	All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardous	Sub	stances (40 CFR 302)
Not applicable		
California Proposition 65	:	This product does not contain a substance listed by California Prop 65.
Canadian Regulations:		
WHMIS Classification	:	D2B
DSL	:	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.
National Inventories:		
Australia AICS	:	Listed.
China IECS	:	Listed.
Europe EINECS	:	Not determined.
Japan ENCS	:	Listed.
Korea KECI	:	Listed.
Philippines PICCS	:	Listed.
		16 OTHER INFORMATION

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

MATERIAL SAFETY DATA SHEET

PINK 670

Version Number 1.0 Revision Date 12/02/2002



Page 6 of 6 Print Date 11/7/2011