MATERIAL SAFETY DATA SHEET STAN-TONE VC-27829 FOIL GRAY 552

Version Number 1.1 Revision Date 10/18/2004

Page 1 of 6 Print Date 11/16/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

| Telephone Emergency telephone number | : | Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident). |
|--|---|---|
| Product name | : | STAN-TONE VC-27829 FOIL GRAY 552 |
| Product code | : | CC10027971 |
| Chemical Name | : | Mixture |
| CAS-No. | : | Mixture |
| Product Use | : | Industrial Applications |

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

| Components | CAS-No. | Weight % |
|------------|------------|----------|
| Mica | 12001-26-2 | 10 - 30 |

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

| Routes of Exposure: | : Inhalation, Skin contact, Ingestion |
|---|--|
| Acute exposure | |
| Inhalation Ingestion Eyes Skin | Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Particulates, like other inert materials can be mechanically irritating. Experience shows no unusual dermatitis hazard from routine handling. |
| Chronic exposure | : Refer to Section 11 for Toxicological Information. |
| Medical Conditions Aggravated by Exposure: | : None known. |
| | 4. FIRST AID MEASURES |



MATERIAL SAFETY DATA SHEET STAN-TONE VC-27829 FOIL GRAY 552

| sion Date 10/18/2004 | Print Date 11/16/2 |
|--|--|
| | |
| Inhalation | : Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases or doubt seek medical advice. |
| Ingestion | : Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice. |
| Eyes | : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention. |
| Skin | : Wash off with soap and plenty of water. If skin irritation persists see medical attention. |
| | 5. FIRE-FIGHTING MEASURES |
| Flash point | : Not applicable |
| Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media | Not applicable Not applicable Not relevant Carbon dioxide blanket, water spray, dry powder, foamnone. |
| Special Fire Fighting Procedures | Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. |
| Unusual Fire/Explosion Hazards | May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxide of nitrogen (NOx), other hazardous materials, and smoke are all possible. |
| | 6. ACCIDENTAL RELEASE MEASURES |
| Personal precautions | : Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls. |
| Environmental precautions | : Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil. |
| Methods for cleaning up | : Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 1 of this MSDS for proper disposal methods. |
| | 7. HANDLING AND STORAGE |
| Handling | : Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation. Processing fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize accumulation of |

MATERIAL SAFETY DATA SHEET STAN-TONE VC-27829 FOIL GRAY 552

Version Number 1.1 Revision Date 10/18/2004 Page 3 of 6 Print Date 11/16/2011

| | | these materials. | |
|-----------------------------------|----|--|--|
| Storage | : | Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place. | |
| 8. EXPOS | UF | RE CONTROLS / PERSONAL PROTECTION | |
| Respiratory protection | : | No personal respiratory protective equipment normally required. If dusty conditions occur wear appropriate respiratory protection. | |
| Eye/Face Protection | : | Safety glasses with side-shields. | |
| Hand protection | : | Protective gloves. | |
| Skin and body protection | : | Long sleeved clothing. | |
| Additional Protective Measures | : | Safety shoes. | |
| General Hygiene Considerations | : | Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. | |
| Engineering measures | : | Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery. | |

Exposure limit(s)

| Components | Value | Exposure time | Exposure type | List: |
|------------|----------|------------------------------|----------------------|-------|
| Mica | 20 mppcf | PEL: | Total dust. | OSHA |
| | 3 mg/m3 | Time Weighted Average (TWA): | Respirable fraction. | ACGIH |

9. PHYSICAL AND CHEMICAL PROPERTIES

| Form |
|---------------------|
| Appearance |
| Color |
| Odor |
| Melting point/range |
| Boiling Point: |
| Water solubility |

Solid powder, granular GREY Very faint Not determined Not applicable Insoluble

Evaporation rate Specific Gravity: Bulk density Vapor pressure Vapour density pH

To avoid thermal decomposition, do not overheat. Keep away from

- : Not applicable
 - Not determined

:

- : Not determined
- : Not applicable
- : Not applicable
- : Not applicable

10. STABILITY AND REACTIVITY

- Stability : Stable.
- Hazardous Polymerization : Will not occur.

:

Conditions to avoid

3/6

PolyOne

MATERIAL SAFETY DATA SHEET STAN-TONE VC-27829 FOIL GRAY 552

Version Number 1.1 Revision Date 10/18/2004 Page 4 of 6 Print Date 11/16/2011

| | | oxidizing agents and open flame. |
|----------------------------------|---|---|
| Incompatible Materials | : | Incompatible with strong acids and oxidizing agents., Avoid contact with acetal homopolymers and acetal copolymers during processing. |
| Hazardous decomposition products | : | Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating (approximately 30 minutes or more) above 392 °F (200 °C) or short term heating at 482 °F (250 °C) may result in product decomposition and evolution of carbon monoxide and hydrogen chloride. |

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

| | | 12. ECOLOGIO | CAL INFORMATION | I |
|------------------------|----------|-----------------------------------|---|---|
| Persistence and degrae | dability | : Not readily bi | odegradable. | |
| Environmental Toxici | ty | : Adverse ecolo | ogical impact is not kno | own or expected under normal us |
| Bioaccumulation Pote | ential | : No data avail | able | |
| Additional advice | | : No data avail | able | |
| | | 13. DISPOSAL | CONSIDERATIONS | |
| Product | | generator of v classification, | vaste material has the r | d to disposal or incineration. The esponsibility for proper waste posal in accordance with nd local regulations. |
| Contaminated package | ing | has the respon | nsibility for proper was n accordance with app | e. The generator of waste materi te classification, transportation licable federal, state/provincial |
| | | 14. TRANSPO | RT INFORMATION | |
| | | | | |

PolyOne

MATERIAL SAFETY DATA SHEET **STAN-TONE VC-27829 FOIL GRAY 552**

Version Number 1.1 Revision Date 10/18/2004 Page 5 of 6 Print Date 11/16/2011

| ICAO/IATA (air) | : | Not regulated for transportation. |
|---|--------|--|
| IMO / IMDG (maritime) | : | Not regulated for transportation. |
| | 15 | 5. REGULATORY INFORMATION |
| US Regulations: | | |
| OSHA Status | : | Classified as hazardous based on components. |
| TSCA Status | : | All components of this product are listed on or exempt from the TSCA Inventory. |
| US. EPA CERCLA Hazardous | Sub | stances (40 CFR 302) |
| Not applicable | | |
| | | |
| California Proposition 65 | : | WARNING! This product contains a chemical known to the State of California to cause cancer. |
| SARA Title III Section 302 Ex | trem | ely Hazardous Substance |
| Not applicable | | |
| SARA Title III Section 313 To | xic C | Chemicals: |
| Not applicable Canadian Regulations: | | |
| National Pollutant Relea | ase Iı | nventory (NPRI) |
| Not applicable | | |
| WHMIS Classification | : | Not controlled. |
| DSL | : | All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt. |
| National Inventories: | | |
| Australia AICS | : | Not determined |
| China IECS | : | Not determined |
| Europe EINECS | : | Not determined |
| | | Not determined |

| | | PolyOne. |
|--|------------------|---|
| LYONE CORPORA | TION | |
| TERIAL SAFETY DATA SH | | |
| AN-TONE VC-2782 | 9 FOIL GRAY 552 | |
| sion Number 1.1 ision Date 10/18/2004 | | Page 6 of 6 Print Date 11/16/2011 |
| | | |
| Korea KECI | : Not determined | |
| Philippines PICCS | : Not determined | |
| | 16. OTHER INFO | RMATION |
| | | material designated and may not be valid for such ils and/or in any particular process or processing |