MATERIAL SAFETY DATA SHEET 000000247642

Version Number 1.0 Revision Date 09/21/2007

Page 1 of 6 Print Date 12/1/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone:Emergency telephone:	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name :	00000247642
Product code :	CC10028105
Chemical Name :	Mixture
CAS-No. :	Mixture
Product Use :	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Iron oxide	1309-37-1	1 - 5
Calcium carbonate	1317-65-3	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact		
Acute exposure			
Inhalation Ingestion Eyes	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to 		
Skin	eyes. : Experience shows no unusual dermatitis hazard from routine handling.		
Chronic exposure	: Refer to Section 11 for Toxicological Information.		
Medical Conditions Aggravated by Exposure:	: None known.		

PolyOne.

MATERIAL SAFETY DATA SHEET 000000247642

Version Number 1.0 Revision Date 09/21/2007 Page 2 of 6 Print Date 12/1/2011

		4. FIRST AID MEASURES
Inhalation	:	Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	:	Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	:	Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
		5. FIRE-FIGHTING MEASURES
Flash point	:	Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	: : :	Not applicable Not applicable Not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. A(CCIDENTAL RELEASE MEASURES
Personal precautions	:	Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	:	Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	:	Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
		7. HANDLING AND STORAGE
Handling	:	Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	·	Keep containers dry and tightly closed to avoid moisture absorption



MATERIAL SAFETY DATA SHEET 000000247642

Version Number 1.0 Revision Date 09/21/2007 Page 3 of 6 Print Date 12/1/2011

8. F	EXPOSURE	CONTROLS / PERSONAL	PROTECTION		
Respiratory protection	: N	o personal respiratory protecti	ve equipment normally r	required.	
Eye/Face Protection	: S	: Safety glasses with side-shields			
Hand protection	: Protective gloves				
Skin and body protection	: Long sleeved clothing				
Additional Protective Measures	: Safety shoes				
General Hygiene Considerations		andle in accordance with good Vash hands before breaks and a		afety practice	
Engineering measures		leat only in areas with appropri ppropriate exhaust ventilation		Provide	
Exposure limit(s) Components	Value	Exposure time	Exposure type	List:	
Calcium carbonate	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1	
	15 mg/m3	PEL:	Total dust.	OSHA ZI	
	10 mg/m3	Time Weighted Average (TWA):		MX OEL	
	20 mg/m3	Short Term Exposure Limit (STEL):		MX OEL	
Iron oxide	20 mg/m3 5 mg/m3	Short Term Exposure Limit (STEL): Time Weighted Average (TWA):	Respirable fraction.	MX OEL ACGIH	
Iron oxide	5 mg/m3 10 mg/m3	Short Term Exposure Limit (STEL): Time Weighted Average (TWA): PEL:	Fume.	ACGIH OSHA Z1	
Iron oxide	5 mg/m3 10 mg/m3 5 mg/m3	Short Term Exposure Limit (STEL): Time Weighted Average (TWA): PEL: Time Weighted Average (TWA):	Fume. as Fe	ACGIH OSHA Z1 MX OEL	
Iron oxide	5 mg/m3 10 mg/m3	Short Term Exposure Limit (STEL): Time Weighted Average (TWA): PEL: Time Weighted Average	Fume.	MX OEL ACGIH OSHA Z1 MX OEL MX OEL	
Iron oxide	5 mg/m3 10 mg/m3 5 mg/m3 10 mg/m3	Short Term Exposure Limit (STEL): Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): Short Term Exposure Limit	Fume. as Fe as Fe	ACGIH OSHA Z1 MX OEL	
Iron oxide	5 mg/m3 10 mg/m3 5 mg/m3 10 mg/m3	Short Term Exposure Limit (STEL): Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PRO	Fume. as Fe as Fe PERTIES	ACGIH OSHA Z1 MX OEL	
	5 mg/m3 10 mg/m3 5 mg/m3 10 mg/m3 9. PHYSIC	Short Term Exposure Limit (STEL): Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PRO	Fume. as Fe as Fe DPERTIES ration rate : Not	ACGIH OSHA Z1 MX OEL MX OEL	
Form Appearance Color	5 mg/m3 10 mg/m3 5 mg/m3 10 mg/m3 9. PHYSIC : Solic : pelle : RED	Short Term Exposure Limit (STEL): Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PRO	Fume. as Fe as Fe DPERTIES ration rate : Not ic Gravity : Not ensity : Not	ACGIH OSHA Z1 MX OEL MX OEL applicable determined established	
Form Appearance Color Odour	5 mg/m3 10 mg/m3 5 mg/m3 10 mg/m3 9. PHYSIC : Solic : pelle : RED : Very	Short Term Exposure Limit (STEL): Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PRO ts Specifi Bulk d faint Vapou	Fume. as Fe as Fe OPERTIES ration rate : Not ic Gravity : Not ensity : Not r pressure : Not	ACGIH OSHA Z1 MX OEL MX OEL applicable determined established applicable	
Form Appearance Color	5 mg/m3 10 mg/m3 5 mg/m3 10 mg/m3 9. PHYSIC : Solid : pelle : RED : Very : Not of	Short Term Exposure Limit (STEL): Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PRO ts Specifi Bulk d faint Vapou	Fume. as Fe as Fe OPERTIES ration rate : Not ic Gravity : Not ensity : Not r pressure : Not r density : Not	ACGIH OSHA Z1 MX OEL MX OEL applicable determined established	

POLYONE CORPORATION

PolyOne

MATERIAL SAFETY DATA SHEET 000000247642

Version Number 1.0 Revision Date 09/21/2007 Page 4 of 6 Print Date 12/1/2011

Stability	:	Stable.
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1309-37-1	Iron oxide	Systemic effects	Respiratory system.
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory system.

	12. ECOLOGICAL INFORMATION
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the polymer matrix.
Additional advice	: No data available
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.

PolyOne.

MATERIAL SAFETY DATA SHEET 000000247642

Version Number 1.0 Revision Date 09/21/2007

Page 5 of 6 Print Date 12/1/2011

	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA (air)	: Refer to specific regulation.
IMO / IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardou	s Substances (40 CFR 302)
Not applicable	
California Proposition 65	: Not applicable
SARA 11tle III Section 302 E	xtremely Hazardous Substance
	extremely Hazardous Substance identified under this section, this product is Not Applicable under this regulation
	identified under this section, this product is Not Applicable under this regulation
Unless specific chemicals are SARA Title III Section 313 T	identified under this section, this product is Not Applicable under this regulation
Unless specific chemicals are SARA Title III Section 313 T	identified under this section, this product is Not Applicable under this regulation
Unless specific chemicals are SARA Title III Section 313 T Unless specific chemicals are	identified under this section, this product is Not Applicable under this regulation oxic Chemicals: identified under this section, this product is Not Applicable under this regulation
Unless specific chemicals are SARA Title III Section 313 T Unless specific chemicals are Canadian Regulations:	identified under this section, this product is Not Applicable under this regulation oxic Chemicals: identified under this section, this product is Not Applicable under this regulation
Unless specific chemicals are SARA Title III Section 313 T Unless specific chemicals are Canadian Regulations: National Pollutant Refe	identified under this section, this product is Not Applicable under this regulation foxic Chemicals: identified under this section, this product is Not Applicable under this regulation ease Inventory (NPRI)

PolyOne

MATERIAL SAFETY DATA SHEET 000000247642

Version Number 1.0 Revision Date 09/21/2007 Page 6 of 6 Print Date 12/1/2011

National Inventories:

Australia AICS	:	Listed
China IECS	:	Listed
Europe EINECS	:	Listed
Japan ENCS	:	Listed
Korea KECI	:	Listed
Philippines PICCS	:	Listed

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.