

MATERIAL SAFETY DATA SHEET

YELLOW CORE

Version Number 1.0 Revision Date 01/02/2003 Page 1 of 6 Print Date 11/7/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	YELLOW CORE
Product code	:	CC10028612
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Titanium dioxide	13463-67-7	1 - 5

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.



MATERIAL SAFETY DATA SHEET

YELLOW CORE

ision Date 01/02/2003	Page 2 Print Date 11/7/
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for a least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	 Not applicable Not applicable Not relevant Carbon dioxide blanket, Water spray, dry powder, foam.
Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. None
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 1 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	: Keep containers dry and tightly closed to avoid moisture absorption



MATERIAL SAFETY DATA SHEET

YELLOW CORE

ision Date 01/02/2003				Print	Page 3 Date 11/7/2
	aı	nd contamination. Keep	p in a d	ry, cool place.	
8. E	XPOSURE	CONTROLS / PERSO	ONAL	PROTECTION	
Respiratory protection	: N	o personal respiratory p	protecti	ve equipment normally	required.
Eye/Face Protection	: Safety glasses with side-shields.				
Hand protection	: Protective gloves.				
Skin and body protection	: Long sleeved clothing.				
Additional Protective Measures	: Safety shoes.				
General Hygiene Considerations	: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.				
Engineering measures	: Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.				
Exposure limit(s)					
	** 1	~ · · ·			T
Components	Value	Exposure time		Exposure type	List:
Titanium dioxide	10 mg/m3	Time Weighted Aver (TWA):	rage	Dust.	ACGIH
		Time Weighted Aver	rage		ACGIH
Titanium dioxide	10 mg/m3 15 mg/m3	Time Weighted Aver (TWA):	_	Dust. Total dust.	ACGIH
Titanium dioxide	10 mg/m3 15 mg/m3 9. PHYSIC	Time Weighted Aver (TWA): PEL: CAL AND CHEMICA	L PRO	Dust. Total dust. PERTIES	ACGIH OSHA ZI
Titanium dioxide Titanium dioxide	10 mg/m3 15 mg/m3	Time Weighted Aver (TWA): PEL: CAL AND CHEMICA	L PRO Evapor	Dust. Total dust. PERTIES ration rate : Not	
Titanium dioxide Titanium dioxide	10 mg/m3 15 mg/m3 9. PHYSIC : Solid : Pelle	Time Weighted Aver (TWA): PEL: CAL AND CHEMICA	L PRO Evapor	Dust. Total dust. PERTIES ration rate : Not ic Gravity : Not	ACGIH OSHA ZI
Titanium dioxide Titanium dioxide Form Appearance	10 mg/m3 15 mg/m3 9. PHYSIC : Solid : Pelle	Time Weighted Aver (TWA): PEL: CAL AND CHEMICA	L PRO Evapor Specifi Bulk d	Dust. Total dust. PERTIES ration rate : Not ic Gravity : Not ensity : Not	ACGIH OSHA ZI applicable. determined established
Titanium dioxide Titanium dioxide Form Appearance Color	10 mg/m3 15 mg/m3 9. PHYSIC : Solid : Pelle : YEL : Very	Time Weighted Aver (TWA): PEL: CAL AND CHEMICA tots LOW faint	L PRO Evapor Specifi Bulk d Vapor	Dust. Total dust. PERTIES ration rate : Not c Gravity : Not ensity : Not pressure : Not	ACGIH OSHA ZI applicable.
Titanium dioxide Titanium dioxide Form Appearance Color Odor	10 mg/m3 15 mg/m3 9. PHYSIC : Solid : Pelle : YEL : Very : Not c	Time Weighted Aver (TWA): PEL: CAL AND CHEMICA ts LOW faint determined	L PRO Evapor Specifi Bulk d Vapor	Dust. Total dust. PERTIES ration rate : Not c Gravity : Not ensity : Not pressure : Not density : Not	ACGIH OSHA ZI applicable. determined established applicable
Titanium dioxide Titanium dioxide Titanium dioxide Form Appearance Color Odor Melting point/range	10 mg/m3 15 mg/m3 9. PHYSIC : Solid : Pelle : YEL : Very : Not c	Time Weighted Aver (TWA): PEL: CAL AND CHEMICA ts LOW faint determined applicable	L PRO Evapor Specifi Bulk d Vapor Vapor	Dust. Total dust. PERTIES ration rate : Not c Gravity : Not ensity : Not pressure : Not density : Not	applicable. etablished applicable applicable applicable
Titanium dioxide Titanium dioxide Titanium dioxide Form Appearance Color Odor Melting point/range Boiling Point:	10 mg/m3 15 mg/m3 9. PHYSIC : Solid : Pelle : YEL : Very : Not a : Insol	Time Weighted Aver (TWA): PEL: CAL AND CHEMICA ts LOW faint determined applicable	L PRO Evapor Specifi Bulk d Vapor Vapor pH	Dust. Total dust. DERTIES ration rate : Not ac Gravity : Not ensity : Not pressure : Not density : Not	applicable. etablished applicable applicable applicable
Titanium dioxide Titanium dioxide Titanium dioxide Form Appearance Color Odor Melting point/range Boiling Point:	10 mg/m3 15 mg/m3 9. PHYSIC : Solid : Pelle : YEL : Very : Not c : Not a : Insol 10. S	Time Weighted Aver (TWA): PEL: CAL AND CHEMICA ts LOW faint determined applicable uble	L PRO Evapor Specifi Bulk d Vapor Vapor pH	Dust. Total dust. DERTIES ration rate : Not ac Gravity : Not ensity : Not pressure : Not density : Not	applicable. etablished applicable applicable applicable
Titanium dioxide Titanium dioxide Titanium dioxide Form Appearance Color Odor Melting point/range Boiling Point: Water solubility	10 mg/m3 15 mg/m3 9. PHYSIC : Solid : Pelle : YEL : Very : Not c : Not a : Insol 10. S : St	Time Weighted Aver (TWA): PEL: CAL AND CHEMICA to ts LOW faint determined applicable uble	L PRO Evapor Specifi Bulk d Vapor Vapor pH	Dust. Total dust. DERTIES ration rate : Not ac Gravity : Not ensity : Not pressure : Not density : Not	applicable. etablished applicable applicable applicable
Titanium dioxide Titanium dioxide Titanium dioxide Form Appearance Color Odor Melting point/range Boiling Point: Water solubility Stability	10 mg/m3 15 mg/m3 9. PHYSIC : Solid : Pelle : YEL : Very : Not c : Not a : Insol 10. S n : W : K	Time Weighted Aver (TWA): PEL: CAL AND CHEMICA to take LOW faint determined applicable uble STABILITY AND REA table.	L PRO Evapor Specifi Bulk d Vapor Vapor pH ACTIV	Dust. Total dust. PERTIES ration rate : Not ic Gravity : Not pressure : Not density : Not TTY ts and open flame. To a	ACGIH OSHA Z applicable. determined established applicable applicable



MATERIAL SAFETY DATA SHEET

YELLOW CORE

Version Number 1.0 Revision Date 01/02/2003 Page 4 of 6 Print Date 11/7/2011

Hazardous decomposition products

: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No. 13463-67-7	Chemical Name Titanium dioxide	Effect Systemic effects	Target OrganRespiratory system.				
	12. ECOLOGI	CAL INFORMATION	I de la companya de la				
Persistence and degrada	ability : Not readily b	iodegradable.					
Environmental Toxicity		: Chemicals are not readily available as they are bound within the matrix of the polymer.					
Bioaccumulation Poten		: Chemicals are not readily available as they are bound within the matrix of the polymer.					
Additional advice	: No data avail	lable.					
	13. DISPOSAL	CONSIDERATIONS	9				
Product Contaminated packagin	g : Recycling is has the respo and disposal	 Like most thermoplastics the product can be recycled. Where possible, recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal. 					
	14. TRANSPO	ORT INFORMATION					
U.S. DOT Classificatio	n : Refer to spec	fic regulation.					
ICAO/IATA	: Refer to spec	: Refer to specific regulation.					
IMO / IMDG	: Refer to spec	ific regulation.					
	15. REGULAT	ORY INFORMATION	N				

MATERIAL SAFETY DATA SHEET



YELLOW CORE Page 5 of 6 Version Number 1.0 Print Date 11/7/2011 Revision Date 01/02/2003 US Regulations: **OSHA Status** : Classified as hazardous based on components. **TSCA Status** All components of this product are listed on or exempt from the TSCA : Inventory. US. EPA CERCLA Hazardous Substances (40 CFR 302) Not applicable California Proposition : This product does not contain a substance listed by California Prop 65. 65 Canadian Regulations: WHMIS Classification : D2B DSL All components of this product are on the Canadian Domestic : Substances List (DSL) or are exempt. National Inventories: Australia AICS : Listed. China IECS Listed. ٠ **Europe EINECS** Not determined. Japan ENCS Listed. : Korea KECI Listed. : **Philippines PICCS** : Listed.

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

MATERIAL SAFETY DATA SHEET

YELLOW CORE

Version Number 1.0 Revision Date 01/02/2003



Page 6 of 6 Print Date 11/7/2011