

MATERIAL SAFETY DATA SHEET

GE DOVER CLIFF GRAY PS

Version Number 1.0 Revision Date 01/28/2003 Page 1 of 6 Print Date 11/10/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	GE DOVER CLIFF GRAY PS
Product code	:	CC10028964
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
C.I. Pigment Yellow 53	8007-18-9	0.1 - 1
Titanium dioxide	13463-67-7	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to
Skin	eyes. : Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.



MATERIAL SAFETY DATA SHEET

GE DOVER CLIFF GRAY PS

Medical Conditions	: None known.
Aggravated by Exposure:	
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases o doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	 Not applicable Not applicable Not relevant Carbon dioxide blanket, Water spray, dry powder, foam.
Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. None
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 1 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.



MATERIAL SAFETY DATA SHEET

GE DOVER CLIFF GRAY PS

Version Number 1.0 Revision Date 01/28/2003 Page 3 of 6 Print Date 11/10/2011

Storage

: Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Respiratory protection	:	No personal respiratory protective equipment normally required.
Eye/Face Protection	:	Safety glasses with side-shields.
Hand protection	:	Protective gloves.
Skin and body protection	:	Long sleeved clothing.
Additional Protective Measures	:	Safety shoes.
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
C.I. Pigment Yellow 53	1 mg/m3	PEL:	as Ni	OSHA Z1
C.I. Pigment Yellow 53	0.5 mg/m3	PEL:	as Sb	OSHA Z1
C.I. Pigment Yellow 53	0.2 mg/m3	Time Weighted Average (TWA):	as Ni	ACGIH
C.I. Pigment Yellow 53	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	ACGIH
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):	Dust.	ACGIH
Titanium dioxide	15 mg/m3	PEL:	Total dust.	OSHA Z1

9. PHYSICAL AND CHEMICAL PROPERTIES

- Form Appearance Color Odor Melting point/range Boiling Point: Water solubility
- Solid
 Pellets
 GREY
 Very faint
 Not determined
 Not applicable
 Insoluble
- Evaporation rate Specific Gravity Bulk density Vapor pressure Vapor density pH
- Not applicable.
 Not determined
 Not established
 Not applicable
 Not applicable
 Not applicable

10. STABILITY AND REACTIVITY

3/6



MATERIAL SAFETY DATA SHEET

GE DOVER CLIFF GRAY PS

Version Number 1.0 Revision Date 01/28/2003 Page 4 of 6 Print Date 11/10/2011

Stability	:	Stable.
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
8007-18-9	C.I. Pigment Yellow 53	Irritant	Eyes, Skin.
		sensitizer	Skin.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

Carcinogenicity:

This product contains the following components which in their pure form have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
8007-18-9	C.I. Pigment Yellow 53	no	1	2

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

Additional Health Hazard Information:

C.I. Pigment Yellow 53 8007-18-9 Skin sensitizer "nickel itch", with pulmonary, brain, liver, kidney andmuscle effects.

12. ECOLOGICAL INFORMATION

Persistence and degradability

: Not readily biodegradable.



MATERIAL SAFETY DATA SHEET

GE DOVER CLIFF GRAY PS

nicals are not readily available as they are bound within the matrix e polymer. nicals are not readily available as they are bound within the matrix e polymer. ata available. POSAL CONSIDERATIONS most thermoplastics the product can be recycled. Where ble, recycling is preferred to disposal or incineration. The rator of waste material has the responsibility for proper waste ification, transportation and disposal in accordance with cable federal, state/provincial and local regulations. cling is preferred when possible. The generator of waste materia ne responsibility for proper waste classification, transportation tisposal in accordance with applicable federal, state/provincial ocal regulations.
e polymer. ata available. POSAL CONSIDERATIONS most thermoplastics the product can be recycled. Where ble, recycling is preferred to disposal or incineration. The rator of waste material has the responsibility for proper waste ification, transportation and disposal in accordance with cable federal, state/provincial and local regulations. cling is preferred when possible. The generator of waste materia he responsibility for proper waste classification, transportation lisposal in accordance with applicable federal, state/provincial ocal regulations. ANSPORT INFORMATION
POSAL CONSIDERATIONS most thermoplastics the product can be recycled. Where ble, recycling is preferred to disposal or incineration. The rator of waste material has the responsibility for proper waste ification, transportation and disposal in accordance with cable federal, state/provincial and local regulations. cling is preferred when possible. The generator of waste materia he responsibility for proper waste classification, transportation lisposal in accordance with applicable federal, state/provincial ocal regulations.
most thermoplastics the product can be recycled. Where ble, recycling is preferred to disposal or incineration. The rator of waste material has the responsibility for proper waste ification, transportation and disposal in accordance with cable federal, state/provincial and local regulations. cling is preferred when possible. The generator of waste materia ne responsibility for proper waste classification, transportation lisposal in accordance with applicable federal, state/provincial ocal regulations.
ble, recycling is preferred to disposal or incineration. The rator of waste material has the responsibility for proper waste ification, transportation and disposal in accordance with cable federal, state/provincial and local regulations. cling is preferred when possible. The generator of waste materia he responsibility for proper waste classification, transportation lisposal in accordance with applicable federal, state/provincial ocal regulations.
ne responsibility for proper waste classification, transportation lisposal in accordance with applicable federal, state/provincial ocal regulations.
to specific regulation.
to specific regulation.
to specific regulation.
to specific regulation.
ULATORY INFORMATION
ified as hazardous based on components.
components of this product are listed on or exempt from the TSCA atory.
s (40 CFR 302)
RNING! This product contains a chemical known to the State of ornia to cause cancer.



MATERIAL SAFETY DATA SHEET

GE DOVER CLIFF GRAY PS

Version Number 1.0 Revision Date 01/28/2003 Page 6 of 6 Print Date 11/10/2011

SARA Title III Section 313 Toxic Chemicals:

С	hemical Name	CAS-No.	Weight %
Ν	ICKEL COMPOUNDS	8007-18-9	00.12
Α	NTIMONY COMPOUNDS		

Canadian Regulations:

WHMIS Classification	:	D2B
DSL	:	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.
National Inventories:		
Australia AICS	:	Listed.
China IECS	:	Listed.
Europe EINECS	:	Not determined.
Japan ENCS	:	Not determined.
Korea KECI	:	Not determined.
Philippines PICCS	:	Listed.
-		

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.