

MATERIAL SAFETY DATA SHEET

GRAY SPECKLE PS

Version Number 1.0 Revision Date 01/23/2003 Page 1 of 7 Print Date *11/10/2011*

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	GRAY SPECKLE PS
Product code	:	CC10028966
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
C.I. Pigment Yellow 53	8007-18-9	0.1 - 1
Cellulose	9004-34-6	5 - 10
Titanium dioxide	13463-67-7	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion	Resin particles, like other inert materials, can be mechanically irritating.May be harmful if swallowed.
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.



MATERIAL SAFETY DATA SHEET

GRAY SPECKLE PS

Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for a least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits	
Upper explosion limit	: Not applicable
Lower explosion limit	: Not applicable
Autoignition temperature	: Not relevant
Suitable extinguishing media	: Carbon dioxide blanket, Water spray, dry powder, foam.
Special Fire Fighting	: Fullface self-contained breathing apparatus (SCBA) used in positive
Procedures	pressure mode should be worn to prevent inhalation of airborne
Tiocedures	contaminants.
Unusual Fire/Explosion Hazards	: None
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should no be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 1 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.

MATERIAL SAFETY DATA SHEET

GRAY SPECKLE PS



Version Number 1.0 Revision Date 01/23/2003	Page 3 of 7 Print Date 11/10/2011
Storage :	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.
8. EXPOSU	RE CONTROLS / PERSONAL PROTECTION
Respiratory protection :	No personal respiratory protective equipment normally required.
Eye/Face Protection : Safety glasses with side-shields.	
Hand protection : Protective gloves.	
Skin and body protection :	Long sleeved clothing.
Additional Protective : Safety shoes. Measures	
General Hygiene:Handle in accordance with good industrial hygiene and safety pract Wash hands before breaks and at the end of workday.	
Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.	

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
C.I. Pigment Yellow	ment Yellow 1 mg/m3 PEL:		as Ni	OSHA Z1
53				
C.I. Pigment Yellow	0.5 mg/m3	PEL:	as Sb	OSHA Z1
53				
C.I. Pigment Yellow	0.2 mg/m3	Time Weighted Average	as Ni	ACGIH
53		(TWA):		
C.I. Pigment Yellow	0.5 mg/m3	Time Weighted Average	as Sb	ACGIH
53		(TWA):		
Cellulose	10 mg/m3	Time Weighted Average	Total dust.	ACGIH
		(TWA):		
Cellulose	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
Titanium dioxide	10 mg/m3	Time Weighted Average	Dust.	ACGIH
	_	(TWA):		
Titanium dioxide	15 mg/m3	PEL:	Total dust.	OSHA Z1

9. PHYSICAL AND CHEMICAL PROPERTIES

Form Appearance Color Odor Melting point/range : Solid
: Pellets
: GREY
: Very faint
: Not determined

Evaporation rate Specific Gravity Bulk density Vapor pressure Vapor density Not applicable.Not determinedNot established

- : Not applicable
- : Not applicable



MATERIAL SAFETY DATA SHEET

GRAY SPECKLE PS

Version Number 1.0 Revision Date 01/23/2003			Print Date	Page 4 of 7 11/10/2011
Boiling Point: Water solubility	: Not applicable : Insoluble	рН	: Not app	licable
	10. STABILITY AND RE	ACTIVITY		
Stability	: Stable.			
Hazardous Polymerization	: Will not occur.			
Conditions to avoid	: Keep away from oxidizi decomposition, do not o	001	flame. To avoid	thermal
Incompatible Materials	: Incompatible with stron	g acids and oxidizin	g agents.	
Hazardous decomposition products	: Carbon dioxide (CO2), (NOx), other hazardous			0

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
8007-18-9	C.I. Pigment Yellow 53	Irritant	Eyes, Skin.
		sensitizer	Skin.
9004-34-6 Cellulose		Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

LC50 / LD50

This product contains the following components which in their pure form have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
9004-34-6	Cellulose	LC50	> 5800 mg/m3	rat
		Oral LD50	> 5 gm/kg	rat
		Dermal LD50	> 2 gm/kg	rabbit

Carcinogenicity:

This product contains the following components which in their pure form have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
8007-18-9	C.I. Pigment Yellow 53	no	1	2

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.



MATERIAL SAFETY DATA SHEET

GRAY SPECKLE PS

Version Number 1.0 Revision Date 01/23/2003

Page 5 of 7 Print Date 11/10/2011

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

<u>Additional Health Hazard Information:</u> C.I. Pigment Yellow 53 8007-18-9 Skin sensitizer "nickel itch", with pulmonary, brain, liver, kidney andmuscle effects.

	12. ECOLOGICAL INFORMATION
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the matri of the polymer.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the matri of the polymer.
Additional advice	: No data available.
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastics the product can be recycled. Where possible, recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Refer to specific regulation.
ICAO/IATA	: Refer to specific regulation.
IMO / IMDG	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.

5/7



MATERIAL SAFETY DATA SHEET

GRAY SPECKLE PS

Chemical Name	CAS-No.	Weight %
NICKEL COMPOUNDS	8007-18-9	00.22
ANTIMONY COMPOUNDS		

Canadian Regulations:

WHMIS Classification	:	D2B
DSL	:	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

Australia AICS	:	Listed.
China IECS	:	Listed.
Europe EINECS	:	Not determined.
Japan ENCS	:	Listed.
Korea KECI	:	Listed.
Philippines PICCS	:	Listed.

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

MATERIAL SAFETY DATA SHEET

GRAY SPECKLE PS

Version Number 1.0 Revision Date 01/23/2003



Page 7 of 7 Print Date 11/10/2011