

### MATERIAL SAFETY DATA SHEET

# PG 29190 SI PP

Version Number 1.0 Revision Date 01/10/2003 Page 1 of 6 Print Date 11/7/2011

## 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	PG 29190 SI PP
Product code	:	CC10029190
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

#### 2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Aluminum	7429-90-5	1 - 5
Mica	12001-26-2	10 - 30
Titanium dioxide	13463-67-7	10 - 30

## **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

## POTENTIAL HEALTH EFFECTS

<b>Routes of Exposure:</b>	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion	<ul><li>Resin particles, like other inert materials, can be mechanically irritating.</li><li>May be harmful if swallowed.</li></ul>
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.





6 29190 SI PP	
sion Number 1.0 ision Date 01/10/2003	Page 2 Print Date 11/7/2
Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	<ul> <li>Not applicable</li> <li>Not applicable</li> <li>Not relevant</li> <li>Carbon dioxide blanket, Water spray, dry powder, foam.</li> </ul>
Special Fire Fighting Procedures	<ul> <li>Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.</li> </ul>
Unusual Fire/Explosion Hazards	: None
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 1 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.

### MATERIAL SAFETY DATA SHEET

# PG 29190 SI PP



Version Number 1.0 Revision Date 01/10/2003		Page 3 of 6 Print Date 11/7/2011
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.
8. EXP	OSUF	RE CONTROLS / PERSONAL PROTECTION
Respiratory protection	:	No personal respiratory protective equipment normally required.
Eye/Face Protection	:	Safety glasses with side-shields.
Hand protection	:	Protective gloves.
Skin and body protection	:	Long sleeved clothing.
Additional Protective Measures	:	Safety shoes.
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Aluminum	10 mg/m3	Time Weighted Average	Dust.	ACGIH
	_	(TWA):		
	5 mg/m3	Time Weighted Average	Welding fume. as Al	ACGIH
	_	(TWA):		
Aluminum	15 mg/m3	PEL:	Total dust. as Al	OSHA Z1
	5 mg/m3	PEL:	Respirable dust. as Al	OSHA Z1
Mica	3 mg/m3	Time Weighted Average	Total dust.	ACGIH
		(TWA):		
Mica	20 mppcf	PEL:	Total dust.	OSHA
Titanium dioxide	10 mg/m3	Time Weighted Average	Dust.	ACGIH
	_	(TWA):		
Titanium dioxide	15 mg/m3	PEL:	Total dust.	OSHA Z1

# 9. PHYSICAL AND CHEMICAL PROPERTIES

- Form Appearance Color Odor Melting point/range Boiling Point: Water solubility
- : Solid
  : Pellets
  : GREY
  : Very faint
  : Not determined
  : Not applicable
  : Insoluble
- Evaporation rate Specific Gravity Bulk density Vapor pressure Vapor density pH
- Not applicable.
  Not determined
  Not established
  Not applicable
  Not applicable
  Not applicable



### MATERIAL SAFETY DATA SHEET

# PG 29190 SI PP

Version Number 1.0 Revision Date 01/10/2003 Page 4 of 6 Print Date 11/7/2011

	10. STABILITY AND REACTIVITY
Stability	: Stable.
Hazardous Polymerization	: Will not occur.
Conditions to avoid	: Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	: Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

# 11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

# Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
7429-90-5	Aluminum	Irritant	Skin, Respiratory system.
		Systemic effects	Eyes, Skin, Respiratory system.
12001-26-2	Mica	Systemic effects	Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the matri of the polymer.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the matri of the polymer.
Additional advice	: No data available.
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastics the product can be recycled. Where possible, recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste materia



MATERIAL SAFETY DATA SHEET

# PG 29190 SI PP Page 5 of 6 Version Number 1.0 Print Date 11/7/2011 Revision Date 01/10/2003 has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. **14. TRANSPORT INFORMATION** : Refer to specific regulation. U.S. DOT Classification ICAO/IATA Refer to specific regulation. : IMO / IMDG Refer to specific regulation. : **15. REGULATORY INFORMATION US Regulations: OSHA Status** Classified as hazardous based on components. · **TSCA Status** : All components of this product are listed on or exempt from the TSCA Inventory. US. EPA CERCLA Hazardous Substances (40 CFR 302) Not applicable California Proposition : This product does not contain a substance listed by California Prop 65. 65 SARA Title III Section 313 Toxic Chemicals: Chemical Name CAS-No. Weight % ALUMINUM (FUME OR DUST) 7429-90-5 01.76 Canadian Regulations: WHMIS Classification : D2B WHMIS Ingredient Disclosure List CAS-No. 7429-90-5 12001-26-2



#### MATERIAL SAFETY DATA SHEET

# PG 29190 SI PP

Version Number 1.0 Revision Date 01/10/2003	Print Date	Page 6 of 6 11/7/2011
DSL	: All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.	
National Inventories:		
Australia AICS	: Listed.	
China IECS	: Listed.	
Europe EINECS	: Not determined.	
Japan ENCS	: Not determined.	
Korea KECI	: Listed.	
Philippines PICCS	: Listed.	

### **16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.