MATERIAL SAFETY DATA SHEET GRANITE

Version Number 1.1 Revision Date 04/05/2007

Product Use

Page 1 of 8 Print Date 11/27/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone number	:	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	GRANITE
Product code	:	CC10029781
Chemical Name	:	Mixture
CAS-No.	:	Mixture

: Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
1,6-Hexanediamine, N,N'-bis(2,2,6,6-tetramethyl-4-piperidinyl)-,	70624-18-9	5 - 10
polymer with 2,4,6-trichloro-1,3,5-triazine, reaction products		
Cellulose	9004-34-6	1 - 5
Rutile, antimony chromium buff	68186-90-3	1 - 5
Titanium dioxide	13463-67-7	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure: : Inhalation, Ingestion, Skin contact

Acute exposure

Inhalation	: Resin particles, like other inert materials, can be mechanically irritating.
Ingestion	: May be harmful if swallowed.
Eyes	: Resin particles, like other inert materials, are mechanically irritating to
	eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.

1/8

POLYONE CORPORATION

PolyOne.

MATERIAL SAFETY DATA SHEET **GRANITE**

Version Number 1.1 Revision Date 04/05/2007 Page 2 of 8 Print Date 11/27/2011

Medical Conditions : None known.				
Aggravated by Exposure:	•	None known.		
		4. FIRST AID MEASURES		
Inhalation	:	Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.		
Ingestion	:	Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.		
Eyes	:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.		
Skin	:	Wash off with soap and plenty of water. If skin irritation persists seek medical attention.		
		5. FIRE-FIGHTING MEASURES		
Flash point	:	Not applicable		
Flammable Limits				
Upper explosion limit	:	Not applicable		
Lower explosion limit	:	Not applicable		
Autoignition temperature	:	Not applicable		
Suitable extinguishing media	:	Carbon dioxide blanket, Water spray, Dry powder, Foamnone.		
Special Fire Fighting	:	Fullface self-contained breathing apparatus (SCBA) used in positive		
Procedures		pressure mode should be worn to prevent inhalation of airborne		
		contaminants.		
Unusual Fire/Explosion Hazards	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.		
	6. A	CCIDENTAL RELEASE MEASURES		
Personal precautions	:	Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.		
Environmental precautions	:	Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.		
Methods for cleaning up	:	Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.		

PolyOne.

MATERIAL SAFETY DATA SHEET **GRANITE**

Version Number 1.1 Revision Date 04/05/2007

Page 3 of 8 Print Date 11/27/2011

Handling	:	Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.	
Storage	:	: Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.	
8. EXI	POSUI	RE CONTROLS / PERSONAL PROTECTION	
Respiratory protection	:	No personal respiratory protective equipment normally required.	
Eye/Face Protection	:	Safety glasses with side-shields	
Hand protection	:	Protective gloves	
Skin and body protection	:	Long sleeved clothing	
Additional Protective Measures	:	Safety shoes	
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice Wash hands before breaks and at the end of workday.	
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.	

PolyOne

MATERIAL SAFETY DATA SHEET GRANITE

Version Number 1.1

Revision Date 04/05/2007

Page 4 of 8 Print Date 11/27/2011

Components	Value	Exposure time	Exposure type	List:
Cellulose	10 mg/m3	Time Weighted Average (TWA):	Total dust.	ACGIH
	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	20 mg/m3	Short Term Exposure Limit (STEL):		MX OEL
Rutile, antimony chromium buff	0.5 mg/m3	Time Weighted Average (TWA):	as Cr	ACGIH
	0.5 mg/m3	PEL:	as Cr	OSHA Z1
	0.5 mg/m3	Time Weighted Average (TWA):		MX OEL
	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	ACGIH
	0.5 mg/m3	PEL:	as Sb	OSHA Z1
	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	MX OEL
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):		ACGIH
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	20 mg/m3	Short Term Exposure Limit (STEL):	as Ti	MX OEL

9. PHYSICAL AND CHEMICAL PROPERTIES

Form Appearance Color Odour Melting point/range Boiling Point: Water solubility

: pellets GREY : : Very faint Not determined : Not applicable : : Insoluble

: Solid

Evaporation rate Specific Gravity Bulk density Vapour pressure Vapour density pН

- Not applicable :
- Not determined :
- Not established :
- Not applicable :
- : Not applicable
- Not applicable :

10. STABILITY AND REACTIVITY

Stability

Hazardous Polymerization

Conditions to avoid

products

: Stable.

Will not occur. :

- Keep away from oxidizing agents and open flame. To avoid thermal : decomposition, do not overheat.
- **Incompatible Materials** Incompatible with strong acids and oxidizing agents. :
- Hazardous decomposition Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen : (NOx), other hazardous materials, and smoke are all possible.
 - **11. TOXICOLOGICAL INFORMATION**

MATERIAL SAFETY DATA SHEET **GRANITE**

Version Number 1.1 Revision Date 04/05/2007

Page 5 of 8 Print Date 11/27/2011

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
70624-18-9	1,6-Hexanediamine, N,N'-bis(2,2,6,6-tetrameth yl-4-piperidinyl)-,polymer with 2,4,6-trichloro-1,3,5-triazi ne, reaction products	Irritant	Eyes, Skin, Respiratory system.
9004-34-6	Cellulose	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory system.
68186-90-3	Rutile, antimony chromium buff	Irritant	Eyes, Skin, Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
70624-18-9	1,6-Hexanediamine,	Oral LD50	> 2,000 mg/kg	rat
	N,N'-bis(2,2,6,6-tetrameth	Dermal LD50	> 3,000 mg/kg	rat
	yl-4-piperidinyl)-,polymer			
	with			
	2,4,6-trichloro-1,3,5-triazi			
	ne, reaction products			
9004-34-6	Cellulose	LC50	> 5800 mg/m3	rat
		Oral LD50	> 5 gm/kg	rat
		Dermal LD50	> 2 gm/kg	rabbit

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
13463-67-7	Titanium dioxide	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

Additional Health Hazard Information:

<u>PolyOne</u>

MATERIAL SAFETY DATA SHEET **GRANITE**

Version Number 1.1 Revision Date 04/05/2007 Page 6 of 8 Print Date 11/27/2011

Rutile, antimony chromium buff 68186-90-3 Can cause eye irritation. Can cause skin irritation. Symptoms may include redness and burning of skin, and other skin damage. Additional symptoms of skin contact may include: antimony measles (a red, pimply rash).

	12. ECOLOGICAL INFORMATION
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the polymer matrix.
Additional advice	: no data available
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
	Net we let 1 Contained the
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA (air)	: Refer to specific regulation.
IMO / IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardous	Substances (40 CFR 302)
Not applicable	

POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET **GRANITE**

Version Number 1.1 Revision Date 04/05/2007 Page 7 of 8 Print Date 11/27/2011

California Proposition : Not applicable 65

SARA Title III Section 302 Extremely Hazardous Substance

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Chemical Name	CAS-No.	Weight %
CHROMIUM III COMPOUNDS	1308-38-9	0.10 - 1.00
CHROMIUM III COMPOUNDSANTIMONY	68186-90-3	1.00 - 5.00
COMPOUNDS		

Canadian Regulations:

National Pollutant Release Inventory (NPRI)Chemical NameCAS-No.Weight %NPRI ID#Chromium (III) oxide1308-38-90.10 - 1.0069Rutile, antimony chromium buff68186-90-31.00 - 5.00691.00 - 5.0017

WHMIS Classification : D2A

WHMIS Ingredient Disclosure List

CAS-No.	
68186-90-3	

DSL

All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

Australia AICS	:	Listed
China IECS	:	Listed
Europe EINECS	:	Listed

:

P_{O}	lyOne.

MATERIAL SAFETY DATA SHEET GRANITE

Version Number 1.1 Revision Date 04/05/2007 Page 8 of 8 Print Date 11/27/2011

Japan ENCS : Not determined

Korea KECI : Not determined

Philippines PICCS : Not determined

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.