

### MATERIAL SAFETY DATA SHEET

## FLESH TAN 155C LCS26304

Version Number 1.0 Revision Date 01/28/2003 Page 1 of 6 Print Date *11/10/2011* 

## 1. PRODUCT AND COMPANY IDENTIFICATION

### POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	FLESH TAN 155C LCS26304
Product code	:	CC10030215
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

#### 2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Titanium dioxide	13463-67-7	60 - 100

#### **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

## POTENTIAL HEALTH EFFECTS

<b>Routes of Exposure:</b>	: Inhalation, Skin contact, Ingestion	
Acute exposure		
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.	
Ingestion	: May be harmful if swallowed.	
Eyes	: Irritating to eyes and respiratory system.	
Skin	: Experience shows no unusual dermatitis hazard from routine handling.	
Chronic exposure	: Refer to Section 11 for Toxicological Information.	
Medical Conditions Aggravated by Exposure:	: None known.	



MATERIAL SAFETY DATA SHEET

# FLESH TAN 155C LCS26304

Version Number 1.0 Revision Date 01/28/2003 Page 2 of 6 Print Date 11/10/2011

	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. Seek medical attention after significant exposure.
Ingestion	: Do not induce vomiting without medical advice. Seek medical attention if necessary.
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If ey irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Greater than 200 °F (93 °C)
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	<ul> <li>Not applicable.</li> <li>Not applicable.</li> <li>Not applicable.</li> <li>Carbon dioxide blanket, dry powder, foam.</li> </ul>
Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	<ul> <li>Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.</li> <li>None</li> </ul>
	5. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should no be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binde universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Heat only in areas with appropriate exhaust ventilation.
Storage	: Keep containers dry and tightly closed to avoid moisture absorption



MATERIAL SAFETY DATA SHEET

# FLESH TAN 155C LCS26304

Version Number 1.0 Revision Date 01/28/2003 Page 3 of 6 Print Date 11/10/2011

8. F		nd contamination. Store			
Respiratory protection				ons a respirator may not	be required.
Eye/Face Protection		afety glasses with side-			•
Hand protection		: Protective gloves.			
Skin and body protection	: Long sleeved clothing.				
Additional Protective Measures		afety shoes.			
General Hygiene Considerations		: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.			
Engineering measures		: Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.			
Exposure limit(s)					
Components	Value	Exposure time		Exposure type	List:
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):		Dust.	ACGIH
Titanium dioxide	15 mg/m3	PEL:		Total dust.	OSHA Z1
	9. PHYSIC	CAL AND CHEMICA	L PRO	PERTIES	
Form Appearance Color Odor Melting point/range Boiling Point: Water solubility	: TAN : Very : Not a	pus, Liquid faint applicable applicable	Specifi Bulk d Vapor	ic Gravity : Not ensity : Not pressure : Not density : Not	determined determined applicable. determined applicable.
	<b>10.</b> S	TABILITY AND REA	ACTIV	ITY	
Stability	: S	table.			
	n : W	/ill not occur.			
Hazardous Polymerization	Conditions to avoid : Keep away from oxidizing agents and open flame.				
Hazardous Polymerization	: K	eep away from oxidizir	ng agen	ts and open flame.	
-		eep away from oxidizir		-	



### MATERIAL SAFETY DATA SHEET

## FLESH TAN 155C LCS26304

Version Number 1.0 Revision Date 01/28/2003

Page 4 of 6 Print Date 11/10/2011

products

(NOx), other hazardous materials, and smoke are all possible.

### **11. TOXICOLOGICAL INFORMATION**

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

<u>Toxicity Overview</u> This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

12. ECOLOGICAL INFORMATION				
Persistence and degradability	: Not readily biodegradable.			
Environmental Toxicity	: Adverse ecological impact is not known or expected under normal use.			
<b>Bioaccumulation Potential</b>	: Does not bioaccumulate.			
Additional advice	: No data available.			
13. DISPOSAL CONSIDERATIONS				
Product	: Where possible, recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.			
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.			
14. TRANSPORT INFORMATION				
U.S. DOT Classification	: Not regulated for transportation.			
ICAO/IATA	: Not regulated for transportation.			
IMO / IMDG	: Not regulated for transportation.			
15. REGULATORY INFORMATION				
US Regulations:				
OSHA Status	: Classified as hazardous based on components.			



### MATERIAL SAFETY DATA SHEET

## FLESH TAN 155C LCS26304

Version Number 1.0 Revision Date 01/28/2003	Page 5 of 6 Print Date 11/10/2011
TSCA Status :	All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardous Sub	stances (40 CFR 302)
Not applicable	
California Proposition : 65	This product does not contain a substance listed by California Prop 65.
Canadian Regulations:	
WHMIS Classification :	D2B
WHMIS Ingredient Disclosu	rre List
CAS-No. 103-23-1	
DSL :	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.
National Inventories:	
Australia AICS :	Listed.
China IECS :	Listed.
Europe EINECS :	Listed.
Japan ENCS :	Listed.
Korea KECI :	Not determined.
Philippines PICCS :	Listed.
	16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.



MATERIAL SAFETY DATA SHEET

# FLESH TAN 155C LCS26304

Version Number 1.0 Revision Date 01/28/2003 Page 6 of 6 Print Date 11/10/2011