

MATERIAL SAFETY DATA SHEET

ORANGE 172C

Version Number 1.0 Revision Date 02/03/2003 Page 1 of 6 Print Date 11/10/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	ORANGE 172C
Product code	:	CC10030643
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Calcium carbonate	1317-65-3	1 - 5
Titanium dioxide	13463-67-7	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to
Skin	eyes.Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.





ion Number 1.0 sion Date 02/03/2003	Page Print Date 11/10
Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for a least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists se medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 Not applicable Not applicable Not relevant Carbon dioxide blanket, Water spray, dry powder, foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. None
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.

MATERIAL SAFETY DATA SHEET

ODANOE 4700



sion Number 1.0 rision Date 02/03/2003			Print [Page 3 o Date 11/10/20	
Storage		eep containers dry and tightly nd contamination. Keep in a d		e absorption	
8. E	XPOSURE	CONTROLS / PERSONAL	PROTECTION		
Respiratory protection	: N	o personal respiratory protecti	ve equipment normally	required.	
Eye/Face Protection	: S	Safety glasses with side-shields.			
Hand protection	: P	Protective gloves.			
Skin and body protection	: L	Long sleeved clothing.			
Additional Protective Measures	: S	afety shoes.			
General Hygiene Considerations		andle in accordance with good ash hands before breaks and a		safety practice.	
	. 11	· · · · · · · · · · · · · · · · · · ·			
Engineering measures		leat only in areas with appropri- ppropriate exhaust ventilation		Provide	
Engineering measures Exposure limit(s)				Provide	
Exposure limit(s) Components				List:	
Exposure limit(s)	aj	ppropriate exhaust ventilation	at machinery.		
Exposure limit(s) Components	aj Value 10 mg/m3 5 mg/m3	Exposure time Time Weighted Average (TWA): PEL:	at machinery. Exposure type Total dust. Respirable dust.	List: ACGIH OSHA Z1	
Exposure limit(s) Components Calcium carbonate Calcium carbonate	aj Value 10 mg/m3 5 mg/m3 15 mg/m3	Exposure time Time Weighted Average (TWA): PEL: PEL:	at machinery. Exposure type Total dust. Respirable dust. Total dust.	List: ACGIH OSHA Z1 OSHA Z1	
Exposure limit(s) Components Calcium carbonate	aj Value 10 mg/m3 5 mg/m3	Exposure time Time Weighted Average (TWA): PEL:	at machinery. Exposure type Total dust. Respirable dust. Total dust. Dust.	List: ACGIH OSHA Z1 OSHA Z1 ACGIH	
Exposure limit(s) Components Calcium carbonate Calcium carbonate	aj Value 10 mg/m3 5 mg/m3 15 mg/m3	Exposure time Time Weighted Average (TWA): PEL: PEL: Time Weighted Average	at machinery. Exposure type Total dust. Respirable dust. Total dust.	List: ACGIH OSHA Z1 OSHA Z1	
Exposure limit(s) Components Calcium carbonate Calcium carbonate Titanium dioxide	aj Value 10 mg/m3 5 mg/m3 15 mg/m3 10 mg/m3 15 mg/m3	Exposure time Time Weighted Average (TWA): PEL: PEL: Time Weighted Average (TWA):	at machinery. Exposure type Total dust. Respirable dust. Total dust. Dust. Total dust.	List: ACGIH OSHA Z1 OSHA Z1 ACGIH	
Exposure limit(s) Components Calcium carbonate Calcium carbonate Titanium dioxide Titanium dioxide	aj Value 10 mg/m3 5 mg/m3 15 mg/m3 10 mg/m3 15 mg/m3 9. PHYSIC	Exposure time Time Weighted Average (TWA): PEL: PEL: Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO	at machinery. Exposure type Total dust. Respirable dust. Total dust. Dust. Total dust.	List: ACGIH OSHA Z1 OSHA Z1 ACGIH OSHA Z1	
Exposure limit(s) Components Calcium carbonate Calcium carbonate Titanium dioxide Titanium dioxide Form	aj Value 10 mg/m3 5 mg/m3 15 mg/m3 10 mg/m3 15 mg/m3 	Exposure time Time Weighted Average (TWA): PEL: PEL: Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO	at machinery. Exposure type Total dust. Respirable dust. Total dust. Dust. Total dust. PERTIES ration rate : No	List: ACGIH OSHA Z1 OSHA Z1 ACGIH OSHA Z1 t applicable.	
Exposure limit(s) Components Calcium carbonate Calcium carbonate Titanium dioxide Titanium dioxide Form Appearance	aj Value 10 mg/m3 5 mg/m3 15 mg/m3 10 mg/m3 15 mg/m3 15 mg/m3 	Exposure time Time Weighted Average (TWA): PEL: PEL: Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO L Evapor Specifi	at machinery. Exposure type Total dust. Respirable dust. Total dust. Dust. Total dust. OPERTIES ration rate : No ic Gravity : No	List: ACGIH OSHA Z1 OSHA Z1 ACGIH OSHA Z1 t applicable. t determined	
Exposure limit(s) Components Calcium carbonate Calcium carbonate Titanium dioxide Titanium dioxide Form Appearance Color	aj Value 10 mg/m3 5 mg/m3 15 mg/m3 10 mg/m3 15 mg/m3 15 mg/m3 5 PHYSIC : Solid : Pelle : ORA	Exposure time Time Weighted Average (TWA): PEL: PEL: Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO L Evapor Sts Specific NGE Bulk d	at machinery. Exposure type Total dust. Respirable dust. Total dust. Dust. Total dust. OPERTIES ration rate : Noisi Gravity ic Gravity : Noisity	List: ACGIH OSHA Z1 OSHA Z1 ACGIH OSHA Z1 t applicable. t determined t established	
Exposure limit(s) Components Calcium carbonate Calcium carbonate Titanium dioxide Titanium dioxide Form Appearance Color Odor	aj Value 10 mg/m3 5 mg/m3 15 mg/m3 10 mg/m3 15 mg/m3 15 mg/m3 5 PHYSIC : Solid : Pelle : ORA : Very	Exposure time Time Weighted Average (TWA): PEL: PEL: Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO t Evapor ts Specific NGE Bulk d faint Vapor	at machinery. Exposure type Total dust. Respirable dust. Total dust. Dust. Total dust. OPERTIES ration rate : Noic Gravity ic Gravity : No ensity : No pressure : No	List: ACGIH OSHA Z1 OSHA Z1 ACGIH OSHA Z1 t applicable. t determined t established t applicable	
Exposure limit(s) Components Calcium carbonate Calcium carbonate Titanium dioxide Titanium dioxide Form Appearance Color	aj Value 10 mg/m3 5 mg/m3 15 mg/m3 10 mg/m3 15 mg/m3 15 mg/m3 15 mg/m3 5 Pelle : ORA : Very : Not of	Exposure time Time Weighted Average (TWA): PEL: PEL: Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO t Evapor ts Specific NGE Bulk d faint Vapor	Exposure type Total dust. Respirable dust. Total dust. Dust. Total dust. OPERTIES ration rate : Noi ic Gravity : Noi ensity : No pressure : No density : No	List: ACGIH OSHA Z1 OSHA Z1 ACGIH OSHA Z1 t applicable. t determined t established	

10. STABILITY AND REACTIVITY

Stability

: Stable.

Hazardous Polymerization : Will not occur.

3/6



MATERIAL SAFETY DATA SHEET

ORANGE 172C

Revision Date 02/03/20	003		Page 4 of e Print Date 11/10/201
Conditions to avoid		from oxidizing agents an on, do not overheat.	nd open flame. To avoid thermal
Incompatible Materia	als : Incompatible	e with strong acids and o	oxidizing agents.
Hazardous decompos products			oxide (CO), oxides of nitrogen nd smoke are all possible.
	11. TOXICOLO	GICAL INFORMATIO	ON
Toxicity Overview			
This product contain			have the following characteristics:
This product contain CAS-No.	Chemical Name	Effect	Target Organ
This product contain		Effect Irritant	Target Organ Eyes, Skin.
This product contain CAS-No.	Chemical Name	Effect	Target Organ
CAS-No. 1317-65-3	Chemical Name Calcium carbonate Titanium dioxide	Effect Irritant Systemic effects	Target OrganEyes, Skin.Eyes, Skin, Respiratory system.Respiratory system.
CAS-No. 1317-65-3	Chemical Name Calcium carbonate Titanium dioxide 12. ECOLOGI	Effect Irritant Systemic effects Systemic effects	Target OrganEyes, Skin.Eyes, Skin, Respiratory system.Respiratory system.
CAS-No. 1317-65-3 13463-67-7	Chemical Name Calcium carbonate Titanium dioxide 12. ECOLOGI adability : Not readily	Effect Irritant Systemic effects Systemic effects CAL INFORMATION biodegradable. re not readily available a	Target OrganEyes, Skin.Eyes, Skin, Respiratory system.Respiratory system.

Additional advice	:	No data available.

13. DISPOSAL CONSIDERATIONS

Product: Like most thermoplastics the product can be recycled. Where
possible, recycling is preferred to disposal or incineration. The
generator of waste material has the responsibility for proper waste
classification, transportation and disposal in accordance with
applicable federal, state/provincial and local regulations.Contaminated packaging: Recycling is preferred when possible. The generator of waste material
has the responsibility for proper waste classification, transportation
and disposal in accordance with applicable federal, state/provincial
and local regulations.**I4. TRANSPORT INFORMATION**



MATERIAL SAFETY DATA SHEET

RANGE 172C	
rsion Number 1.0 vision Date 02/03/2003	Page 5 Print Date 11/10/2
U.S. DOT Classification	: Refer to specific regulation.
ICAO/IATA	: Refer to specific regulation.
IMO / IMDG	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardous	ubstances (40 CFR 302)
Not applicable	
65 Constitute Descriptions	
Canadian Regulations: WHMIS Classification	: D2A
DSL	 D2A All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.
National Inventories:	
Australia AICS	: Listed.
China IECS	: Listed.
Europe EINECS	: Not determined.
Japan ENCS	: Not determined.
Korea KECI	: Listed.
Philippines PICCS	: Listed.
	16. OTHER INFORMATION



MATERIAL SAFETY DATA SHEET

ORANGE 172C

Version Number 1.0 Revision Date 02/03/2003 Page 6 of 6 Print Date 11/10/2011

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.