

MATERIAL SAFETY DATA SHEET

TRANS GRAY V3

Version Number 1.0 Revision Date 02/10/2003 Page 1 of 6 Print Date 11/10/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	TRANS GRAY V3
Product code	:	CC10030944
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Carbon black	1333-86-4	0.1 - 1

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.



MATERIAL SAFETY DATA SHEET

TRANS GRAY V3

sion Number 1.0 ision Date 02/10/2003	Page 2 Print Date 11/10/2			
	4. FIRST AID MEASURES			
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.			
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.			
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for a least 15 minutes. If eye irritation persists, seek medical attention.			
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.			
5. FIRE-FIGHTING MEASURES				
Flash point	: Not applicable			
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	 Not applicable Not applicable Not relevant Carbon dioxide blanket, Water spray, dry powder, foam. 			
Special Fire Fighting Procedures	 Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. None 			
Unusual Fire/Explosion Hazards	. None			
6. ACCIDENTAL RELEASE MEASURES				
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.			
Environmental precautions	: Should not be released into the environment. The product should no be allowed to enter drains, water courses or the soil.			
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 1 of this MSDS for proper disposal methods.			
	7. HANDLING AND STORAGE			
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.			
Storage	: Keep containers dry and tightly closed to avoid moisture absorption			



MATERIAL SAFETY DATA SHEET

TRANS GRAY V3

Respiratory protection Eye/Face Protection Hand protection Skin and body protection Additional Protective Measures General Hygiene Considerations Engineering measures Exposure limit(s) Components Valu Carbon black 3.5 mg Q. PHT	URE CONT : No perso : Safety gl : Protectiv : Long slea : Safety sh : Handle ir Wash har : Heat only appropria	in accordance with good industrial hygiene and safety prac ands before breaks and at the end of workday. ly in areas with appropriate exhaust ventilation. Provide iate exhaust ventilation at machinery. <u>Exposure time Exposure type List</u> he Weighted Average Total dust. as carbon ACG (TWA): black		
Respiratory protection Eye/Face Protection Hand protection Skin and body protection Additional Protective Measures General Hygiene Considerations Engineering measures Exposure limit(s) Components Valu Carbon black 3.5 mg Q. PHT	 No perso Safety gl Protectiv Long sleet Safety sh Handle in Wash hand Heat only appropriate 	onal respiratory protective equipment normally required. glasses with side-shields. ve gloves. eeved clothing. hoes. in accordance with good industrial hygiene and safety pracands before breaks and at the end of workday. ly in areas with appropriate exhaust ventilation. Provide iate exhaust ventilation at machinery. Exposure time Exposure type List black Methods Use the state of the		
Eye/Face Protection Hand protection Skin and body protection Additional Protective Measures General Hygiene Considerations Engineering measures Exposure limit(s) Components Valu Carbon black 3.5 mg Q. PHT	 Safety gl Protectiv Long sleet Safety sh Handle in Wash han Heat only appropriate 	glasses with side-shields. ve gloves. eeved clothing. hoes. in accordance with good industrial hygiene and safety practands before breaks and at the end of workday. ly in areas with appropriate exhaust ventilation. Provide iate exhaust ventilation at machinery. Exposure time Exposure type List according to the formation of the second to		
Hand protection Skin and body protection Additional Protective Measures General Hygiene Considerations Engineering measures Exposure limit(s) Components Valu Carbon black 3.5 mg Qarbon black 3.5 mg	 Protectiv Long sleet Safety sh Handle ir Wash har Heat only appropria 	ve gloves. eeved clothing. hoes. in accordance with good industrial hygiene and safety prac ands before breaks and at the end of workday. ly in areas with appropriate exhaust ventilation. Provide iate exhaust ventilation at machinery. <u>Exposure time Exposure type List</u> a Weighted Average Total dust. as carbon ACG (TWA): black		
Skin and body protection Additional Protective Measures General Hygiene Considerations Engineering measures Exposure limit(s) Components Valu Carbon black 3.5 mg Carbon black 3.5 mg 9. PH	 Long sleet Safety sh Handle in Wash han Heat only appropriate 	eeved clothing. hoes. in accordance with good industrial hygiene and safety pracands before breaks and at the end of workday. ly in areas with appropriate exhaust ventilation. Provide iate exhaust ventilation at machinery. Exposure time Exposure type List text text text text text text text te		
Additional Protective Measures General Hygiene Considerations Engineering measures Exposure limit(s) Components Valu Carbon black 3.5 mg Quebook 3.5 mg 9. PH	 Safety sh Handle ir Wash hat Heat only appropria 	hoes. in accordance with good industrial hygiene and safety practands before breaks and at the end of workday. ly in areas with appropriate exhaust ventilation. Provide iate exhaust ventilation at machinery. Exposure time Exposure type List ist ist ist ist ist ist ist ist ist		
Measures General Hygiene Considerations Engineering measures Exposure limit(s) Components Valu Carbon black 3.5 mg Carbon black 3.5 mg 9. PH	: Handle ir Wash har : Heat only appropria e /m3 Time	in accordance with good industrial hygiene and safety prac ands before breaks and at the end of workday. ly in areas with appropriate exhaust ventilation. Provide iate exhaust ventilation at machinery. <u>Exposure time Exposure type List</u> he Weighted Average Total dust. as carbon ACG (TWA): black		
Considerations Engineering measures Exposure limit(s) Components Valu Carbon black 3.5 mg Carbon black 3.5 mg 9. PH	Wash han : Heat only appropria e /m3 Time	ands before breaks and at the end of workday. ly in areas with appropriate exhaust ventilation. Provide iate exhaust ventilation at machinery. Exposure time Exposure type List list list list list list list list l		
Exposure limit(s) Components Valu Carbon black 3.5 mg Carbon black 3.5 mg 9. PH	appropria e /m3 Time	Exposure timeExposure typeListne Weighted Average (TWA):Total dust. as carbon blackACGI		
ComponentsValuCarbon black3.5 mgCarbon black3.5 mg9. PH	/m3 Time	ne Weighted Average Total dust. as carbon ACG (TWA): black		
Carbon black 3.5 mg Carbon black 3.5 mg 9. PH	/m3 Time	ne Weighted Average Total dust. as carbon ACG (TWA): black		
Carbon black 3.5 mg 9. PH		(TWA): black		
9. PH	1 2			
	Carbon black 3.5 mg/m3 PEL: Total dust. as carbon black OSHA 2			
Form :	YSICAL AN	ND CHEMICAL PROPERTIES		
	Solid	Evaporation rate : Not applicabl		
Appearance :	Pellets	Specific Gravity : Not determine		
Color :	GREY	Bulk density : Not established		
	: Very faint Vapor pressure :			
61 6	: Not determined Vapor density : Not applicat			
	: Not applicable pH : Not applicable : Insoluble			
	<u>10. STABII</u>	LITY AND REACTIVITY		
Stability	: Stable.			
Hazardous Polymerization	: Will not	t occur.		
Conditions to avoid		way from oxidizing agents and open flame. To avoid therroristion, do not overheat.		
Incompatible Materials	: Incompa	atible with strong acids and oxidizing agents.		



MATERIAL SAFETY DATA SHEET

TRANS GRAY V3

Version Number 1.0 Revision Date 02/10/2003 Page 4 of 6 Print Date 11/10/2011

Hazardous decomposition products

: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1333-86-4	Carbon black	Systemic effects	Eyes, Respiratory system.

LC50 / LD50

This product contains the following components which in their pure form have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
1333-86-4	Carbon black	Oral LD50	>15,400 mg/kg	rat
		Dermal LD50	> 3 gm/kg	rabbit

Carcinogenicity:

This product contains the following components which in their pure form have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
1333-86-4	Carbon black	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

Additional Health Hazard Information:

Carbon black 1333-86-4 Carcinogenicity: Many inhalation toxicologists believe that the tumor response observed in the referenced rat studies is species specific and does not correlate to human exposure. However, the IARC evaluation in Monograph Volume 65, issued in April 1996 concluded that, "There is sufficient evidence in experimental animals for the carcinogenicity of carbon black". Based on this evaluation, along with their evaluation of inadequate evidence of carcinogenicity in humans, IARC's overall evaluation is that "Carbon Black is possibly carcinogenic to humans (Group 2B). Carbon Black has not been listed as a carcinogen by the National Toxicology Program (NTP) or the Occupational Safety and Health Administration (OSHA). The National Institute of Occupational Safety and Health (NIOSH) criteria document on carbon black recommends that only carbon black with PAH (polynuclear aromatic hydrocarbon) levels greater than 0.1% be considered suspect carcinogens.



MATERIAL SAFETY DATA SHEET

TRANS GRAY V3

sion Number 1.0 ision Date 02/10/2003	Page : Print Date 11/10/
	12. ECOLOGICAL INFORMATION
	12. ECOLOGICAL INFORMATION
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the matrix of the polymer.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the matrix of the polymer.
Additional advice	: No data available.
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastics the product can be recycled. Where possible, recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste materi has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Refer to specific regulation.
ICAO/IATA	: Refer to specific regulation.
IMO / IMDG	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSC Inventory.
US. EPA CERCLA Hazardous	Substances (40 CFR 302)
Not applicable	



MATERIAL SAFETY DATA SHEET

TRANS GRAY V3

Version Number 1.0 Revision Date 02/10/2003		Page 6 of 6 Print Date <i>11/10/2011</i>
California Proposition 65	:	This product does not contain a substance listed by California Prop 65.
SARA Title III Section 302 Extrem	me	ely Hazardous Substance
Not applicable		
SARA Title III Section 313 Toxic	c C	Chemicals:
	No	ot applicable
Canadian Regulations:		
WHMIS Classification	:	D2A
DSL	:	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.
National Inventories:		
Australia AICS	:	Listed.
China IECS	:	Listed.
Europe EINECS	:	Not determined.
Japan ENCS	:	Listed.
Korea KECI	:	Listed.
Philippines PICCS	:	Listed.
		16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.